

# Package ‘PHInfiniteEstimates’

June 26, 2022

**Type** Package

**Title** Tools for Inference in the Presence of a Monotone Likelihood

**Version** 2.5

**Date** 2022-06-25

**Author** John E. Kolassa and Juan Zhang

**Maintainer** John E. Kolassa <kolassa@stat.rutgers.edu>

**Description** Proportional hazards estimation in the presence of a partially monotone likelihood has difficulties, in that finite estimators do not exist. These difficulties are related to those arising from logistic and multinomial regression. References for methods are given in the separate function documents. Supported by grant NSF DMS 1712839.

**License** GPL-3

**Depends** survival, lpSolve, coxphf

**Suggests** KMsurv

**Imports** Rdpack (>= 0.7)

**RdMacros** Rdpack

**Encoding** UTF-8

**RoxygenNote** 7.1.2

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2022-06-26 21:20:10 UTC

## R topics documented:

|                                |   |
|--------------------------------|---|
| aalenjohansen . . . . .        | 2 |
| bestbeta . . . . .             | 3 |
| checkcensor . . . . .          | 4 |
| checkresults . . . . .         | 4 |
| compareplot . . . . .          | 5 |
| compete.simulation . . . . .   | 5 |
| convertbaselineltolr . . . . . | 6 |

|                                |           |
|--------------------------------|-----------|
| convertmtol . . . . .          | 7         |
| convertstoml . . . . .         | 8         |
| drawdiagram . . . . .          | 9         |
| fixcoxph . . . . .             | 10        |
| gehan.wilcoxon.test . . . . .  | 11        |
| heinzschemper . . . . .        | 11        |
| inference . . . . .            | 12        |
| network . . . . .              | 14        |
| newllk . . . . .               | 15        |
| PHInfiniteEstimates . . . . .  | 16        |
| pllk . . . . .                 | 17        |
| reduceLR . . . . .             | 18        |
| simcode . . . . .              | 19        |
| simultaneouscoverage . . . . . | 21        |
| summarizefits . . . . .        | 21        |
| summarizetable . . . . .       | 22        |
| testcox . . . . .              | 23        |
| voter.ml . . . . .             | 23        |
| <b>Index</b>                   | <b>24</b> |

---

|               |  |
|---------------|--|
| aalenjohansen | <i>Calculate the Aalen-Johansen (1978) estimate in the Competing risk context. See Aalen, Odd O., and Søren Johansen. "An Empirical Transition Matrix for Non-Homogeneous Markov Chains Based on Censored Observations." Scandinavian Journal of Statistics 5, no. 3 (1978): 141-50. Accessed January 15, 2021. <a href="http://www.jstor.org/stable/4615704">http://www.jstor.org/stable/4615704</a>.</i> |
|---------------|--|

---

## Description

Calculate the Aalen-Johansen (1978) estimate in the Competing risk context. See Aalen, Odd O., and Søren Johansen. "An Empirical Transition Matrix for Non-Homogeneous Markov Chains Based on Censored Observations." *Scandinavian Journal of Statistics* 5, no. 3 (1978): 141-50. Accessed January 15, 2021. <http://www.jstor.org/stable/4615704>.

## Usage

```
aalenjohansen(times, causes)
```

## Arguments

|        |  |
|--------|--|
| times  | Event times.   |
| causes | Causes, with 0 coded as censored, 1 as cause of interest, other for competing. |

**Value**

a list with components

- times Unique times
- surv Aalen-Johansen estimator for cause 1.

---

|          |   |
|----------|---|
| bestbeta | <i>Newton Raphson Fitter for partial likelihood</i> |
|----------|---|

---

**Description**

This function implements the approximate conditional inferential approach of Kolassa and Zhang (2019) to proportional hazards regression.

**Usage**

```
bestbeta(fit, exclude = NULL, start = NULL, touse = NA, usecc = FALSE)
```

**Arguments**

|         |   |
|---------|---|
| fit     | Output from a Cox PH regression, with x=TRUE and y=TRUE             |
| exclude | data set with stratum and patient number to exclude.                |
| start   | Starting value  |
| touse   | columns of the design matrix to use.                                |
| usecc   | Logical variable indicating whether to use a continuity correction. |

**Value**

Fitted survival analysis regression parameter of class coxph

**References**

Kolassa JE, Zhang J (2019). [https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB\\_Conference/Presentations/2019/kolassa\\_toxslides.pdf](https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB_Conference/Presentations/2019/kolassa_toxslides.pdf). Accessed: 2019-07-14.

**Examples**

```
bfit<-coxph(Surv(TIME,CENS)~T+N+CD,data=breast,x=TRUE)
bestbeta(bfit)
bestbeta(bfit,usecc=TRUE)
```

---

|             |   |
|-------------|---|
| checkcensor | <i>Check how censoring impacts sampling properties of KM fit and log rank test.</i> |
|-------------|---|

---

**Description**

Check how censoring impacts sampling properties of KM fit and log rank test.

**Usage**

```
checkcensor(nsamp = 1000, nobs = 1000)
```

**Arguments**

|       |                        |
|-------|------------------------|
| nsamp | Number of MC samples   |
| nobs  | Number of observations |

**Value**

biases of fits.

---

|              |  |
|--------------|--|
| checkresults | <i>Produce a graphical assessment of Monte Carlo experiment on fidelity of proportional hazards regression to the uniform ideal.</i> |
|--------------|--|

---

**Description**

This function draws a quantile plot for Monte Carlo assessments of fit to the corrected proportional hazards fit.

**Usage**

```
checkresults(regnsimulation, frac = 0.1)
```

**Arguments**

|                |  |
|----------------|--|
| regnsimulation | A structure with a component out, matrix with columns representing definitions of p-values and as many rows as there MC samples. |
| frac           | Proportion for bottom of distribution to be assessed.  |

**Value**

A list with components of consisting of simulated Wald p-values, likelihood ratio p-values, and corrected likelihood ratio p-values.

---

|             |                                |
|-------------|--------------------------------|
| compareplot | <i>Plot results of simcode</i> |
|-------------|--------------------------------|

---

**Description**

Plot results of simcode

**Usage**

```
compareplot(simresults)
```

**Arguments**

simresults      the result of simcode

**Value**

nothing.

---

|                    |  |
|--------------------|--|
| compete.simulation | <i>Simulate from a competing risk model with correlated log normal errors, and plot various estimates.</i> |
|--------------------|--|

---

**Description**

Simulate from a competing risk model with correlated log normal errors, and plot various estimates.

**Usage**

```
compete.simulation(ncr = 4, sig = 0.8, ns = 1000)
```

**Arguments**

ncr              Number of competing risks.  
sig              correlation among competing risks.  
ns                number of observations.

---

convertbaselineltolr *Convert a baseline logit model data set, formatted in the long form as described in the documentation for mlogit.data from mlogit package, to a conditional logistic regression.*

---

### Description

Convert a baseline logit model data set, formatted in the long form as described in the documentation for mlogit.data from mlogit package, to a conditional logistic regression.

### Usage

```
convertbaselineltolr(dataset, choice, covs, strs = "chid", alt = "alt")
```

### Arguments

|         |  |
|---------|--|
| dataset | in formatted as in the output from mlogit.data of the mlogit packages  |
| choice  | name of variable in dataset representing choice, a logical variable indicating whether this choice is actually chosen. |
| covs    | vector of names of covariates  |
| strs    | name of variable in data set indicating independent subject  |
| alt     | name of variable in data set indicating potential choice.  |

### Details

This function implements version of (Kolassa 2016). The multinomial regression is converted to a conditional logistic regression, and methods of (Kolassa 1997) may be applied. This function differs from convertmtol of this package in that convertmtol treats a less-rich data structure, and this function treats the richer data structure that is an output of mlogit.data from package mlogit. Data in the example is from Sanders et al. (2007).

### Value

a data set on which to apply conditional logistic regression, corresponding to the baseline logit model.

### References

Sanders DJ, Whiteley PF, Clarke HD, Stewart M, Winters K (2007). "The British Election Study." <https://www.britishelectionstudy.com>.

Kolassa JE (1997). "Infinite Parameter Estimates in Logistic Regression." *Scandinavian Journal of Statistics*, **24**, 523–530. doi: [10.1111/14679469.00078](https://doi.org/10.1111/14679469.00078).

Kolassa JE (2016). "Inference in the Presence of Likelihood Monotonicity for Polytomous and Logistic Regression." *Advances in Pure Mathematics*, **6**, 331-341. doi: [10.4236/apm.2016.65024](https://doi.org/10.4236/apm.2016.65024).

**Examples**

```

data(voter.ml)
covs<-c("Labor","Liberal.Democrat","education")
#Fit the multinomial regression model, for comparison purposes.
## Lines beginning ## give mlogit syntax that has been made obsolete.
#Add the index attribute to the data set, giving the index of choice made and the index of the
#alternative, and a boolean variable giving choice.
##attributes(voter.ml)$index<-voter.ml[,c("chid","alt")]
##attributes(voter.ml)$choice<-"voter"
##mlogit(voter~1|Labor+Liberal.Democrat+education,data=voter.ml)
# The package mlogit is scheduled for archiving. If it is available, the
# next two lines fit the model using mlogit.
# mlogit(voter~1|Labor+Liberal.Democrat+education,data=voter.ml,
#   chid.var = "chid", alt.var = "alt")
#Convert to a data set allowing treatment as the equivalent conditional logistic regression.
#This result will be processed using reduceLR of this package to give an equivalent conditional
# regression model avoiding infinite estimates.
out<-convertbaselineltolr(voter.ml,"voter",c("Labor","Liberal.Democrat","education"))
#Fit the associated unconditional logistic regression for comparison purposes.
glm(out[, "y"]~out[,1:75],family=binomial)

```

---

convertmtol

---

*Convert a polytomous regression to a conditional logistic regression.*


---

**Description**

Convert a polytomous regression to a conditional logistic regression.

**Usage**

```
convertmtol(xmat, str, yvec, subjects)
```

**Arguments**

|          |   |
|----------|---|
| xmat     | regression matrix                                       |
| str      | stratum label   |
| yvec     | vector of responses                                     |
| subjects | vector of subject labels passed directly to the output. |

**Details**

Implements version of (Kolassa 2016). The multinomial regression is converted to a conditional logistic regression, and methods of (Kolassa 1997) may be applied. This function differs from `convertbaselineltolr` of this package in that the former treats the richer data structure of package `mlogit`, and this function treats a less complicated structure. Data in the example is the breast cancer data set `breast` of package `coxphf`.

**Value**

a data set on which to apply conditional logistic regression, corresponding to the multinomial regression model.

**References**

Kolassa JE (1997). “Infinite Parameter Estimates in Logistic Regression.” *Scandinavian Journal of Statistics*, **24**, 523–530. doi: [10.1111/14679469.00078](https://doi.org/10.1111/14679469.00078).

Kolassa JE (2016). “Inference in the Presence of Likelihood Monotonicity for Polytomous and Logistic Regression.” *Advances in Pure Mathematics*, **6**, 331-341. doi: [10.4236/apm.2016.65024](https://doi.org/10.4236/apm.2016.65024).

**Examples**

```
#Uses data set breast from package coxphf.
data(breast)
out<-convertstoml(Surv(breast$TIME,breast$CENS),breast[,c("T","N","G","CD")])
out1<-convertmtol(out[,c("T","N","G","CD")],out[, "chid"],out[, "choice"],
  out[, "patients"])
glmout<-glm.fit(out1$xmat,out1$y,family=binomial())
#In many practice examples, the following line shows which observations to retain
#in the logistic regression example.
moderate<-(fitted(glmout)<1-1.0e-8)&(fitted(glmout)>1.0e-8)
# Proportional hazards fit illustrating infinite estimates.
coxph(Surv(TIME,CENS)~ T+ N+ G+ CD,data=breast)
# Wrong analysis naively removing covariate with infinite estimate
coxph(Surv(TIME,CENS)~ T+ N+ CD,data=breast)
summary(glm((CENS>22)~T+N+G+CD,family=binomial,data=breast))

out2<-reduceLR(out1$xmat,yvec=out1$y,keep="CD")
bestcoxout<-coxph(Surv(TIME,CENS)~ T+ N+ G+ CD,data=breast,
  subset=as.numeric(unique(out1$subjects[out2$moderate])))
```

---

convertstoml

*Convert a proportional hazards regression to a multinomial regression.*

---

**Description**

Convert a proportional hazards regression to a multinomial regression.

**Usage**

```
convertstoml(survobj, covmat)
```

**Arguments**

survobj      A survival object, with potentially right censoring.  
 covmat      a matrix of covariates.



## Details

Implements version of (Kolassa and Zhang 2019). The proportional hazards regression is converted to a multinomial regression logistic regression, and methods of (Kolassa 2016) may be applied. This function is intended to produce intermediate results to be passed to `convertmto1`, and then to `reducelR` of (Kolassa 1997). See examples in the `convertmto1` documentation.

## Value

a data set on which to apply conditional multinomial regression, corresponding to the proportional hazards regression analysis. In order to run the line commented out below, you would need this: `# @importFrom mlogit mlogit.data`

## References

Kolassa JE (1997). “Infinite Parameter Estimates in Logistic Regression.” *Scandinavian Journal of Statistics*, **24**, 523–530. doi: [10.1111/14679469.00078](https://doi.org/10.1111/14679469.00078).

Kolassa JE (2016). “Inference in the Presence of Likelihood Monotonicity for Polytomous and Logistic Regression.” *Advances in Pure Mathematics*, **6**, 331-341. doi: [10.4236/apm.2016.65024](https://doi.org/10.4236/apm.2016.65024).

Kolassa JE, Zhang J (2019). [https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB\\_Conference/Presentations/2019/kolassa\\_toxslides.pdf](https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB_Conference/Presentations/2019/kolassa_toxslides.pdf). Accessed: 2019-07-14.

---

drawdiagram

*Draw diagram for toy PH example.*

---

## Description

Draw diagram for toy PH example.

## Usage

```
drawdiagram()
```

## Value

nothing.

---

|          |   |
|----------|---|
| fixcoxph | <i>Remove observations from a proportional hazards regression, and return the fit of the reduced model.</i> |
|----------|---|

---

### Description

This function implements the approximate conditional inferential approach of Kolassa and Zhang (2019) to proportional hazards regression.

### Usage

```
fixcoxph(randdat, xxx, iv, verbose = FALSE)
```

### Arguments

|         |   |
|---------|---|
| randdat | A list with at least the component y, representing the Surv() object. I expect that this will be output from an initial non-convergent regression.          |
| xxx     | a design matrix for the regression. I expect that this will be the \$x component of the output from an initial non-convergent regression, run with x=TRUE . |
| iv      | name of the variable of interest, as a character string   |
| verbose | logical flag governing printing.  |

### Value

Fitted survival analysis regression parameter of class coxph, fitted form data set with observations forcing infinite estimation removed.

### References

Kolassa JE, Zhang J (2019). [https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB\\_Conference/Presentations/2019/kolassa\\_toxslides.pdf](https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB_Conference/Presentations/2019/kolassa_toxslides.pdf). Accessed: 2019-07-14.

### Examples

```
data(breast) # From library coxphf
bcfit<-coxph(Surv(TIME,CENS)~ T+ N+ G+ CD,data=breast,x=TRUE)

fixcoxph(bcfit,bcfit$x,"T",Surv(TIME,CENS)~ T+ N+ G+ CD)

testdat2 <- data.frame(Time=c(4,3,1,1,2,2,3),
  Cen=c(1,1,1,0,0,0,0), Primary=c(0,2,1,1,1,0,0), Sex=c(0,0,0,0,1,1,1))
(bcfit<-coxph(Surv(Time,Cen)~Primary + Sex, testdat2, x=TRUE, ties="breslow"))
fixcoxph(bcfit,bcfit$x,"Primary")
```

---

gehan.wilcoxon.test     *Perform Gehan's application to the Wilcoxon test for multiple samples, testing for equivalence of survival curve. See Klein and Moeschberger (1997) Survival Analysis (7.3.3) and pp. 193-194.*

---

### Description

Perform Gehan's application to the Wilcoxon test for multiple samples, testing for equivalence of survival curve. See Klein and Moeschberger (1997) Survival Analysis (7.3.3) and pp. 193-194.

### Usage

```
gehan.wilcoxon.test(myformula, data, gehan = TRUE, plot = FALSE, alpha = 0.05)
```

### Arguments

|           |   |
|-----------|---|
| myformula | Proportional hazards formula appropriate for survfit  |
| data      | the data set  |
| gehan     | logical flag triggering the Wilcoxon test (gehan=TRUE), with weights equal to total at risk, or the log rank test (gehan=FALSE) with weights all 1. |
| plot      | logical flag triggering plotting.   |
| alpha     | Nominal test level for plotting on graph  |

### Value

An htest-like object with the chi-square version of the test.

### Examples

```
data(breast)#From package coxphf
gehan.wilcoxon.test(Surv(TIME,CENS)~G,data=breast)
```

---

heinzschemper     *Simulate operating characteristics of repaired Cox regression and competitors.*

---

### Description

This function is intended to verify the operating characteristics of the approximate conditional inferential approach of Kolassa and Zhang (2019) to proportional hazards regression. An exponential regression model, corresponding to the proportional hazards regression model, is fit to the data, and new data sets are simulated from this model. P-values are calculated for these new data sets, and their empirical distribution is compared to the theoretical uniform distribution.

**Usage**

```

heinzschemper(
  nobs = 50,
  k = 5,
  B = 1,
  c = 0,
  nsamp = 1000,
  beta = NULL,
  add = NULL,
  half = NULL,
  verbose = FALSE,
  smoothfirst = FALSE
)

```

**Arguments**

|             |   |
|-------------|---|
| nobs        | number of observations in simulated data set.                                 |
| k           | number of covariates in simulated data set. Each covariate is dichotomous.    |
| B           | odds of 1 vs. 0 in dichotomous variables.                                     |
| c           | censoring proportion.   |
| nsamp       | number of samples.  |
| beta        | regression parameters, all zeros if null, and all the same value if a scalar. |
| add         | partial simulation results to be added to, or NULL if de novo.                |
| half        | does nothing; provided for compatibility with simcode.                        |
| verbose     | Triggers verbose messages.  |
| smoothfirst | Triggers normal rather than dichotomous interest covariate.                   |

**Value**

a list with components

- out matrix with columns corresponding to p-values.

---

inference

---

*Perform inference on conditional sample space.*


---

**Description**

This function performs classical frequentist statistical inference to a discrete multivariate canonical exponential family. It produces the maximum likelihood estimator, one- and two-sided p-values for the test that model parameters are zero, and providing confidence intervals for the parameters. The discrete probability model is given by a set of possible values of the random vectors, and null weights for these vectors. Such a discrete probability model arises in logistic regression, and this function is envisioned to be applied to the results of a network algorithm for conditional logistic regression. Examples apply this to data from Hirji et al. (1987), citing Goorin et al. (1987).

**Usage**

```
inference(out, alpha = 0.05, rng = c(-5, 5))
```

**Arguments**

|       |  |
|-------|--|
| out   | List of the sort provided by network. <ul style="list-style-type: none"> <li>• possible matrix with vectors of possible unconditioned values of the sufficient statistic.</li> <li>• count count of entries in the conditional distribution.</li> <li>• obsd Observed value of unconditioned sufficient statistics.</li> </ul> |
| alpha | Test level, or 1- confidence level.  |
| rng   | Range of possible parameter values.  |

**Value**

List with components:

- ospv Observed one-sided p values
- tspv Observed two-sided p value.
- ci confidence interval.
- mle Maximum likelihood estimator.

**References**

Hirji KF, Mehta CR, Patel NR (1987). “Computing Distributions for Exact Logistic Regression.” *Journal of the American Statistical Association*, **82**(400), pp. 1110-1117. ISSN 01621459, doi: [10.2307/2289388](https://doi.org/10.2307/2289388).

Goorin AM, Perez-Atayde A, Gebhardt M, Andersen J (1987). “Weekly High-Dose Methotrexate and Doxorubicin for Osteosarcoma: The Dana-Farber Cancer Institute/The Children’s Hospital – Study III.” *Journal of Clinical Oncology*. doi: [10.1200/JCO.1987.5.8.1178](https://doi.org/10.1200/JCO.1987.5.8.1178).

**Examples**

```
#Columns in table are:
# Lymphocytic Infiltration (1=low, 0=high)
# Sex (1=male, 0=female)
# Any Ostioid Pathology (1=yes, 0=no)
# Number in LI-Sex-AOP group
# Number in LI-Sex-AOP group with disease free interval greater than 3 y
goorin<-data.frame(LI=c(0,0,0,0,1,1,1,1),Sex=c(0,0,1,1,0,0,1,1),
  AOP=c(0,1,0,1,0,1,0,1),N=c(3,2,4,1,5,5,9,17),Y=c(3,2,4,1,5,3,5,6))

out<-network(goorin[,1:3],goorin[,4],conditionon=1:3,resp=goorin[,5])
inference(out)
```

---

|         |  |
|---------|--|
| network | <i>This function enumerates conditional sample spaces associated with logistic regression,</i> |
|---------|--|

---

### Description

This function uses a network algorithm to enumerate conditional sample spaces associated with logistic regression, using a minimal version of the algorithm of Hirji et al. (1987).

### Usage

```
network(
  dm,
  n = NULL,
  resp = NULL,
  conditionon = NULL,
  sst = NULL,
  addint = TRUE,
  verbose = FALSE
)
```

### Arguments

|             |  |
|-------------|--|
| dm          | matrix of covariates   |
| n           | Vector of number of trials. If null, make them all ones.   |
| resp        | vector of successes. Used only to calculate the sufficient statistics, unless sufficient statistics are entered directly. Either resp or sst must be provided. |
| conditionon | indices of covariate matrix indicating sufficient statistics to be conditioned on.   |
| sst         | sufficient statistic vector, if input directly. Otherwise, recomputed from resp.   |
| addint      | logical, true if a column of 1s must be added to the covariate matrix.   |
| verbose     | logical; if true, print intermediate results.  |

### Details

Examples apply this to data from Hirji et al. (1987), citing Goorin et al. (1987).

### Value

For a successful run, a list with components:

- possible matrix with vectors of possible unconditioned values of the sufficient statistic.
- count count of entries in the conditional distribution.
- obsd Observed value of unconditioned sufficient statistics.

For an unsuccessful run (because of input inconsistencies) NA

## References

Hirji KF, Mehta CR, Patel NR (1987). “Computing Distributions for Exact Logistic Regression.” *Journal of the American Statistical Association*, **82**(400), pp. 1110-1117. ISSN 01621459, doi: [10.2307/2289388](https://doi.org/10.2307/2289388).

Goorin AM, Perez–Atayde A, Gebhardt M, Andersen J (1987). “Weekly High–Dose Methotrexate and Doxorubicin for Osteosarcoma: The Dana–Farber Cancer Institute/The Children’s Hospital – Study III.” *Journal of Clinical Oncology*. doi: [10.1200/JCO.1987.5.8.1178](https://doi.org/10.1200/JCO.1987.5.8.1178).

## Examples

```
#Columns in table are:
# Lymphocytic Infiltration (1=low, 0=high)
# Sex (1=male, 0=female)
# Any Ostioid Pathology (1=yes, 0=no)
# Number in LI-Sex-AOP group
# Number in LI-Sex-AOP group with disease free interval greater than 3 y
goorin<-data.frame(LI=c(0,0,0,0,1,1,1,1),Sex=c(0,0,1,1,0,0,1,1),
  AOP=c(0,1,0,1,0,1,0,1),N=c(3,2,4,1,5,5,9,17),Y=c(3,2,4,1,5,3,5,6))

out<-network(goorin[,1:3],goorin[,4],conditionon=1:3,resp=goorin[,5])
inference(out)
```

---

newllk

*Proportional hazards partial likelihood, using Breslow method for ties, excluding some observations.*

---

## Description

This function implements the approximate conditional inferential approach of Kolassa and Zhang (2019) to proportional hazards regression.

## Usage

```
newllk(
  beta,
  fit,
  exclude = NULL,
  minus = FALSE,
  keeponly = NULL,
  justd0 = FALSE,
  cc1 = 0
)
```

**Arguments**

|          |   |
|----------|---|
| beta     | parameter vector.   |
| fit      | Output from a Cox PH regression, with x=TRUE and y=TRUE   |
| exclude  | data set with stratum and patient number to exclude.  |
| minus    | logical flag to change sign of partial likelihood   |
| keeponly | variables to retain. Keep all if this is null or NA.  |
| justd0   | logical variable, indicating whether to calculate only the function value and skip derivatives. |
| cc1      | Continuity correction for first component of the score.   |

**Value**

a list with components

- d0 partial likelihood
- d1 first derivative vector
- d2 second derivative matrix

**References**

Kolassa JE, Zhang J (2019). [https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB\\_Conference/Presentations/2019/kolassa\\_toxslides.pdf](https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB_Conference/Presentations/2019/kolassa_toxslides.pdf). Accessed: 2019-07-14.

---

PHInfiniteEstimates    *PHInfiniteEstimates: Tools for Proportional Hazards Estimation, and Inference on the Associate Parameters, when Other Parameters are Estimated at Infinity.*

---

**Description**

The PHInfiniteEstimates package Proportional hazards estimation in the presence of partial likelihood monotonicity has difficulties, in that finite estimators do not exist. These difficulties are related to those arising from logistic regression, addressed by (Kolassa 1997), and multinomial regression, addressed by (Kolassa 2016). Algorithms to provide conditionally similar problems in these contexts are provided.

**References**

- Kolassa JE (1997). “Infinite Parameter Estimates in Logistic Regression.” *Scandinavian Journal of Statistics*, **24**, 523–530. doi: [10.1111/14679469.00078](https://doi.org/10.1111/14679469.00078).
- Kolassa JE (2016). “Inference in the Presence of Likelihood Monotonicity for Polytomous and Logistic Regression.” *Advances in Pure Mathematics*, **6**, 331-341. doi: [10.4236/apm.2016.65024](https://doi.org/10.4236/apm.2016.65024).



---

p11k *Partial likelihood for proportional hazards*

---

## Description

Partial likelihood for proportional hazards

## Usage

```
p11k(beta, xmat, ind, cc = NULL)
```

## Arguments

|      |   |
|------|---|
| beta | parameter vector  |
| xmat | regression matrix   |
| ind  | censoring indicator, 1 for event and any other value otherwise.   |
| cc   | Continuity correction for sum of x vectors with multiple occurrences in risk set. For binary covariates is half. Default a vector of zeros. |

## Value

a list with components

- d0 partial likelihood
- d1 first derivative vector
- d2 second derivative matrix

## Examples

```
#Uses data set breast from package coxphf.  
data(breast)  
xmat<-as.matrix(breast)[order(breast$TIME),c("T", "N")]  
ind<-breast$CENS[order(breast$TIME)]  
short<-coxph(Surv(TIME, CENS)~ T+ N, data=breast)  
p11k(as.vector(coef(short)), xmat, ind)
```

---

|          |   |
|----------|---|
| reduceLR | <i>Reduce a logistic regression with monotone likelihood to a conditional regression with double descending likelihood.</i> |
|----------|---|

---

**Description**

Reduce a logistic regression with monotone likelihood to a conditional regression with double descending likelihood.

**Usage**

```
reduceLR(Z, nvec = NULL, yvec = NULL, keep, sst = NULL, verybig = 1e+07)
```

**Arguments**

|         |   |
|---------|---|
| Z       | regression matrix   |
| nvec    | vector of sample sizes  |
| yvec    | vector of responses   |
| keep    | vector of variable names to block from consideration for removal. |
| sst     | vector of sufficient statistics                                   |
| verybig | threshold for condition number to declare colinearity.            |

**Details**

This function implements version of Kolassa (1997). It is intended for use with extensions to multinomial regression as in Kolassa (1997) and to survival analysis as in Kolassa and Zhang (2019). The method involves linear optimization that is potentially repeated. Initial calculations were done using a proprietary coding of the simplex, in a way that allowed for later iterations to be restarted from earlier iterations; this computational advantage is not employed here, in favor of computational tools in the public domain and included in the R package IpSolve. Furthermore, Kolassa (1997) removed regressors that became linearly dependent using orthogonalization, but on further reflection this computation is unnecessary. Data in the examples are from Hirji et al. (1987), citing Goorin et al. (1987).

**Value**

a list with components

- keepme indicators of which variables are retained in the reduced data set
- moderate indicators of which observations are retained in the reduced data set
- extreme indicators of which observations are removed in the reduced data set
- toosmall indicator of whether resulting data set is too small to fit the proportional hazards regression

## References

Hirji KF, Mehta CR, Patel NR (1987). “Computing Distributions for Exact Logistic Regression.” *Journal of the American Statistical Association*, **82**(400), pp. 1110-1117. ISSN 01621459, doi: [10.2307/2289388](https://doi.org/10.2307/2289388).

Goorin AM, Perez-Atayde A, Gebhardt M, Andersen J (1987). “Weekly High-Dose Methotrexate and Doxorubicin for Osteosarcoma: The Dana-Farber Cancer Institute/The Children’s Hospital – Study III.” *Journal of Clinical Oncology*. doi: [10.1200/JCO.1987.5.8.1178](https://doi.org/10.1200/JCO.1987.5.8.1178).

Kolassa JE (1997). “Infinite Parameter Estimates in Logistic Regression.” *Scandinavian Journal of Statistics*, **24**, 523–530. doi: [10.1111/14679469.00078](https://doi.org/10.1111/14679469.00078).

Kolassa JE (2016). “Inference in the Presence of Likelihood Monotonicity for Polytomous and Logistic Regression.” *Advances in Pure Mathematics*, **6**, 331-341. doi: [10.4236/apm.2016.65024](https://doi.org/10.4236/apm.2016.65024).

Kolassa JE, Zhang J (2019). [https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB\\_Conference/Presentations/2019/kolassa\\_toxslides.pdf](https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB_Conference/Presentations/2019/kolassa_toxslides.pdf). Accessed: 2019-07-14.

## Examples

```
#Cancer Data
Z<-cbind(rep(1,8),c(rep(0,4),rep(1,4)),rep(c(0,0,1,1),2),rep(c(0,1),4))
dimnames(Z)<-list(NULL,c("1","LI","SEX","AOP"))
nvec<-c(3,2,4,1,5,5,9,17); yvec<-c(3,2,4,1,5,3,5,6)
reduceLR(Z,nvec,yvec,c("SEX","AOP"))
#CD4, CD8 data
Z<-cbind(1,c(0,0,1,1,0,0,1,0),c(0,0,0,0,1,1,0,1),c(0,0,0,0,0,1,1,0),c(0,1,0,1,0,0,0,1))
dimnames(Z)<-list(NULL,c("1","CD41","CD42","CD81","CD82"))
nvec<-c(7,1,7,2,2,13,12,3); yvec<-c(4,1,2,2,0,0,4,1)
reduceLR(Z,nvec,yvec,"CD41")
```

---

simcode

*Simulate Weibull survival data from a model, perform reduction to remove infinite estimates, and calculate p values.*

---

## Description

Operating characteristics for the approximate conditional inferential approach to proportional hazards.

## Usage

```
simcode(
  dataset,
  myformula,
  iv,
  ctime,
  nsamp = 10000,
  add = NULL,
```

```

nobs = NA,
half = FALSE,
verbose = FALSE
)

```

### Arguments

|           |  |
|-----------|--|
| dataset   | the data set to use  |
| myformula | the formula for the Cox regression   |
| iv        | name of the variable of interest, as a character string  |
| ctime     | fixed censoring time   |
| nsamp     | number of samples.   |
| add       | preliminary results, if any.   |
| nobs      | number of observations in target models, if different from that of dataset.                              |
| half      | logical flag triggering a less extreme simulation by dividing the Weibull regression parameters in half. |
| verbose   | logical flag triggering intermediate messaging.  |

### Details

This function is intended to verify the operating characteristics of the approximate conditional inferential approach of Kolassa and Zhang (2019) to proportional hazards regression. A Weibull regression model, corresponding to the proportional hazards regression model, is fit to the data, and new data sets are simulated from this model. P-values are calculated for these new data sets, and their empirical distribution is compared to the theoretical uniform distribution.

### Value

a list with components

- out matrix with columns corresponding to p-values.
- seed random seed
- bad unused.
- srreg parametric lifetime regression

### References

Kolassa JE, Zhang J (2019). [https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB\\_Conference/Presentations/2019/kolassa\\_toxslides.pdf](https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB_Conference/Presentations/2019/kolassa_toxslides.pdf). Accessed: 2019-07-14.

### Examples

```
data(breast)
```

```
breasttestp<-simcode(breast,Surv(TIME,CENS)~ T+ N+ G+ CD,"T",72,nsamp=100,verbose=TRUE)
```

---

simultaneouscoverage    *Calculate simultaneous coverage of pointwise confidence intervals.*

---

**Description**

Simulate exponential event times with expectation 1. Simulate censoring times with expectation 2. Calculate confidence intervals and check simultaneous coverage.

**Usage**

```
simultaneouscoverage(nsamp, nobs)
```

**Arguments**

|       |                                    |
|-------|------------------------------------|
| nsamp | Number of Monte Carlo samples.     |
| nobs  | Number of observations per sample. |

**Value**

Simultaneous coverage proportion.

**Examples**

```
simultaneouscoverage(1000,20)
```

---

summarizefits    *Summarize proportional hazards fits*

---

**Description**

Summarize proportional hazards fits

**Usage**

```
summarizefits(  
  repairedfit,  
  penalizedout,  
  penalizedoutsmaller,  
  iv,  
  verbose = TRUE  
)
```

**Arguments**

|                     |   |
|---------------------|---|
| repairedfit         | coxph fit   |
| penalizedout        | coxphf fit  |
| penalizedoutsmaller | smaller coxphf fit                                      |
| iv                  | name of the variable of interest, as a character string |
| verbose             | logical flag triggering intermediate messaging.         |

**Value**

a vector with components

- Wald p-value from the Cox regression fit.
- partial likelihood ratio p-value from Cox regression fit.
- parameter estimate from the Cox regression fit.
- standard error from the Cox regression fit.
- Conditional Skovgaard standard error from the Cox regression fit.
- Signed root of the partial likelihood ratio statistic from Cox regression fit.
- partial likelihood ratio statistic p-value from coxphf
- Wald p-value from coxphf
- parameter estimate from coxphf
- standard error from coxphf
- number of parameters in reduced fit.

**References**

Kolassa JE, Zhang J (2019). [https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB\\_Conference/Presentations/2019/kolassa\\_toxslides.pdf](https://higherlogicdownload.s3.amazonaws.com/AMSTAT/fa4dd52c-8429-41d0-abdf-UploadedImages/NCB_Conference/Presentations/2019/kolassa_toxslides.pdf). Accessed: 2019-07-14.

---

|                |   |
|----------------|---|
| summarizetable | <i>Summarize the results of simulations investigating operating conditions for the data reduction method to avoid monotone likelihood. Files are of form "hsxxx", for xxx numerals.</i> |
|----------------|---|

---

**Description**

Summarize the results of simulations investigating operating conditions for the data reduction method to avoid monotone likelihood. Files are of form "hsxxx", for xxx numerals.

**Usage**

```
summarizetable()
```

---

|         |   |
|---------|---|
| testcox | <i>Test size of asymptotic Cox tests.</i> |
|---------|---|

---

**Description**

Test size of asymptotic Cox tests.

**Usage**

```
testcox(nsamp = 1000, nobs = 50, ncov = 5, randomcov = TRUE)
```

**Arguments**

|           |   |
|-----------|---|
| nsamp     | Number of MC samples                            |
| nobs      | Number of observations                          |
| ncov      | Number of covariates                            |
| randomcov | Indicator of whether to draw random covariates. |

**Value**

level of two-sided test of nominal size 0.05.

---

|          |  |
|----------|--|
| voter.ml | <i>Subset of British elections data used in (Kolassa 2016). Data are from (Sanders et al. 2007).</i> |
|----------|--|

---

**Description**

Subset of British elections data used in (Kolassa 2016). Data are from (Sanders et al. 2007).

**Usage**

```
data(voter.ml)
```

**References**

Sanders DJ, Whiteley PF, Clarke HD, Stewart M, Winters K (2007). “The British Election Study.” <https://www.britishelectionstudy.com>.

Kolassa JE (2016). “Inference in the Presence of Likelihood Monotonicity for Polytomous and Logistic Regression.” *Advances in Pure Mathematics*, **6**, 331-341. doi: [10.4236/apm.2016.65024](https://doi.org/10.4236/apm.2016.65024).

**Examples**

```
data(voter.ml)
```

# Index

`aalenjohansen`, [2](#)  
`bestbeta`, [3](#)  
`checkcensor`, [4](#)  
`checkresults`, [4](#)  
`compareplot`, [5](#)  
`compete.simulation`, [5](#)  
`convertbaselineltolr`, [6](#)  
`convertmtol`, [7](#)  
`convertstoml`, [8](#)  
`drawdiagram`, [9](#)  
`fixcoxph`, [10](#)  
`gehan.wilcoxon.test`, [11](#)  
`heinzschemper`, [11](#)  
`inference`, [12](#)  
`network`, [14](#)  
`newllk`, [15](#)  
`PHInfiniteEstimates`, [16](#)  
`pllk`, [17](#)  
`reduceLR`, [18](#)  
`simcode`, [19](#)  
`simultaneouscoverage`, [21](#)  
`summarizefits`, [21](#)  
`summarizetable`, [22](#)  
`testcox`, [23](#)  
`voter.ml`, [23](#)