

Package ‘RNOMni’

October 5, 2020

Title Rank Normal Transformation Omnibus Test

Version 1.0.0

Date 2020-10-04

Description Inverse normal transformation (INT) based genetic association testing. These tests are recommended for continuous traits with non-normally distributed residuals. INT-based tests robustly control the type I error in settings where standard linear regression does not, as when the residual distribution exhibits excess skew or kurtosis. Moreover, INT-based tests dominate standard linear regression in terms of power. These tests may be classified into two types. In direct INT (D-INT), the phenotype is itself transformed. In indirect INT (I-INT), phenotypic residuals are transformed. The omnibus test (O-INT) adaptively combines D-INT and I-INT into a single robust and statistically powerful approach. See McCaw ZR, Lane JM, Saxena R, Redline S, Lin X. ``Operating characteristics of the rank-based inverse normal transformation for quantitative trait analysis in genome-wide association studies'' <doi:10.1111/biom.13214>.

Depends R (>= 3.2.2)

Imports plyr, Rcpp, stats

LinkingTo Rcpp, RcppArmadillo

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Suggests R.rsp

VignetteBuilder R.rsp

NeedsCompilation yes

Author Zachary McCaw [aut, cre] (<<https://orcid.org/0000-0002-2006-9828>>)

Maintainer Zachary McCaw <zmccaw@alumni.harvard.edu>

Repository CRAN

Date/Publication 2020-10-05 16:40:02 UTC

R topics documented:

BasicInputChecks	2
BAT	3
BAT.ScoreTest	4
BAT.WaldTest	4
CauchyToP	5
DINT	5
fitOLS	6
IINT	7
IINT.ScoreTest	8
matInv	9
matIP	9
OINT	10
OmniP	11
PartitionData	11
PtoCauchy	12
RankNorm	12
RNOmni-help	13
SchurC	13
ScoreStat	14
WaldStat	14
Index	15

BasicInputChecks *Basic Input Checks*

Description

Basic Input Checks

Usage

```
BasicInputChecks(y, G, X)
```

Arguments

- y Numeric phenotype vector.
- G Genotype matrix with observations as rows, SNPs as columns.
- X Covariate matrix.

BAT*Basic Association Test*

Description

Conducts tests of association between the loci in G and the untransformed phenotype y, adjusting for the model matrix X.

Usage

```
BAT(y, G, X = NULL, test = "Score", simple = FALSE)
```

Arguments

y	Numeric phenotype vector.
G	Genotype matrix with observations as rows, SNPs as columns.
X	Model matrix of covariates and structure adjustments. Should include an intercept. Omit to perform marginal tests of association.
test	Either Score or Wald.
simple	Return the p-values only?

Value

If `simple` = TRUE, returns a vector of p-values, one for each column of G. If `simple` = FALSE, returns a numeric matrix, including the Wald or Score statistic, its standard error, the Z-score, and the p-value.

See Also

- Direct INT [DINT](#)
- Indirect INT [IINT](#)
- Omnibus INT [OINT](#)

Examples

```
set.seed(100)
# Design matrix
X <- cbind(1, rnorm(1e3))
# Genotypes
G <- replicate(1e3, rbinom(n = 1e3, size = 2, prob = 0.25))
storage.mode(G) <- "numeric"
# Phenotype
y <- as.numeric(X %*% c(1, 1)) + rnorm(1e3)
# Association test
p <- BAT(y = y, G = G, X = X)
```

BAT.ScoreTest	<i>Basic Association Score Test</i>
----------------------	-------------------------------------

Description

Basic Association Score Test

Usage

```
BAT.ScoreTest(y, G, X)
```

Arguments

y	Numeric phenotype vector.
G	Genotype matrix with observations as rows, SNPs as columns.
X	Model matrix of covariates.

Value

Numeric matrix, with 1 row per SNP, containing these columns:

- "score", the score statistic.
- "se", its standard error.
- "z", the Z statistic.
- "p", the p-value.

BAT.WaldTest	<i>Basic Association Wald Test</i>
---------------------	------------------------------------

Description

Basic Association Wald Test

Usage

```
BAT.WaldTest(y, G, X)
```

Arguments

y	Numeric phenotype vector.
G	Genotype matrix with observations as rows, SNPs as columns.
X	Model matrix of covariates.

Value

Numeric matrix, with 1 row per SNP, containing these columns:

- "score", the score statistic.
- "se", its standard error.
- "z", the Z statistic.
- "p", the p-value.

CauchyToP

Convert Cauchy Random Variable to P

Description

Convert Cauchy Random Variable to P

Usage

CauchyToP(z)

Arguments

z Numeric Cauchy random variable.

Value

Numeric p-value.

DINT

Direct-INT

Description

Applies the rank-based inverse normal transformation ([RankNorm](#)) to the phenotype y. Conducts tests of association between the loci in G and transformed phenotype, adjusting for the model matrix X.

Usage

DINT(y, G, X = NULL, k = 0.375, test = "Score", simple = FALSE)

Arguments

<code>y</code>	Numeric phenotype vector.
<code>G</code>	Genotype matrix with observations as rows, SNPs as columns.
<code>X</code>	Model matrix of covariates and structure adjustments. Should include an intercept. Omit to perform marginal tests of association.
<code>k</code>	Offset applied during rank-normalization. See RankNorm .
<code>test</code>	Either Score or Wald.
<code>simple</code>	Return the p-values only?

Value

If `simple` = TRUE, returns a vector of p-values, one for each column of `G`. If `simple` = FALSE, returns a numeric matrix, including the Wald or Score statistic, its standard error, the Z-score, and the p-value.

See Also

- Basic association test [BAT](#).
- Indirect INT test [IINT](#).
- Omnibus INT test [OINT](#).

Examples

```
set.seed(100)
# Design matrix
X <- cbind(1, rnorm(1e3))
# Genotypes
G <- replicate(1e3, rbinom(n = 1e3, size = 2, prob = 0.25))
storage.mode(G) <- "numeric"
# Phenotype
y <- exp(as.numeric(X %*% c(1, 1)) + rnorm(1e3))
# Association test
p <- DINT(y = y, G = G, X = X)
```

Description

Fits the standard OLS model.

Usage

```
fitOLS(y, X)
```

Arguments

y	Nx1 Numeric vector.
X	NxP Numeric matrix.

Value

List containing the following:

Beta	Regression coefficient.
V	Outcome variance.
Ibb	Information matrix for beta.
Resid	Outcome residuals.

Description

Two-stage association testing procedure. In the first stage, phenotype y and genotype G are each regressed on the model matrix X to obtain residuals. The phenotypic residuals are transformed using [RankNorm](#). In the next stage, the INT-transformed residuals are regressed on the genotypic residuals.

Usage

```
IINT(y, G, X = NULL, k = 0.375, simple = FALSE)
```

Arguments

y	Numeric phenotype vector.
G	Genotype matrix with observations as rows, SNPs as columns.
X	Model matrix of covariates and structure adjustments. Should include an intercept. Omit to perform marginal tests of association.
k	Offset applied during rank-normalization. See RankNorm .
simple	Return the p-values only?

Value

If `simple = TRUE`, returns a vector of p-values, one for each column of G. If `simple = FALSE`, returns a numeric matrix, including the Wald or Score statistic, its standard error, the Z-score, and the p-value.

See Also

- Basic association test [BAT](#).
- Direct INT test [DINT](#).
- Omnibus INT test [OINT](#).

Examples

```
set.seed(100)
# Design matrix
X <- cbind(1, rnorm(1e3))
# Genotypes
G <- replicate(1e3, rbinom(n = 1e3, size = 2, prob = 0.25))
storage.mode(G) <- "numeric"
# Phenotype
y <- exp(as.numeric(X %*% c(1,1)) + rnorm(1e3))
# Association test
p <- IINT(y = y, G = G, X = X)
```

IINT.ScoreTest*Basic Association Score Test***Description**

Basic Association Score Test

Usage

```
IINT.ScoreTest(y, G, X, k)
```

Arguments

<i>y</i>	Numeric phenotype vector.
<i>G</i>	Genotype matrix with observations as rows, SNPs as columns.
<i>X</i>	Model matrix of covariates.
<i>k</i>	Offset applied during rank-normalization.

Value

Numeric matrix, with 1 row per SNP, containing these columns:

- "score", the score statistic.
- "se", its standard error.
- "z", the Z statistic.
- "p", the p-value.

matInv*Matrix Inverse*

Description

Calcuates A^{-1} .

Usage

`matInv(A)`

Arguments

A Numeric matrix.

Value

Numeric matrix.

matIP*Matrix Inner Product*

Description

Calculates the product $A'B$.

Usage

`matIP(A, B)`

Arguments

A Numeric matrix.

B Numeric matrix.

Value

Numeric matrix.

OINT*Omnibus-INT*

Description

Association test that synthesizes the [DINT](#) and [IINT](#) tests. The first approach is most powerful for traits that could have arisen from a rank-preserving transformation of a latent normal trait. The second approach is most powerful for traits that are linear in covariates, yet have skewed or kurtotic residual distributions. During the omnibus test, the direct and indirect tests are separately applied, then the p-values are combined via the Cauchy combination method.

Usage

```
OINT(y, G, X = NULL, k = 0.375, simple = FALSE)
```

Arguments

y	Numeric phenotype vector.
G	Genotype matrix with observations as rows, SNPs as columns.
X	Model matrix of covariates and structure adjustments. Should include an intercept. Omit to perform marginal tests of association.
k	Offset applied during rank-normalization. See RankNorm .
simple	Return the OINT p-values only?

Value

A numeric matrix of p-values, three for each column of G.

See Also

- Basic association test [BAT](#).
- Direct INT test [DINT](#).
- Indirect INT test [IINT](#).

Examples

```
set.seed(100)
# Design matrix
X <- cbind(1, rnorm(1e3))
# Genotypes
G <- replicate(1e3, rbinom(n = 1e3, size = 2, prob = 0.25))
storage.mode(G) <- "numeric"
# Phenotype
y <- exp(as.numeric(X %*% c(1, 1)) + rnorm(1e3))
# Omnibus
p <- OINT(y = y, G = G, X = X, simple = TRUE)
```

OmniP	<i>Omnibus P-value.</i>
-------	-------------------------

Description

Obtains an omnibus p-value from a vector of potentially dependent p-values using the method of Cauchy combination. The p-values are converted to Cauchy random deviates then averaged. The distribution of the average of these deviates is well-approximated by a Cauchy distribution in the tails. See <<https://doi.org/10.1080/01621459.2018.1554485>>.

Usage

```
OmniP(p)
```

Arguments

p	Numeric vector of p-values.
---	-----------------------------

Value

OINT p-value.

PartitionData	<i>Partition Data</i>
---------------	-----------------------

Description

Partition y and X according to the missingness pattern of g.

Usage

```
PartitionData(e, g, X)
```

Arguments

e	Numeric residual vector.
g	Genotype vector.
X	Model matrix of covariates.

Value

List containing:

- "g_obs", observed genotype vector.
- "X_obs", covariates for subjects with observed genotypes.
- "X_mis", covariates for subjects with missing genotypes.
- "e_obs", residuals for subjects with observed genotypes.

PtoCauchy*Convert P-value to Cauchy Random***Description**

Convert P-value to Cauchy Random

Usage

```
PtoCauchy(p)
```

Arguments

p	Numeric p-value.
---	------------------

Value

Numeric Cauchy random variable.

RankNorm*Rank-Normalize***Description**

Applies the rank-based inverse normal transform (INT) to a numeric vector. The INT can be broken down into a two-step procedure. In the first, the observations are transformed onto the probability scale using the empirical cumulative distribution function (ECDF). In the second, the observations are transformed onto the real line, as Z-scores, using the probit function.

Usage

```
RankNorm(u, k = 0.375)
```

Arguments

u	Numeric vector.
k	Offset. Defaults to (3/8), correspond to the Blom transform.

Value

Numeric vector of rank normalized measurements.

See Also

- Direct INT test [DINT](#).
- Indirect INT test [IINT](#).
- Omnibus INT test [OINT](#).

Examples

```
# Draw from chi-1 distribution
y <- rchisq(n = 1e3, df = 1)
# Rank normalize
z <- RankNorm(y)
# Plot density of transformed measurement
plot(density(z))
```

RNOmni-help

RNOmni: Rank-Normal Omnibus Association Testing

Description

Implementation of genetic association tests that incorporate the rank-based inverse normal transformation (INT) [RankNorm](#). In direct-INT [DINT](#), the phenotype itself is transformed. In indirect-INT [IINT](#), phenotypic residuals are transformed. The omnibus INT [OINT](#) test adaptively combines the D-INT and I-INT tests into a single robust and statistically powerful procedure. See McCaw ZR, Lane JM, Saxena R, Redline S, Lin X. "Operating characteristics of the rank-based inverse normal transformation for quantitative trait analysis in genome-wide association studies." *Biometrics*, 2019. <<https://doi.org/10.1111/biom.13214>>.

Author(s)

Zachary R. McCaw

SchurC

Schur complement

Description

Calculates the efficient information $I_{bb} - I_{ba}I_{aa}^{-1}I_{ab}$.

Usage

```
SchurC(Ibb, Iaa, Iba)
```

Arguments

Ibb	Information of target parameter
Iaa	Information of nuisance parameter
Iba	Cross information between target and nuisance parameters

Value

Numeric matrix.

ScoreStat*Score Statistics***Description**

Score Statistics

Usage

```
ScoreStat(e, g, X, v)
```

Arguments

e	Numeric residual vector.
g	Genotype vector.
X	Model matrix of covariates.
v	Residual variance.

Value

Numeric vector containing the "score" statistic, standard error "se", "z", and "p" value.

WaldStat*Basic Association Score Test***Description**

Basic Association Score Test

Usage

```
WaldStat(y, g, X)
```

Arguments

y	Numeric phenotype vector.
g	Genotype vector.
X	Model matrix of covariates.

Value

Numeric matrix, with 1 row per SNP, containing these columns:

- "score", the score statistic.
- "se", its standard error.
- "z", the Z statistic.
- "p", the p-value.

Index

BasicInputChecks, 2
BAT, 3, 6, 8, 10
BAT.ScoreTest, 4
BAT.WaldTest, 4

CauchyToP, 5

DINT, 3, 5, 8, 10, 12, 13

fitOLS, 6

IINT, 3, 6, 7, 10, 12, 13
IINT.ScoreTest, 8

matInv, 9
matIP, 9

OINT, 3, 6, 8, 10, 12, 13
OmniP, 11

PartitionData, 11
PtoCauchy, 12

RankNorm, 5–7, 10, 12, 13
RN0mni-help, 13

SchurC, 13
ScoreStat, 14

WaldStat, 14