

Package ‘fitur’

October 6, 2021

Title Fit Univariate Distributions

Version 0.6.2

Description Wrapper for computing parameters for univariate distributions using MLE. It creates an object that stores d, p, q, r functions as well as parameters and statistics for diagnostics. Currently supports automated fitting from base and actuar packages. A manually fitting distribution fitting function is included to support directly specifying parameters for any distribution from ancillary packages.

URL <https://github.com/tomroh/fitur>

BugReports <https://github.com/tomroh/fitur/issues>

Depends R (>= 3.3.0)

Imports stats, fitdistrplus, actuar, e1071, ggplot2, goftest, shiny (>= 0.13), miniUI (>= 0.1.1), rstudioapi (>= 0.5), DT

Suggests knitr, rmarkdown

License MIT + file LICENSE

Encoding UTF-8

VignetteBuilder knitr

RoxygenNote 7.1.1

NeedsCompilation no

Author Thomas Roh [aut, cre]

Maintainer Thomas Roh <thomas@roh.engineering>

Repository CRAN

Date/Publication 2021-10-06 16:30:02 UTC

R topics documented:

build_dist	2
calc_moments	3
DiscreteUniform	3
fit_dist_addin	4
fit_empirical	4

fit_univariate	6
fit_univariate_man	7
gen_dist_fun	8
GOFTests	8
gof_tests	9
is.distfun	10
Mode	10
plot_density	11
plot_pp	11
plot_qq	12

Index	13
--------------	-----------

build_dist	<i>Build Distribution Functions</i>
------------	-------------------------------------

Description

A wrapper for building function families given a numeric vector and the distribution

Usage

```
build_dist(x, distribution)
```

Arguments

x	numeric vector
distribution	distribution character name

Value

list of distribution functions for d, p, q, r, and parameters

Examples

```
fittedDists <- build_dist(rpois(100,5), 'pois')
dpois(x = 5, lambda = 5)
fittedDists$dpois(5)
ppois(5, 5)
fittedDists$ppois(5)
qpois(.5, 5)
fittedDists$qpois(.5)
set.seed(8257)
rpois(100, 5)
set.seed(8257)
fittedDists$rpois(100)
fittedDists$parameters
```

calc_moments	<i>Calculate moments of a numeric vector</i>
--------------	--

Description

Calculate moments of a numeric vector

Usage

```
calc_moments(x)
```

Arguments

x a numeric vector

Value

a named vector of descriptive statistics

Examples

```
x <- rexp(1000, 2)
calc_moments(x)
```

DiscreteUniform	<i>The Discrete Uniform Distribution</i>
-----------------	--

Description

The Discrete Uniform Distribution

Usage

```
ddunif(x, min = 0, max = 1)
pdunif(q, min = 0, max = 1)
qdunif(p, min = 0, max = 1)
rdunif(n, min = 0L, max = 1)
```

Arguments

x	vector of (non-negative integer) quantiles
min	minimum value of distribution (integer)
max	maximum value of distribution (integer)
q	vector of quantiles
p	vector of probabilities
n	number of random values to return

Value

ddunif gives the density, pdunif gives the distribution function, qdunif gives the quantile function, rdunif generates random deviates

Examples

```
ddunif(0:1)
pdunif(1)
qdunif(.5)
rdunif(10)
```

fit_dist_addin

Fit Univariate Distributions Addin

Description

Interactively submit a numeric vector and choose what distributions that you want to run fit diagnostics. Click done to have the desired distribution code put into your cursor position.

Usage

```
fit_dist_addin()
```

fit_empirical

Fit Empirical Distribution

Description

Fit Empirical Distribution

Usage

```
fit_empirical(x)
```

Arguments

x integer or double vector

Value

if integer vector then list of family functions for d, p, q, r, and parameters based on each integer value. if it is a double vector then list of family functions for d, p, q, r, and parameters based on Freedman-Diaconis rule for optimal number of histogram bins.

Examples

```
set.seed(562)
x <- rpois(100, 5)
empDis <- fit_empirical(x)

# probability density function
plot(empDis$dempDis(0:10),
     xlab = 'x',
     ylab = 'dempDis')
# cumulative distribution function
plot(x = 0:10,
     y = empDis$pempDis(0:10),
     #type = 'l',
     xlab = 'x',
     ylab = 'pempDis')
# quantile function
plot(x = seq(.1, 1, .1),
     y = empDis$qempDis(seq(.1, 1, .1)),
     type = 'p',
     xlab = 'x',
     ylab = 'qempDis')
# random sample from fitted distribution
summary(empDis$r(100))

empDis$parameters

set.seed(562)
x <- rexp(100, 1/5)
empCont <- fit_empirical(x)

# probability density function
plot(x = 0:10,
     y = empCont$dempCont(0:10),
     xlab = 'x',
     ylab = 'dempCont')
# cumulative distribution function
plot(x = 0:10,
     y = empCont$pempCont(0:10),
     #type = 'l',
     xlab = 'x',
     ylab = 'pempCont')
# quantile function
```

```

plot(x = seq(.5, 1, .1),
     y = empCont$qempCont(seq(.5, 1, .1)),
     type = 'p',
     xlab = 'x',
     ylab = 'qempCont')
# random sample from fitted distribution
summary(empCont$r(100))

empCont$parameters

```

fit_univariate

Fit Univariate Distribution

Description

Fit Univariate Distribution

Usage

```
fit_univariate(x, distribution, type = "continuous")
```

Arguments

x	numeric vector
distribution	character name of distribution
type	discrete or continuous data

Value

a fitted list object of d, p, q, r distribution functions and parameters, MLE for probability distributions, custom fit for empirical

Examples

```

# Fit Discrete Distribution
set.seed(42)
x <- rpois(1000, 3)
fitted <- fit_univariate(x, 'pois', type = 'discrete')
# density function
plot(fitted$dpois(x=0:10),
     xlab = 'x',
     ylab = 'dpois')
# distribution function
plot(fitted$ppois(seq(0, 10, 1)),
     xlab = 'x',
     ylab = 'ppois')
# quantile function
plot(fitted$qpois,
     xlab = 'x',

```

```
      ylab = 'qpois')
# sample from theoretical distribution
summary(fitted$rpois(100))
# estimated parameters from MLE
fitted$parameters

set.seed(24)
x <- rweibull(1000, shape = .5, scale = 2)
fitted <- fit_univariate(x, 'weibull')
# density function
plot(fitted$dweibull,
     xlab = 'x',
     ylab = 'dweibull')
# distribution function
plot(fitted$pweibull,
     xlab = 'x',
     ylab = 'pweibull')
# quantile function
plot(fitted$qweibull,
     xlab = 'x',
     ylab = 'qweibull')
# sample from theoretical distribution
summary(fitted$rweibull(100))
# estimated parameters from MLE
fitted$parameters
```

fit_univariate_man *Fit Univariate Distributions by Specifying Parameters*

Description

Fit Univariate Distributions by Specifying Parameters

Usage

```
fit_univariate_man(distribution, parameters)
```

Arguments

distribution	distribution character name
parameters	named vector of parameters to set

Value

list of distribution functions for d, p, q, r, and parameters

Examples

```

manFun <- fit_univariate_man('norm', c(mean = 2, sd = 5))
set.seed(5)
m1 <- mean(manFun$rnorm(100000))
set.seed(5)
m2 <- mean(rnorm(100000, 2, 5))
identical(m1, m2)

```

gen_dist_fun	<i>Generate Single Distribution Function</i>
--------------	--

Description

Generate Single Distribution Function

Usage

```
gen_dist_fun(f, parameters, ...)
```

Arguments

f	one of distribution functions
parameters	new parameters for distribution
...	arguments to pass on to distribution function

Value

one of parameterized distribution functions in d, p, q, r

GOFTests	<i>Wrappers to compute goodness of fit test froms distfun objects</i>
----------	---

Description

Wrappers to compute goodness of fit test froms distfun objects

Usage

```
ks_test(distfun, x, ...)  
  
## S3 method for class 'distfun'  
ad_test(distfun, x)  
  
ad_test(distfun, x)  
  
## S3 method for class 'distfun'  
cvm_test(distfun, x)  
  
cvm_test(distfun, x)
```

Arguments

distfun	a distfun object
x	numeric vector
...	arguments to be passed on to test function

Value

goodness of fit object

Examples

```
x <- rgamma(100, 1, 1)  
fit <- fit_univariate(x, 'gamma')  
ks_test(fit, x)  
ad_test(fit, x)  
cvm_test(fit, x)
```

gof_tests

Goodness of Fit Testing

Description

Apply all goodness of fit tests and return a data.frame with the results

Usage

```
gof_tests(fits, x)
```

Arguments

fits	a list object produced from fit_univariate, fit_empirical, or fit_univariate_man
x	numeric vector of sample data

Value

a data.frame of test statistic results for each distribution

Examples

```
set.seed(84)
x <- rgamma(100, 1, 1)
dists <- c('gamma', 'lnorm', 'weibull')
multipleFits <- lapply(dists, fit_univariate, x = x)
gof_tests(multipleFits, x)
```

is.distfun	<i>Test if object is a distfun object</i>
------------	---

Description

Test if object is a distfun object

Usage

```
is.distfun(x)
```

Arguments

x an R object to be tested

Value

TRUE if x is a disfun object, FALSE otherwise

Mode	<i>Find Mode</i>
------	------------------

Description

Find Mode

Usage

```
Mode(x)
```

Arguments

x vector of data

Value

mode of data

plot_density	<i>Density Comparison Plot</i>
--------------	--------------------------------

Description

Density Comparison Plot

Usage

```
plot_density(x, fits, nbins)
```

Arguments

x	numeric vector of sample data
fits	a list object produced from fit_univariate, fit_empirical, or fit_univariate_man
nbins	number of bins for histogram

Value

ggplot of empirical histogram of x compared to theoretical density distributions

Examples

```
library(ggplot2)
set.seed(37)
x <- rgamma(10000, 5)
dists <- c('gamma', 'lnorm', 'weibull')
fits <- lapply(dists, fit_univariate, x = x)
plot_density(x, fits, 30) +
  theme_bw()
```

plot_pp	<i>P-P Plot</i>
---------	-----------------

Description

P-P Plot

Usage

```
plot_pp(x, fits)
```

Arguments

x	numeric vector of sample data
fits	a list object produced from fit_univariate, fit_empirical, or fit_univariate_man

Value

ggplot of percentile-percentile comparison of theoretical distribution

Examples

```
library(ggplot2)
set.seed(37)
x <- rgamma(10000, 5)
dists <- c('gamma', 'lnorm', 'weibull')
fits <- lapply(dists, fit_univariate, x = x)
plot_pp(x, fits) +
  theme_bw()
```

plot_qq

Q-Q Plot

Description

Q-Q Plot

Usage

```
plot_qq(x, fits)
```

Arguments

x	numeric vector of sample data
fits	a list object produced from fit_univariate, fit_empirical, or fit_univariate_man

Value

ggplot of quantile-quantile comparison of theoretical distribution

Examples

```
library(ggplot2)
set.seed(37)
x <- rgamma(10000, 5)
dists <- c('gamma', 'lnorm', 'weibull')
fits <- lapply(dists, fit_univariate, x = x)
plot_qq(x, fits) +
  theme_bw()
```

Index

ad_test (GOFTests), 8

build_dist, 2

calc_moments, 3

cvm_test (GOFTests), 8

ddunif (DiscreteUniform), 3

DiscreteUniform, 3

fit_dist_addin, 4

fit_empirical, 4

fit_univariate, 6

fit_univariate_man, 7

gen_dist_fun, 8

gof_tests, 9

GOFTests, 8

is.distfun, 10

ks_test (GOFTests), 8

Mode, 10

pdunif (DiscreteUniform), 3

plot_density, 11

plot_pp, 11

plot_qq, 12

qdunif (DiscreteUniform), 3

rdunif (DiscreteUniform), 3