

Package ‘lboxcox’

January 27, 2022

Type Package

Title Implementation of Logistic Box-Cox Regression

Version 1.0

Date 2022-01-15

Maintainer Li Xing <sfulxing@gmail.com>

Description Implements a logistic box-cox model. This model is fully described in Xing, L. et al. (2021) <[doi:10.1002/cjs.11587](https://doi.org/10.1002/cjs.11587)>.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.2

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

Depends R (>= 2.10)

Imports survey, maxLik, doParallel, parallel, foreach

NeedsCompilation no

Author Li Xing [cre, aut],
Kohlton Booth [aut],
Xuekui Zhang [aut],
Igor Burstyn [aut],
Paul Gustafson [aut]

Repository CRAN

Date/Publication 2022-01-27 19:50:02 UTC

R topics documented:

depress	2
lbc_train	2
LogLikeFun	3
ScoreFun	4

Index**5**

depress	<i>Depression dataset</i>
---------	---------------------------

Description

The depress data frame has 8,893 rows and 5 columns from the National Health and Nutrition Examination Survey (NHANES) 2009–2010.

Usage

```
depress
```

Format

Sample survey data

depression binary response variable indicating whether the participant has depression (=1) or not (=0)

mercury a numeric vector giving the log-transformed total blood mercury in micro-grams per litre

age 0 if participant is female and 1 if they are male

gender age of the participant

weight a numeric vector giving the sampling-weight.

Source

Xing, L., Zhang, X., Burstyn, I., & Gustafson, P. (2021). On logistic Box–Cox regression for flexibly estimating the shape and strength of exposure-disease relationships. *Canadian Journal of Statistics*, 49(3), 808-825.

lbc_train	<i>Train a Logistic Box-Cox model</i>
-----------	---------------------------------------

Description

Train the given formula using a Logistic Box-Cox model.

Usage

```
lbc_train(
  formula,
  weight_column_name,
  data,
  init = NULL,
  svy_lambda_vector = seq(0, 2, length = 100),
  num_cores = 1
)
```

Arguments

formula	a formula of the form $y \sim x + z1 + z2$ where y is a binary response variable, x is a continuous predictor variable, and $z1, z2, \dots$ are covariates
weight_column_name	the name of the column in 'data' containing the survey weights.
data	dataframe containing the dataset to train on
init	initial estimates for the coefficients. If NULL the svyglm model will be used
svy_lambda_vector	values of lambda used in training svyglm model. Best model is used for initial coefficient estimates. If init is not NULL this parameter is ignored.
num_cores	the number of cores used when finding the best svyglm model. If init is not NULL this parameter is ignored.

Value

object of class 'maxLik' from the 'maxLik' package. Contains the coefficient estimates that maximizes likelihood among other statistics.

Note

This is reliant on the following work:

Henningsen, A., Toomet, O. (2011). maxLik: A package for maximum likelihood estimation in R. Computational Statistics, 26(3), 443-458.

Microsoft Corporation, Weston, S. (2020). foreach: Provides Foreach Looping Construct. R package version 1.5.1.

Microsoft Corporation, Weston, S. (2020). doParallel: Foreach Parallel Adaptor for the 'parallel' Package. R package version 1.0.16.

 LogLikeFun

Log Likelihood of Logistic Box-Cox

Description

This function gives the log likelihood of the Box-Cox model. Main purpose is to be an input to the maxLik function.

Usage

```
LogLikeFun(bb, ixx, iyy, iw, iZZ)
```

Arguments

bb	current values for the intercept and slope coefficients
ixx	continuous predictor
iyx	binary outcome
iw	sample weight
izz	covariates to be incorporated in the model

Value

the log likelihood estimate for the coefficients in 'bb'

ScoreFun

Log Likelihood Gradient of Logistic Box-Cox

Description

This function gives the gradient of the log likelihood of the Box-Cox model. Main purpose is to be an input to the maxLik function.

Usage

```
ScoreFun(bb, ixx, iyy, iw, izz)
```

Arguments

bb	initial values for the intercept and slope coefficients
ixx	continuous predictor
iyx	binary outcome
iw	sample weight
izz	covariates to be incorporated in the model

Value

the gradient of the log likelihood estimate for the coefficients in 'bb'

Index

* **datasets**
 depress, [2](#)

depress, [2](#)

lbc_train, [2](#)
LogLikeFun, [3](#)

ScoreFun, [4](#)