

Package ‘showtextdb’

June 4, 2020

Type Package

Title Font Files for the 'showtext' Package

Version 3.0

Date 2020-05-31

Author Yixuan Qiu and authors/contributors of the included fonts. See file AUTHORS for details.

Maintainer Yixuan Qiu <yixuan.qiu@cos.name>

Description Providing font files that can be used by the 'showtext' package.

Imports sysfonts (>= 0.7), utils

Suggests curl

License Apache License (>= 2.0)

Copyright see file COPYRIGHTS

RoxygenNote 7.1.0

NeedsCompilation no

Repository CRAN

Date/Publication 2020-06-04 08:10:02 UTC

R topics documented:

font_install	2
google_fonts	3
load_showtext_fonts	4
source_han	4

Index	6
--------------	----------

`font_install`*Install Fonts to the 'showtextdb' Package*

Description

`font_install()` saves the specified font to the 'fonts' directory of the **showtextdb** package, so that it can be used by the **showtext** package. This function requires the **curl** package.

`font_installed()` lists fonts that have been installed to **showtextdb**.

NOTE: Since the fonts are installed locally to the package directory, they will be removed every time the **showtextdb** package is upgraded or re-installed.

Usage

```
font_install(font_desc, quiet = FALSE, ...)
```

```
font_installed()
```

Arguments

<code>font_desc</code>	A list that provides necessary information of the font for installation. See the Details section.
<code>quiet</code>	Whether to show the progress of downloading and installation.
<code>...</code>	Other parameters passed to <code>curl::curl_download()</code> .

Details

`font_desc` is a list that should contain at least the following components:

`showtext_name` The family name of the font that will be used in **showtext**.

`font_ext` Extension name of the font files, e.g., `ttf` for TrueType, and `otf` for OpenType.

`regular_url` URL of the font file for "regular" font face.

Optionally, `font_desc` can also contain `bold_url`, `italic_url`, `bolditalic_url`, and `symbol_url` that provide the URLs of the other font faces.

See [source_han_sans\(\)](#) and [source_han_serif\(\)](#) for an example of the `font_desc` parameter.

Author(s)

Yixuan Qiu <<https://statr.me/>>

Examples

```
## Not run:
## Install Source Han Serif Simplified Chinese
font_install(source_han_serif())

## List available font families
sysfonts::font_families()

## Use the font with the "showtext" package
if(require(showtext)) {
  wd = setwd(tempdir())
  showtext.auto()

  pdf("source-han-serif.pdf")
  par(family = "source-han-serif-cn")
  plot.new()
  box()
  text(0.5, 0.9, "\u601d\u6e90\u5b8b\u4f53", cex = 3, font = 2)
  text(0.5, 0.4, "\u843d\u5176\u5b9e\u8005\u601d\u5176\u6811", cex = 3)
  text(0.5, 0.2, "\u996e\u5176\u6d41\u8005\u6000\u5176\u6e90", cex = 3)
  dev.off()
  setwd(wd)
}

## End(Not run)
```

google_fonts

Meta-information for the Google Fonts

Description

This function provides information of Google Fonts that can be used in the `font_install()` function. It will try to include all font faces available for a specified family name.

Usage

```
google_fonts(name, ...)
```

Arguments

name	Name of the font that will be searched in Google Fonts.
...	Other parameters passed to <code>curl::curl_fetch_memory()</code> .

Author(s)

Yixuan Qiu <<https://statr.me/>>

Examples

```
opensans = google_fonts("Open Sans")
print(opensans)

## Not run:
## Install the Open Sans font to the showtextdb package
font_install(opensans)

## End(Not run)
```

load_showtext_fonts *Load Fonts for the 'showtext' Package*

Description

This function loads fonts that will be used by the **showtext** package.

Usage

```
load_showtext_fonts()
```

Author(s)

Yixuan Qiu <<https://statr.me/>>

Examples

```
## Not run:
sysfonts::font_families()

load_showtext_fonts()
sysfonts::font_families()

## End(Not run)
```

source_han *Meta-information for the Source Han Sans/Serif Fonts*

Description

These functions provide information of the Source Han Sans/Serif fonts that can be used in the [font_install\(\)](#) function. Source Han Sans/Serif fonts provide complete support for the CJK (Chinese, Japanese, and Korean) characters.

Usage

```
source_han_sans(lang = c("CN", "TW", "JP", "KR"))
```

```
source_han_serif(lang = c("CN", "TW", "JP", "KR"))
```

Arguments

lang Language of the font. "CN" for simplified Chinese, "TW" for traditional Chinese, "JP" for Japanese, and "KR" for Korean.

Author(s)

Yixuan Qiu <<https://statr.me/>>

Examples

```
## Not run:  
## Install Source Han Sans font (by default Simplified Chinese)  
## to the showtexdb package  
font_install(source_han_sans())  
  
## Source Han Serif Japanese  
font_install(source_han_serif("JP"))  
  
## End(Not run)
```

Index

font_install, [2](#), [3](#), [4](#)
font_installed(font_install), [2](#)

google_fonts, [3](#)

load_showtext_fonts, [4](#)

source_han, [4](#)
source_han_sans, [2](#)
source_han_sans(source_han), [4](#)
source_han_serif, [2](#)
source_han_serif(source_han), [4](#)