

Package ‘vein’

May 13, 2022

Type Package

Title Vehicular Emissions Inventories

Version 0.9.6

Date 2022-05-1

Description Elaboration of vehicular emissions inventories, consisting in four stages, pre-processing activity data, preparing emissions factors, estimating the emissions and post-processing of emissions in maps and databases. More details in Ibarra-Espinosa et al (2018) <[doi:10.5194/gmd-11-2209-2018](https://doi.org/10.5194/gmd-11-2209-2018)>.

Before using VEIN you need to know the vehicular composition of your study area, in other words, the combination of of type of vehicles, size and fuel of the fleet. Then, it is recommended to start with the project to download a template to create a structure of directories and scripts.

License MIT + file LICENSE

URL <https://github.com/atmoschem/vein>

BugReports <https://github.com/atmoschem/vein/issues>

LazyData no

Depends R (>= 3.5.0)

Imports sf (>= 1.0.1), data.table, units, graphics, stats, dotCall64, cptcity, fields, grDevices

Suggests knitr, rmarkdown, testthat

RoxygenNote 7.1.2

Encoding UTF-8

NeedsCompilation yes

Config/testthat/parallel true

VignetteBuilder knitr

Author Sergio Ibarra-Espinosa [aut, cre]
(<<https://orcid.org/0000-0002-3162-1905>>),
Joao Bazzo [ctb] (<<https://orcid.org/0000-0003-4536-5006>>)

Maintainer Sergio Ibarra-Espinosa <zergioibarra@gmail.com>

Repository CRAN

Date/Publication 2022-05-13 14:10:02 UTC

R topics documented:

add_lkm	4
add_miles	4
add_polid	5
adt	6
age	7
age_hdv	9
age_ldv	11
age_moto	12
aw	14
celsius	15
check_nt	16
cold_mileage	17
colplot	17
decoder	19
dmonth	20
ef_cetesb	21
ef_china	24
ef_eea	28
ef_evap	29
ef_fun	31
ef_hdv_scaled	32
ef_hdv_speed	34
ef_im	36
ef_ive	37
ef_ldv_cold	39
ef_ldv_cold_list	40
ef_ldv_scaled	42
ef_ldv_speed	43
ef_local	47
ef_nitro	49
ef_wear	50
ef_whe	51
emis	52
EmissionFactors	56
EmissionFactorsList	57
Emissions	58
EmissionsArray	60
emis_chem	62
emis_chem2	63
emis_cold	65
emis_cold_td	67
emis_det	70
emis_dist	72
emis_evap	73
emis_evap2	74
emis_grid	77

emis_hot_td	79
emis_merge	84
emis_order	85
emis_paved	87
emis_post	89
emis_source	91
emis_to_streets	92
emis_wear	93
fe2015	94
flm	95
fuel_corr	96
get_project	97
GriddedEmissionsArray	98
grid_emis	100
invcop	101
inventory	103
long_to_wide	104
make_grid	105
moves_ef	106
moves_rpd	107
moves_rpdy	109
moves_rpdy_meta	110
moves_rpdy_sf	111
moves_rpsy_meta	113
moves_rpsy_sf	114
moves_speed	115
my_age	116
net	117
netspeed	118
pc_cold	119
pc_profile	120
pollutants	120
profiles	121
remove_units	122
speciate	123
Speed	126
split_emis	128
temp_fact	129
to_latex	130
Vehicles	131
vein_notes	132
vkm	133
wide_to_long	135

add_1km	<i>Construction function to add unit km</i>
---------	---

Description

add_1km just add unit 'km' to different R objects

Usage

```
add_1km(x)
```

Arguments

x Object with class "data.frame", "matrix", "numeric" or "integer"

Value

Objects of class "data.frame" or "units"

See Also

Other Add distance units: [add_miles\(\)](#)

Examples

```
## Not run:
a <- add_1km(rnorm(100)*10)
plot(a)
b <- add_1km(matrix(rnorm(100)*10, ncol = 10))
print(head(b))

## End(Not run)
```

add_miles	<i>Construction function to add unit miles</i>
-----------	--

Description

add_miles just add unit 'miles' to different R objects

Usage

```
add_miles(x)
```

Arguments

x Object with class "data.frame", "matrix", "numeric" or "integer"

Value

Objects of class "data.frame" or "units"

See Also

Other Add distance units: [add_lkm\(\)](#)

Examples

```
## Not run:
a <- add_miles(rnorm(100)*10)
plot(a)
b <- add_miles(matrix(rnorm(100)*10, ncol = 10))
print(head(b))

## End(Not run)
```

add_polid

Add polygon id to lines road network

Description

Sometimes you need to add polygon id into your streets road network. [add_polid](#) add add_polid id into your road network cropping your network by.

For instance, you have open street maps road network the you have the polygon of your regions. This function adds the id of your polygon as a new column in the streets network.

Usage

```
add_polid(polyg, street, by)
```

Arguments

polyg	sf object POLYGON or sp
street	streets road network class sf or sp
by	Character indicating the column with the id in polyg

See Also

[emis_to_streets](#)

Examples

```
## Not run:
data(net)
nets <- sf::st_as_sf(net)
bb <- sf::st_as_sf(sf::st_as_sfc(sf::st_bbox(nets)))
bb$id <- "a"
a <- add_polid(polyg = bb, street = nets, by = "id")

## End(Not run)
```

adt

Average daily traffic (ADT) from hourly traffic data.

Description

`adt` calculates ADT based on hourly traffic data.

Usage

```
adt(
  pc,
  lcv,
  hgv,
  bus,
  mc,
  p_pc,
  p_lcv,
  p_hgv,
  p_bus,
  p_mc,
  feq_pc = 1,
  feq_lcv = 1.5,
  feq_hgv = 2,
  feq_bus = 2,
  feq_mc = 0.5
)
```

Arguments

pc	numeric vector for passenger cars
lcv	numeric vector for light commercial vehicles
hgv	numeric vector for heavy good vehicles or trucks
bus	numeric vector for bus
mc	numeric vector for motorcycles
p_pc	data-frame profile for passenger cars, 24 hours only.

p_lcv	data-frame profile for light commercial vehicles, 24 hours only.
p_hgv	data-frame profile for heavy good vehicles or trucks, 24 hours only.
p_bus	data-frame profile for bus, 24 hours only.
p_mc	data-frame profile for motorcycles, 24 hours only.
feq_pc	Numeric, factor equivalence
feq_lcv	Numeric, factor equivalence
feq_hgv	Numeric, factor equivalence
feq_bus	Numeric, factor equivalence
feq_mc	Numeric, factor equivalence

Value

numeric vector of total volume of traffic per link as ADT

Examples

```
## Not run:
data(net)
data(pc_profile)
p1 <- pc_profile[, 1]
adt1 <- adt(pc = net$ldv*0.75,
           lcv = net$ldv*0.1,
           hgv = net$hdv,
           bus = net$hdv*0.1,
           mc = net$ldv*0.15,
           p_pc = p1,
           p_lcv = p1,
           p_hgv = p1,
           p_bus = p1,
           p_mc = p1)
head(adt1)

## End(Not run)
```

age

Applies a survival rate to numeric new vehicles

Description

`age` returns survived vehicles

Usage

```
age(x, type = "weibull", a = 14.46, b = 4.79, agemax, verbose = FALSE)
```

Arguments

x	Numeric; numerical vector of sales or registrations for each year
type	Character; any of "gompertz", "double_logistic", "weibull" and "weibull2"
a	Numeric; parameter of survival equation
b	Numeric; parameter of survival equation
agemax	Integer; age of oldest vehicles for that category
verbose	Logical; message with average age and total number of vehicles regions or streets.

Value

dataframe of age distribution of vehicles

Note

The functions `age*` produce distribution of the circulating fleet by age of use. The order of using these functions is:

1. If you know the distribution of the vehicles by age of use, use: `my_age` 2. If you know the sales of vehicles, or the registry of new vehicles, use `age` to apply a survival function. 3. If you know the theoretical shape of the circulating fleet and you can use `age_ldv`, `age_hdv` or `age_moto`. For instance, you don't know the sales or registry of vehicles, but somehow you know the shape of this curve. 4. You can use/merge/transform/dapt any of these functions.

gompertz: $1 - \exp(-\exp(a + b \cdot \text{time}))$, defaults PC: $b = -0.137$, $a = 1.798$, LCV: $b = -0.141$, $a = 1.618$ MCT (2006). de Gases de Efeito Estufa-Emissões de Gases de Efeito Estufa por Fontes Móveis, no Setor Energético. Ministério da Ciência e Tecnologia. This curve is also used by Guo and Wang (2012, 2015) in the form: $V \cdot \exp(\alpha \cdot \exp(\beta \cdot E))$ where V is the saturation car ownership level and E GDP per capita Huo, H., & Wang, M. (2012). Modeling future vehicle sales and stock in China. Energy Policy, 43, 17–29. doi:10.1016/j.enpol.2011.09.063 Huo, Hong, et al. "Vehicular air pollutant emissions in China: evaluation of past control policies and future perspectives." Mitigation and Adaptation Strategies for Global Change 20.5 (2015): 719-733.

double_logistic: $1/(1 + \exp(a \cdot (\text{time} + b))) + 1/(1 + \exp(a \cdot (\text{time} - b)))$, defaults PC: $b = 21$, $a = 0.19$, LCV: $b = 15.3$, $a = 0.17$, HGV: $b = 17$, $a = 0.1$, BUS: $b = 19.1$, $a = 0.16$ MCT (2006). de Gases de Efeito Estufa-Emissões de Gases de Efeito Estufa por Fontes Móveis, no Setor Energético. Ministério da Ciência e Tecnologia.

weibull: $\exp(-(\text{time}/a)^b)$, defaults PC: $b = 4.79$, $a = 14.46$, Taxi: $b = +\text{inf}$, $a = 5$, Government and business: $b = 5.33$, $a = 13.11$ Non-operating vehicles: $b = 5.08$, $a = 11.53$ Bus: $b = +\text{inf}$, $a = 9$, non-transit bus: $b = +\text{inf}$, $a = 5.5$ Heavy HGV: $b = 5.58$, $a = 12.8$, Medium HGV: $b = 5.58$, $a = 10.09$, Light HGV: $b = 5.58$, $a = 8.02$ Hao, H., Wang, H., Ouyang, M., & Cheng, F. (2011). Vehicle survival patterns in China. Science China Technological Sciences, 54(3), 625-629.

weibull2: $\exp(-((\text{time} + b)/a)^b)$, defaults $b = 11$, $a = 26$ Zachariadis, T., Samaras, Z., Zierock, K. H. (1995). Dynamic modeling of vehicle populations: an engineering approach for emissions calculations. Technological Forecasting and Social Change, 50(2), 135-149. Cited by Huo and Wang (2012)

See Also

Other age: `age_hdv()`, `age_ldv()`, `age_moto()`

Examples

```
## Not run:
vehLIA <- rep(1, 25)
PV_Minia <- age(x = vehLIA)
PV_Minib <- age(x = vehLIA, type = "weibull2", b = 11, a = 26)
PV_Minic <- age(x = vehLIA, type = "double_logistic", b = 21, a = 0.19)
PV_Minid <- age(x = vehLIA, type = "gompertz", b = -0.137, a = 1.798)
plot(PV_Minia, type = "b", pch = 16)
lines(PV_Minib, type = "b", pch = 16, col = "red")
lines(PV_Minic, type = "b", pch = 16, col = "blue")
lines(PV_Minid, type = "b", pch = 16, col = "green")
legend(x = 20, y = 0.85,
       legend = c("weibull", "weibull2", "double_logistic", "gompertz"),
       col = c("black", "red", "blue", "green"),
       lty=c(1,1),
       lwd=c(2.5, 2.5, 2.5, 2.5))
#lets put some numbers
vehLIA <- c(65400, 79100, 80700, 85300, 86700, 82000, 74500, 67700, 60600, 62500,
84700, 62600, 47900, 63900, 41800, 37492, 34243, 30995, 27747, 24499, 21250,
18002, 14754, 11506, 8257)
PV_Minia <- age(x = vehLIA)
PV_Minib <- age(x = vehLIA, type = "weibull2", b = 11, a = 26)
PV_Minic <- age(x = vehLIA, type = "double_logistic", b = 21, a = 0.19)
PV_Minid <- age(x = vehLIA, type = "gompertz", b = -0.137, a = 1.798)
plot(PV_Minia, type = "b", pch = 16)
lines(PV_Minib, type = "b", pch = 16, col = "red")
lines(PV_Minic, type = "b", pch = 16, col = "blue")
lines(PV_Minid, type = "b", pch = 16, col = "green")
legend(x = 20, y = 80000,
       legend = c("weibull", "weibull2", "double_logistic", "gompertz"),
       col = c("black", "red", "blue", "green"),
       lty=c(1,1),
       lwd=c(2.5, 2.5, 2.5, 2.5))

## End(Not run)
```

age_hdv

*Returns amount of vehicles at each age***Description**

[age_hdv](#) returns amount of vehicles at each age

Usage

```
age_hdv(
  x,
  name = "age",
  a = 0.2,
```

```

    b = 17,
    agemin = 1,
    agemax = 50,
    k = 1,
    bystreet = F,
    net,
    verbose = FALSE,
    namerows,
    time
  )

```

Arguments

x	Numeric; numerical vector of vehicles with length equal to lines features of road network
name	Character; of vehicle assigned to columns of dataframe
a	Numeric; parameter of survival equation
b	Numeric; parameter of survival equation
agemin	Integer; age of newest vehicles for that category
agemax	Integer; age of oldest vehicles for that category
k	Numeric; multiplication factor. If its length is > 1, it must match the length of x
bystreet	Logical; when TRUE it is expecting that 'a' and 'b' are numeric vectors with length equal to x
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"
verbose	Logical; message with average age and total numer of vehicles
namerows	Any vector to be change row.names. For instance, name of regions or streets.
time	Character to be the time units as denominator, eg "1/h"

Value

dataframe of age distrubution of vehicles at each street

Note

The functions age* produce distribution of the circulating fleet by age of use. The order of using these functions is:

1. If you know the distribution of the vehicles by age of use , use: [my_age](#)
2. If you know the sales of vehicles, or the registry of new vehicles, use [age](#) to apply a survival function.
3. If you know the theoretical shape of the circulating fleet and you can use [age_ldv](#), [age_hdv](#) or [age_moto](#). For instance, you dont know the sales or registry of vehicles, but somehow you know the shape of this curve.
4. You can use/merge/transform/adapt any of these functions.

See Also

Other age: [age_ldv\(\)](#), [age_moto\(\)](#), [age\(\)](#)

Examples

```
## Not run:
data(net)
LT_B5 <- age_hdv(x = net$hdv, name = "LT_B5")
plot(LT_B5)
LT_B5 <- age_hdv(x = net$hdv, name = "LT_B5", net = net)
plot(LT_B5)

## End(Not run)
```

age_ldv

*Returns amount of vehicles at each age***Description**

`age_ldv` returns amount of vehicles at each age

Usage

```
age_ldv(
  x,
  name = "age",
  a = 1.698,
  b = -0.2,
  agemin = 1,
  agemax = 50,
  k = 1,
  bystreet = F,
  net,
  verbose = FALSE,
  namerows,
  time
)
```

Arguments

x	Numeric; numerical vector of vehicles with length equal to lines features of road network
name	Character; of vehicle assigned to columns of dataframe
a	Numeric; parameter of survival equation
b	Numeric; parameter of survival equation
agemin	Integer; age of newest vehicles for that category
agemax	Integer; age of oldest vehicles for that category
k	Numeric; multiplication factor. If its length is > 1, it must match the length of x
bystreet	Logical; when TRUE it is expecting that 'a' and 'b' are numeric vectors with length equal to x

net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"
verbose	Logical; message with average age and total numer of vehicles
namerows	Any vector to be change row.names. For instance, name of regions or streets.
time	Character to be the time units as denominator, eg "1/h"

Value

dataframe of age distrubution of vehicles

Note

The functions age* produce distribution of the circulating fleet by age of use. The order of using these functions is:

1. If you know the distribution of the vehicles by age of use , use: [my_age](#) 2. If you know the sales of vehicles, or the registry of new vehicles, use [age](#) to apply a survival function. 3. If you know the theoretical shape of the circulating fleet and you can use [age_ldv](#), [age_hdv](#) or [age_moto](#). For instance, you dont know the sales or registry of vehicles, but somehow you know the shape of this curve. 4. You can use/merge/transform/adapt any of these functions.

It consists in a Gompertz equation with default parameters from 1 national emissions inventory for green housegases in Brazil, MCT 2006

See Also

Other age: [age_hdv\(\)](#), [age_moto\(\)](#), [age\(\)](#)

Examples

```
## Not run:
data(net)
PC_E25_1400 <- age_ldv(x = net$ldv, name = "PC_E25_1400")
plot(PC_E25_1400)
PC_E25_1400 <- age_ldv(x = net$ldv, name = "PC_E25_1400", net = net)
plot(PC_E25_1400)

## End(Not run)
```

age_moto

Returns amount of vehicles at each age

Description

[age_moto](#) returns amount of vehicles at each age

Usage

```
age_moto(
  x,
  name = "age",
  a = 0.2,
  b = 17,
  agemin = 1,
  agemax = 50,
  k = 1,
  bystreet = FALSE,
  net,
  verbose = FALSE,
  namerows,
  time
)
```

Arguments

x	Numeric; numerical vector of vehicles with length equal to lines features of road network
name	Character; of vehicle assigned to columns of dataframe
a	Numeric; parameter of survival equation
b	Numeric; parameter of survival equation
agemin	Integer; age of newest vehicles for that category
agemax	Integer; age of oldest vehicles for that category
k	Numeric; multiplication factor. If its length is > 1, it must match the length of x
bystreet	Logical; when TRUE it is expecting that 'a' and 'b' are numeric vectors with length equal to x
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"
verbose	Logical; message with average age and total number of vehicles
namerows	Any vector to be change row.names. For instance, name of regions or streets.
time	Character to be the time units as denominator, eg "1/h"

Value

dataframe of age distribution of vehicles

Note

The functions age* produce distribution of the circulating fleet by age of use. The order of using these functions is:

1. If you know the distribution of the vehicles by age of use, use: [my_age](#)
2. If you know the sales of vehicles, or the registry of new vehicles, use [age](#) to apply a survival function.
3. If you know the theoretical shape of the circulating fleet and you can use [age_ldv](#), [age_hdv](#) or [age_moto](#). For instance, you don't know the sales or registry of vehicles, but somehow you know the shape of this curve.
4. You can use/merge/transform/adapt any of these functions.

See Also

Other age: [age_hdv\(\)](#), [age_ldv\(\)](#), [age\(\)](#)

Examples

```
## Not run:
data(net)
MOTO_E25_500 <- age_moto(x = net$ldv, name = "M_E25_500", k = 0.4)
plot(MOTO_E25_500)
MOTO_E25_500 <- age_moto(x = net$ldv, name = "M_E25_500", k = 0.4, net = net)
plot(MOTO_E25_500)

## End(Not run)
```

aw

Average Weight for hourly traffic data.

Description

[aw](#) average weight form traffic.

Usage

```
aw(
  pc,
  lcv,
  hgv,
  bus,
  mc,
  p_pc,
  p_lcv,
  p_hgv,
  p_bus,
  p_mc,
  w_pc = 1,
  w_lcv = 3.5,
  w_hgv = 20,
  w_bus = 20,
  w_mc = 0.5,
  net
)
```

Arguments

pc	numeric vector for passenger cars
lcv	numeric vector for light commercial vehicles
hgv	numeric vector for heavy good vehicles or trucks

bus	numeric vector for bus
mc	numeric vector for motorcycles
p_pc	data-frame profile for passenger cars, 24 hours only.
p_lcv	data-frame profile for light commercial vehicles, 24 hours only.
p_hgv	data-frame profile for heavy good vehicles or trucks, 24 hours only.
p_bus	data-frame profile for bus, 24 hours only.
p_mc	data-frame profile for motorcycles, 24 hours only.
w_pc	Numeric, factor equivalence
w_lcv	Numeric, factor equivalence
w_hgv	Numeric, factor equivalence
w_bus	Numeric, factor equivalence
w_mc	Numeric, factor equivalence
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"

Value

data.frame with with average weight

Examples

```
## Not run:
data(net)
data(pc_profile)
p1 <- pc_profile[, 1]
aw1 <- aw(pc = net$ldv*0.75,
          lcv = net$ldv*0.1,
          hgv = net$hdv,
          bus = net$hdv*0.1,
          mc = net$ldv*0.15,
          p_pc = p1,
          p_lcv = p1,
          p_hgv = p1,
          p_bus = p1,
          p_mc = p1)

head(aw1)

## End(Not run)
```

celsius

Construction function for Celsius temperature

Description

celsius just add unit celsius to different R objects

Usage

```
celsius(x)
```

Arguments

x Object with class "data.frame", "matrix", "numeric" or "integer"

Value

Objects of class "data.frame" or "units"

Examples

```
## Not run:  
a <- celsius(rnorm(100)*10)  
plot(a)  
b <- celsius(matrix(rnorm(100)*10, ncol = 10))  
print(head(b))  
  
## End(Not run)
```

check_nt

Check the max number of threads

Description

get_threads check the number of threads in this machine

Usage

```
check_nt()
```

Value

Integer with the max number of threads

Examples

```
{  
  check_nt()  
}
```

cold_mileage	<i>Fraction of mileage driven with a cold engine or catalizer below normal temperature</i>
--------------	--

Description

This function depends length of trip and on ambient temperature. From the guidelines EMEP/EEA air pollutant emission inventory guidebook <http://www.eea.europa.eu/themes/air/emep-eea-air-pollutant-emission-inventory-guidebook>

Usage

```
cold_mileage(ltrip, ta)
```

Arguments

ltrip	Numeric; Length of trip. It must be in 'units' km.
ta	Numeric or data.frame; average monthly temperature Celsius. If it is a data.frame, it is convenient that each column is each month.

Note

This function is set so that values vaires between 0 and 1.

Examples

```
## Not run:  
lkm <- units::set_units(1:10, km)  
ta <- celsius(matrix(0:9, ncol = 12, nrow = 10))  
a <- cold_mileage(lkm, rbind(ta, ta))  
(a)  
filled.contour(as.matrix(a), col = cptcity::lucky(n = 16))  
  
## End(Not run)
```

colplot	<i>Function to plot columns of data.frames</i>
---------	--

Description

`colplot` plots columns of data.frame

Usage

```
colplot(
  df,
  x,
  cols = names(df),
  xlab = "",
  ylab = "",
  main = NULL,
  theme = "black",
  col = cptcity::cpt(pal = cptcity::find_cpt("pastel")[4], n = length(names(df))),
  type = "b",
  lwd = 2,
  pch = 1:ncol(df),
  familyfont = "",
  spl = 5,
  all_values = FALSE
)
```

Arguments

df	data.frame.
x	the coordinates of points in the plot. (optional)
cols	Character, columns of data.frame.
xlab	a label for the x axis, defaults to a description of x.
ylab	a label for the x axis, defaults to a description of x.
main	Character, a main title for the plot, see also title .
theme	Character; "black", "dark", "clean", "ink"
col	The colors for lines and points. Multiple colors can be specified so that each point can be given its own color. If there are fewer colors than points they are recycled in the standard fashion. Default are cptcity colour palette "kst_18_pastels"
type	1-character string giving the type of plot desired. The following values are possible, for details, see plot: "p" for points, "l" for lines, "b" for both points and lines, "c" for empty points joined by lines, "o" for overplotted points and lines, "s" and "S" for stair steps and "h" for histogram-like vertical lines. Finally, "n" does not produce any points or lines.
lwd	a vector of line widths, see par .
pch	plotting 'character', i.e., symbol to use. This can either be a single character or an integer code for one of a set of graphics symbols. The full set of S symbols is available with pch = 0:18, see the examples below. (NB: R uses circles instead of the octagons used in S.). Value pch = "." (equivalently pch = 46) is handled specially. It is a rectangle of side 0.01 inch (scaled by cex). In addition, if cex = 1 (the default), each side is at least one pixel (1/72 inch on the pdf, postscript and xfig devices). For other text symbols, cex = 1 corresponds to the default fontsize of the device, often specified by an argument pointsize. For pch in 0:25 the default size is about 75 the character height (see par("cin")).

familyfont	"Character" to specify font, default is "", options "serif", "sans", "mono" or more according device
spl	numer to control space for legend, default is 5.
all_values	logical, if FALSE shows only positive > 0 values

Value

a nice plot

Note

This plot shows values > 0 by default. To plot all values, use `all_values = TRUE`

See Also

[par](#)

Other helpers: [dmonth\(\)](#), [to_latex\(\)](#), [wide_to_long\(\)](#)

Examples

```
## Not run:
a <- ef_cetesb("CO", c("PC_G", "PC_FE", "PC_FG"), agemax = 20)
colplot(df = a, ylab = "CO [g/km]", theme = "dark", pch = NULL, type = "l")
#colplot(df = a, cols = "PC_FG", main = "EF", ylab = "CO [g/km]")
#colplot(df = a, ylab = "CO [g/km]", theme = "clean")

## End(Not run)
```

decoder

Description data.frame for MOVES

Description

A data.frame descriptors to use MOVES functions

Usage

```
data(decoder)
```

Format

A data frame with 69 rows and 4 columns:

CategoryField dayID, sourceTypID, roadTypeID, pollutantID and procesID

pollutantID Associated number

Description Associatd description

V4 pollutants

Source

US/EPA MOVES

dmonth	<i>Number of days of the month</i>
--------	------------------------------------

Description

`ef_ldv_speed` return the number of day sof the month

Usage

```
dmonth(year, month)
```

Arguments

year	Numeric
month	Numeric

Value

days of the month

See Also

Other helpers: `colplot()`, `to_latex()`, `wide_to_long()`

Examples

```
## Not run:  
dmonth(2022, 1)  
  
## End(Not run)
```

ef_cetesb	<i>Emissions factors for Environment Company of Sao Paulo, Brazil (CETESB)</i>
-----------	--

Description

`ef_cetesb` returns a vector or data.frame of Brazilian emission factors.

Usage

```
ef_cetesb(
  p,
  veh,
  year = 2017,
  agemax = 40,
  scale = "default",
  sppm,
  full = FALSE,
  einput,
  verbose = FALSE,
  csv
)
```

Arguments

p	Character; Pollutants: "CO", "HC", "NMHC", "CH4", "NOx", "CO2", "RCHO" (aldehydes + formaldehyde), "ETOH", "PM", "N2O", "KML", "FC", "NO2", "NO", "NH3", "gD/KWH", "gCO2/KWH", "RCHO_0km" (aldehydes + formaldehyde), "PM25RES", "PM10RES", "CO_0km", "HC_0km", "NMHC_0km", "NOx_0km", "NO2_0km", "NO_0km", "RCHO_0km" and "ETOH_0km", "FS" (fuel sales) (g/km). If scale = "tunnel" is used, there is also "ALD" for aldehydes and "HCHO" for formaldehydes Evaporative emissions at average temperature ranges: "D_20_35", "S_20_35", "R_20_35", "D_10_25", "S_10_25", "R_10_25", "D_0_15", "S_0_15" and "R_0_15" where D means diurnal (g/day), S hot/warm soak (g/trip) and R hot/warm running losses (g/trip). The deteriorated emission factors are calculated inside this function.
veh	Character; Vehicle categories: "PC_G", "PC_FG", "PC_FE", "PC_E", "LCV_G", "LCV_FG", "LCV_FE", "LCV_E", "LCV_D", "TRUCKS_SL", "TRUCKS_L", "TRUCKS_M", "TRUCKS_SH", "TRUCKS_H", "BUS_URBAN", "BUS_MICRO", "BUS_COACH", "BUS_ARTIC", "MC_150_G", "MC_150_500_G", "MC_500_G", "MC_150_FG", "MC_150_500_FG", "MC_500_FG", "MC_150_FE", "MC_150_500_FE", "MC_500_FE", "CICLOMOTOR", "GNV"
year	Numeric; Filter the emission factor to start from a specific base year. If project is 'constant' values above 2017 and below 1980 will be repeated
agemax	Integer; age of oldest vehicles for that category

scale	Character; values "default","tunnel" o "tunnel2018". If "tunnel", emission factors are scaled to represent EF measurements in tunnels in Sao Paulo
sppm	Numeric, sulfur (sulphur) in ppm in fuel.
full	Logical; To return a data.frame instead or a vector adding Age, Year, Brazilian emissions standards and its euro equivalentents.
efinput	data.frame with efinput structure of sysdata cetesb. Allow apply deterioration for future emission factors
verbose	Logical; To show more information
csv	String with the path to download the ef in a .csv file. For instance, ef.csv

Value

A vector of Emission Factor or a data.frame

Note

The new convention for vehicles names are translated from CETESB report:

veh	description
PC_G	Passenger Car Gasohol (Gasoline + 27perc of anhydrous ethanol)
PC_E	Passenger Car Ethanol (hydrous ethanol)
PC_FG	Passenger Car Flex Gasohol (Gasoline + 27perc of anhydrous ethanol)
PC_FE	Passenger Car Flex Ethanol (hydrous ethanol)
LCV_G	Light Commercial Vehicle Gasohol (Gasoline + 27perc of anhydrous ethanol)
LCV_E	Light Commercial Vehicle Ethanol (hydrous ethanol)
LCV_FG	Light Commercial Vehicle Flex Gasohol (Gasoline + 27perc of anhydrous ethanol)
LCV_FE	Light Commercial Vehicle Flex Ethanol (hydrous ethanol)
LCV_D	Light Commercial Vehicle Diesel (5perc bio-diesel)
TRUCKS_SL_D	Trucks Semi Light Diesel (5perc bio-diesel)
TRUCKS_L_D	Trucks Light Diesel (5perc bio-diesel)
TRUCKS_M_D	Trucks Medium Diesel (5perc bio-diesel)
TRUCKS_SH_D	Trucks Semi Heavy Diesel (5perc bio-diesel)
TRUCKS_H_D	Trucks Heavy Diesel (5perc bio-diesel)
BUS_URBAN_D	Urban Bus Diesel (5perc bio-diesel)
BUS_MICRO_D	Micro Urban Bus Diesel (5perc bio-diesel)
BUS_COACH_D	Coach (inter-state) Bus Diesel (5perc bio-diesel)
BUS_ARTIC_D	Articulated Urban Bus Diesel (5perc bio-diesel)
MC_150_G	Motorcycle engine less than 150cc Gasohol (Gasoline + 27perc of anhydrous ethanol)
MC_150_500_G	Motorcycle engine 150-500cc Gasohol (Gasoline + 27perc of anhydrous ethanol)
MC_500_G	Motorcycle greater than 500cc Gasohol (Gasoline + 27perc of anhydrous ethanol)
MC_150_FG	Flex Motorcycle engine less than 150cc Gasohol (Gasoline + 27perc of anhydrous ethanol)
MC_150_500_FG	Flex Motorcycle engine 150-500cc Gasohol (Gasoline + 27perc of anhydrous ethanol)
MC_500_FG	Flex Motorcycle greater than 500cc Gasohol (Gasoline + 27perc of anhydrous ethanol)
MC_150_FE	Flex Motorcycle engine less than 150cc Ethanol (hydrous ethanol)
MC_150_500_FE	Flex Motorcycle engine 150-500cc Ethanol (hydrous ethanol)
MC_500_FE	Flex Motorcycle greater than 500cc Ethanol (hydrous ethanol)
PC_ELEC	Passenger Car Electric
LCV_ELEC	Light Commercial Vehicle Electric

The percentage varies of biofuels varies by law.

This emission factors are not exactly the same as the report of CETESB.

1) In this emission factors, there is also NO and NO₂ based on split by published in the EMEP/EEA air pollutant emission inventory guidebook.

2) Also, the emission factors were extended till 50 years of use, repeating the oldest value.

3) CNG emission factors were expanded to other pollutants by comparison of US.EPA-AP42 emission factor: Section 1.4 Natural Gas Combustion.

In the previous versions I used the letter 'd' for deteriorated. I removed the letter 'd' internally to not break older code.

If by mistake, the user inputs one of veh names from the old convention, they are internally changed to the new convention: "SLT", "LT", "MT", "SHT", "HT", "UB", "SUB", "COACH", "ARTIC", "M_G_150", "M_G_150_500", "M_G_500", "M_FG_150", "M_FG_150_500", "M_FG_500", "M_FE_150", "M_FE_150_500", "M_FE_500", PC_ELEC, LCV_ELEC, TRUCKS_ELEC, BUS_ELEC, MC_150_ELEC, MC_150_500_ELEC, MC_500_ELEC

If pollutant is "SO₂", it needs ppm. It is designed when veh has length 1, if it has length 2 or more, it will show a warning

Emission factor for vehicles older than the reported by CETESB were filled with las highest EF

- Range EF from PC and LCV otto: 2018 - 1982. EF for 1981 and older as moving average.
- Range LCV diesel : 2018 - 2006. EF for 2005 and older as moving average.
- Range Trucks and Buse: 2018 - 1998. EF for 1997 and older as moving average.
- Range MC Gasoline: 2018 - 2003. EF for 2002 and older as moving average.
- Range MC Flex 150-500cc and >500cc: 2018 - 2012. EF for 2011 and older as moving average.

Currently, 2020, there are not any system for recovery of fuel vapors in Brazil. Hence, the FS takes into account the vapour that comes from the fuel tank inside the car and released into the atmosphere when injecting new fuel. There are discussions about increasing implementing stage I and II and/or ORVR these days. The ef FS is calculated by transforming g FC/km into (L/KM)*g/L with g/L 1.14 fgor gasoline and 0.37 for ethanol (CETESB, 2016). The density considered is 0.75425 for gasoline and 0.809 for ethanol (t/m³)

CETESB emission factors did not cover evaporative emissions from motorcycles, which occur. Therefore, in the absence of better data, it was assumed the same ratio from passenger cars.

Li, Lan, et al. "Exhaust and evaporative emissions from motorcycles fueled with ethanol gasoline blends." *Science of the Total Environment* 502 (2015): 627-631.

If scale is used with tunnel, the references are:

- Pérez-Martinez, P. J., Miranda, R. M., Nogueira, T., Guardani, M. L., Fornaro, A., Ynoue, R., and Andrade, M. F. (2014). Emission factors of air pollutants from vehicles measured inside road tunnels in Sao Paulo: case study comparison. *International Journal of Environmental Science and Technology*, 11(8), 2155-2168.
- Nogueira, T., de Souza, K. F., Fornaro, A., de Fatima Andrade, M., and de Carvalho, L. R. F. (2015). On-road emissions of carbonyls from vehicles powered by biofuel blends in traffic tunnels in the Metropolitan Area of Sao Paulo, Brazil. *Atmospheric Environment*, 108, 88-97.

- Nogueira, T., et al (2021). In preparation (for tunnel 2018)

Emission factors for resuspension applies **only** with top-down approach as a experimental feature. Units are g/(streets*veh)/day. These values were derived form a bottom-up resuspension emissions from metropolitan area of Sao Paulo 2018, assuming 50000 streets

NH3 from EEA Tier 2

References

Emissoes Veiculares no Estado de Sao Paulo 2016. Technical Report. url: <https://cetesb.sp.gov.br/veicular/relatorios-e-publicacoes/>.

Examples

```
## Not run:
a <- ef_cetesb(p = "CO", veh = "PC_G")
a <- ef_cetesb(p = "NOx", veh = "TRUCKS_M_D")
a <- ef_cetesb("R_10_25", "PC_G")
a <- ef_cetesb("CO", c("PC_G", "PC_FE"))
ef_cetesb(p = "CO", veh = "PC_G", year = 1970, agemax = 40)
ef_cetesb(p = "CO", veh = "TRUCKS_L_D", year = 2018)
ef_cetesb(p = "CO", veh = "SLT", year = 2018) # olds names
a <- ef_cetesb(p = "NMHC", veh = c("PC_G", "PC_FG", "PC_FE", "PC_E"), year = 2018, agemax = 20)
colplot(a, main = "NMHC EF", ylab = "[g/km]", xlab = "Years of use")
ef_cetesb(p = "PM25RES", veh = "PC_ELEC", year = 1970, agemax = 40)
ef_cetesb(p = "PM25RES", veh = "BUS_ELEC", year = 1970, agemax = 40)

## End(Not run)
```

ef_china

Emissions factors from Chinese emissions guidelines

Description

`ef_china` returns emission factors as vector or data.frames. The emission factors comes from the chinese emission guidelines (v3) from the Chinese Ministry of Ecology and Environment <http://www.mee.gov.cn/gkml/hbb/bj>

Usage

```
ef_china(
  v = "PV",
  t = "Small",
  f = "G",
  standard,
  p,
  k = 1,
  ta = celsius(15),
  humidity = 0.5,
  altitude = 1000,
```



```

    speed = Speed(30),
    baseyear_det = 2016,
    sulphur = 50,
    load_factor = 0.5,
    details = FALSE,
    correction_only = FALSE
)

```

Arguments

v	Character; category vehicle: "PV" for Passenger Vehicles or "Trucks"
t	Character; sub-category of of vehicle: PV Gasoline: "Mini", "Small", "Medium", "Large", "Taxi", "Motorcycles", "Moped", PV Diesel: "Mediumbus", "Largebus", "3-Wheel". Trucks: "Mini", "Light", "Medium", "Heavy"
f	Character; fuel: "G", "D"
standard	Character or data.frame; "PRE", "I", "II", "III", "IV", "V". When it is a data.frame, it each row is a different region and ta, humidity, altitud, speed, sulphur and load_factor lengths have the same as the number of rows.
p	Character; pollutant: "CO", "NOx", "HC", "PM", "Evaporative_driving" or "Evaporative_parking"
k	Numeric; multiplication factor
ta	Numeric; temperature of ambient in celcius degrees. When standard is a data.frame, the length must be equal to the number of rows of standard.
humidity	Numeric; relative humidity. When standard is a data.frame, the length must be equal to the number of rows of standard.
altitude	Numeric; altitude in meters. When standard is a data.frame, the length must be equal to the number of rows of standard.
speed	Numeric; altitude in km/h When standard is a data.frame, the length must be equal to the number of rows of standard.
baseyear_det	Integer; any of 2014, 2015, 2016, 2017, 2018
sulphur	Numeric; sulphur in ppm. When standard is a data.frame, the length must be equal to the number of rows of standard.
load_factor	Numeric; When standard is a data.frame, the length must be equal to the number of rows of standard.
details	Logical; When TRUE, it shows a description of the vehicle in chinese and english. Only when length standard is 1.
correction_only	Logical; When TRUE, return only correction factors.

Value

An emission factor

Note

Combination of vehicles:

v	t	f
PV	Mini	G
PV	Small	G
PV	Medium	G
PV	Large	G
PV	Taxi	G
PV	Bus	G
PV	Motorcycles	G
PV	Moped	G
PV	Mini	D
PV	Small	D
PV	Mediumbus	D
PV	Largebus	D
PV	Bus	D
PV	3-Wheel	D
PV	Small	ALL
PV	Mediumbus	ALL
PV	Largebus	ALL
PV	Taxi	ALL
PV	Bus	ALL
Trucks	Bus	G
Trucks	Light	G
Trucks	Medium	G
Trucks	Heavy	G
Trucks	Light	D
Trucks	Medium	D
Trucks	Heavy	D
Trucks	Low Speed	D
Trucks	Mini	D

See Also

[ef_ldv_speed emis_hot_td](#)

Examples

```
## Not run:
# when standard is 'character'
# Checking
df_st <- rev(c(as.character(as.roman(5:1)), "PRE"))
ef_china(t = "Mini", f = "G", standard = df_st, p = "CO")
ef_china(t = "Mini", f = "G", standard = df_st, p = "HC")
ef_china(t = "Mini", f = "G", standard = df_st, p = "NOx")
ef_china(t = "Mini", f = "G", standard = df_st, p = "PM2.5")
ef_china(t = "Mini", f = "G", standard = df_st, p = "PM10")

ef_china(t = "Small", f = "G", standard = df_st, p = "CO")
ef_china(t = "Small", f = "G", standard = df_st, p = "HC")
ef_china(t = "Small", f = "G", standard = df_st, p = "NOx")
```

```

ef_china(t = "Small", f = "G", standard = df_st, p = "PM2.5")
ef_china(t = "Small", f = "G", standard = df_st, p = "PM10")

ef_china(t = "Mini",
         standard = c("PRE"),
         p = "CO",
         k = 1,
         ta = celsius(15),
         humidity = 0.5,
         altitude = 1000,
         speed = Speed(30),
         baseyear_det = 2014,
         sulphur = 50,
         load_factor = 0.5,
         details = FALSE)
ef_china(standard = c("PRE", "I"), p = "CO", correction_only = TRUE)

# when standard is 'data.frame'
df_st <- matrix(c("V", "IV", "III", "III", "II", "I", "PRE"), nrow = 2, ncol = 7, byrow = TRUE)
df_st <- as.data.frame(df_st)
a <- ef_china(standard = df_st,
              p = "PM10",
              ta = rep(celsius(15), 2),
              altitude = rep(1000, 2),
              speed = rep(Speed(30), 2),
              sulphur = rep(50, 2))

dim(a)
dim(df_st)
ef_china(standard = df_st, p = "PM2.5", ta = rep(celsius(20), 2),
         altitude = rep(1501, 2), speed = rep(Speed(29), 2), sulphur = rep(50, 2))
a

# when standard, temperature and humidity are data.frames
# assuming 10 regions
df_st <- matrix(c("V", "IV", "III", "III", "II", "I", "PRE"), nrow = 10, ncol = 7, byrow = TRUE)
df_st <- as.data.frame(df_st)
df_t <- matrix(21:30, nrow = 10, ncol = 12, byrow = TRUE)
df_t <- as.data.frame(df_t)
for(i in 1:12) df_t[, i] <- celsius(df_t[, i])

# assuming 10 regions
df_h <- matrix(seq(0.4, 0.5, 0.05), nrow = 10, ncol = 12, byrow = TRUE)
df_h <- as.data.frame(df_h)
a <- ef_china(standard = df_st, p = "CO", ta = df_t, humidity = df_h,
              altitude = rep(1501, 10), speed = rep(Speed(29), 10), sulphur = rep(50, 10))
a
a <- ef_china(standard = df_st, p = "PM2.5", ta = df_t, humidity = df_h,
              altitude = rep(1501, 10), speed = rep(Speed(29), 10), sulphur = rep(50, 10))
a
a <- ef_china(standard = df_st, p = "PM10", ta = df_t, humidity = df_h,
              altitude = rep(1501, 10), speed = rep(Speed(29), 10), sulphur = rep(50, 10))
a

```

```
dim(a)
## End(Not run)
```

 ef_eea

Emissions factors from European Environment Agency

Description

`ef_cetesb` returns a vector or data.frame of Brazilian emission factors.

Usage

```
ef_eea(
  category,
  fuel,
  segment,
  euro,
  tech,
  pol,
  mode,
  slope,
  load,
  speed,
  fcorr = rep(1, 8)
)
```

Arguments

category	String: "PC" (Passenger Cars), "LCV" (Light Commercial Vehicles), "TRUCKS" (Heavy Duty Trucks), "BUS" (Buses) or "MC" (Motorcycles or L-Category as in EEA 2019).
fuel	String: "G", "G HY", "G PHEV G", "G PHEV ELEC", "D", "D PHEV D", "D PHEV ELEC", "LPG BIFUEL LPG", "LPG BIFUEL G", "CNG BIFUEL CNG", "CNG BIFUEL G", "D HY D", "D HY ELEC", "CNG", "BIO D"
segment	String for type of vehicle (try different, the function will show values).
euro	String; euro standard: "PRE", "IMPROVED CONVENTIONAL", "OPEN LOOP", "ECE 15/00-01", "ECE 15/02", "ECE 15/03", "ECE 15/04". "I", "II", "III", "IV", "V", "VI A/B/C", "VI D", "VI D-TEMP", "VI D/E", "EEV".
tech	String; technology: "DPF", "DPF With S/W Update", "DPF+SCR" "EGR", "GDI", "GDI+GPF", "LNT+DPF", "PFI", "SCR".
pol	String: "CO", "NOx", "NMHC" (VOC), "PM" (PM Exhaust), "EC", "CH4", "NH3", "N2O"
mode	String: "Urban Peak", "Urban Off Peak", "Rural", "Highway", NA.
slope	Numeric; 0.00, -0.06, -0.04, -0.02, 0.02, 0.04, 0.06, or NA

load	Numeric; 0.0,0.5, 1.0 or NA
speed	Numeric; optional numeric in km/h.
fcorr	Numeric; Correction by fuel properties by euro technology. See fuel_corr . The order from first to last is "PRE", "I", "II", "III", "IV", "V", "VI", "or other VI. Default is 1

Value

Return a function depending of speed or numeric (g/km)

Examples

```
{
# ef_eea(category = "I DONT KNOW")
ef_eea(category = "PC",
fuel = "G",
segment = "Small",
euro = "I",
tech = NA,
pol = "CO",
mode = NA,
slope = 0,
load = 0)(10)
}
```

ef_evap

Evaporative emission factor

Description

[ef_evap](#) is a lookup table with tier 2 evaporative emission factors from EMEP/EEA emisison guidelines

Usage

```
ef_evap(
  ef,
  v,
  cc,
  dt,
  ca,
  pollutant = "NMHC",
  k = 1,
  ltrip,
  kmday,
  show = FALSE,
  verbose = FALSE
)
```

Arguments

ef	Name of evaporative emission factor as *eshotc*: mean hot-soak with carburetor, *eswarmc*: mean cold and warm-soak with carburetor, eshotfi: mean hot-soak with fuel injection, *erhotc*: mean hot running losses with carburetor, *erwarmc* mean cold and warm running losses, *erhotfi* mean hot running losses with fuel injection. Length of ef 1.
v	Type of vehicles, "PC", "Motorcycle", "Motorcycle_2S" and "Moped"
cc	Size of engine in cc. PC "<=1400", "1400_2000" and ">2000" Motorcycle_2S: "<=50". Motorcycles: ">50", "<=250", "250_750" and ">750". Only engines of >750 has canister.
dt	Character or Numeric: Average monthly temperature variation: "-5_10", "0_15", "10_25" and "20_35". This argument can vector with several elements. dt can also be data.frame, but it is recommended that the number of columns are each month. So that dt varies in each row and each column.
ca	Size of canister: "no" meaning no canister, "small", "medium" and "large".
pollutant	Character indicating any of the covered pollutants: "NMHC", "ethane", "propane", "i-butane", "n-butane", "i-pentane", "n-pentane", "2-methylpentane", "3-methylpentane", "n-hexane", "n-heptane", "propene", "trans-2-butene", "isobutene", "cis-2-butene", "1,3-butadiene", "trans-2-pentene", "cis-2-pentene", "isoprene", "propyne", "acetylene", "benzene", "toluene", "ethylbenzene", "m-xylene", "o-xylene", "1,2,4-trimethylbenzene" and "1,3,5-trimethylbenzene". Default is "NMHC"
k	multiplication factor
ltrip	Numeric; Length of trip. Experimental feature to conter g/trip and g/proced (assuming proced similar to trip) in g/km.
kmday	Numeric; average daily mileage. Experimental option to convert g/day in g/km. it is an information more solid than to know the average number of trips per day.
show	when TRUE shows row of table with respective emission factor.
verbose	Logical; To show more information

Value

emission factors in g/trip or g/proced. The object has class (g) but it order to know it is g/trip or g/proceed the argument show must by T

Note

Diurnal loses occur with daily temperature variations. Running loses occur during vehicles use. Hot soak emission occur following vehicles use.

References

Mellios G and Ntziachristos 2016. Gasoline evaporation. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2009

Examples

```
## Not run:
# Do not run
a <- ef_evap(ef = "eshotc", v = "PC", cc = "<=1400", dt = "0_15", ca = "no",
pollutant = "cis-2-pentene")
a <- ef_evap(ef = "ed", v = "PC", cc = "<=1400", dt = "0_15", ca = "no",
show = TRUE)
a <- ef_evap(ef = c("erhotc", "erhotc"), v = "PC", cc = "<=1400",
dt = "0_15", ca = "no",
show = TRUE)
a <- ef_evap(ef = c("erhotc", "erhotc"), v = "PC", cc = "<=1400",
dt = "0_15", ca = "no",
show = FALSE)
a <- ef_evap(ef = "eshotc", v = "PC", cc = "<=1400", dt = "0_15", ca = "no",
show = TRUE)
ef_evap(ef = "erhotc", v = "PC", cc = "<=1400", dt = "0_15", ca = "no",
show = TRUE)
temps <- 10:20
a <- ef_evap(ef = "erhotc", v = "PC", cc = "<=1400", dt = temps, ca = "no",
show = TRUE)
dt <- matrix(rep(1:24,5), ncol = 12) # 12 months
dt <- celsius(dt)
a <- ef_evap(ef = "erhotc", v = "PC", cc = "<=1400",
dt = dt, ca = "no")
lkm <- units::set_units(10, km)
a <- ef_evap(ef = "erhotc", v = "PC", cc = "<=1400", ltrip = lkm,
dt = dt, ca = "no")

## End(Not run)
```

ef_fun

Experimental: Returns a function of Emission Factor by age of use

Description

[ef_fun](#) returns amount of vehicles at each age

Usage

```
ef_fun(
  ef,
  type = "logistic",
  x = 1:length(ef),
  x0 = mean(ef),
  k = 1/4,
  L = max(ef)
)
```

Arguments

ef	Numeric; numeric vector of emission factors.
type	Character; "logistic" by default so far.
x	Numeric; vector for ages of use.
x0	Numeric; the x-value of the sigmoid's midpoint,
k	Numeric; the steepness of the curve.
L	Integer; the curve's maximum value.

Value

dataframe of age distribution of vehicles at each street.

References

https://en.wikipedia.org/wiki/Logistic_function

Examples

```
## Not run:
data(fe2015)
CO <- vein::EmissionFactors(fe2015[fe2015$Pollutant == "CO", "PC_G"])
ef_logit <- ef_fun(ef = CO, x0 = 27, k = 0.4, L = 33)
plot(ef_logit, type = "b", pch = 16)
lines(ef_logit, pch = 16, col = "blue")

## End(Not run)
```

ef_hdv_scaled

Scaling constant with speed emission factors of Heavy Duty Vehicles

Description

`ef_hdv_scaled` creates a list of scaled functions of emission factors. A scaled emission factor which at a speed of the driving cycle (SDC) gives a desired value. This function needs a dataframe with local emission factors with a column with the name "Euro_HDV" indicating the Euro equivalence standard, assuming that there are available local emission factors for several consecutive years.

Usage

```
ef_hdv_scaled(df, dfcol, SDC = 34.12, v, t, g, eu, gr = 0, l = 0.5, p)
```


Arguments

df	deprecated
dfcol	Column of the dataframe with the local emission factors eg df\$dfcol
SDC	Speed of the driving cycle
v	Category vehicle: "Coach", "Trucks" or "Ubus"
t	Sub-category of of vehicle: "3Axes", "Artic", "Midi", "RT", "Std" and "TT"
g	Gross weight of each category: "<=18", ">18", "<=15", ">15 & <=18", "<=7.5", ">7.5 & <=12", ">12 & <=14", ">14 & <=20", ">20 & <=26", ">26 & <=28", ">28 & <=32", ">32", ">20 & <=28", ">28 & <=34", ">34 & <=40", ">40 & <=50" or ">50 & <=60"
eu	Euro emission standard: "PRE", "I", "II", "III", "IV" and "V"
gr	Gradient or slope of road: -0.06, -0.04, -0.02, 0.00, 0.02, 0.04 or 0.06
l	Load of the vehicle: 0.0, 0.5 or 1.0
p	Pollutant: "CO", "FC", "NOx" or "HC"

Value

A list of scaled emission factors g/km

Note

The length of the list should be equal to the name of the age categories of a specific type of vehicle

Examples

```
## Not run:
# Do not run
data(fe2015)
co1 <- fe2015[fe2015$Pollutant=="CO",]
lef <- ef_hdv_scaled(dfcol = co1$LT, v = "Trucks", t = "RT",
g = "<=7.5", eu = co1$Euro_HDV, gr = 0, l = 0.5, p = "CO")
length(lef)
plot(x = 0:150, y = lef[[36]](0:150), col = "red", type = "b", ylab = "[g/km]",
pch = 16, xlab = "[km/h]",
main = "Variation of emissions with speed of oldest vehicle")
plot(x = 0:150, y = lef[[1]](0:150), col = "blue", type = "b", ylab = "[g/km]",
pch = 16, xlab = "[km/h]",
main = "Variation of emissions with speed of newest vehicle")

## End(Not run)
```

ef_hdv_speed

*Emissions factors for Heavy Duty Vehicles based on average speed***Description**

This function returns speed dependent emission factors. The emission factors comes from the guidelines EMEP/EEA air pollutant emission inventory guidebook <http://www.eea.europa.eu/themes/air/emep-eea-air-pollutant-emission-inventory-guidebook>

Usage

```
ef_hdv_speed(
  v,
  t,
  g,
  eu,
  x,
  gr = 0,
  l = 0.5,
  p,
  k = 1,
  show.equation = FALSE,
  speed,
  fcorr = rep(1, 8)
)
```

Arguments

v	Category vehicle: "Coach", "Trucks" or "Ubus"
t	Sub-category of of vehicle: "3Axes", "Artic", "Midi", "RT", "Std" and "TT"
g	Gross weight of each category: "<=18", ">18", "<=15", ">15 & <=18", "<=7.5", ">7.5 & <=12", ">12 & <=14", ">14 & <=20", ">20 & <=26", ">26 & <=28", ">28 & <=32", ">32", ">20 & <=28", ">28 & <=34", ">34 & <=40", ">40 & <=50" or ">50 & <=60"
eu	Euro emission standard: "PRE", "I", "II", "III", "IV", "V". Also "II+CRDPF", "III+CRDPF", "IV+CRDPF", "II+SCR", "III+SCR" and "V+SCR" for pollutants Number of particles and Active Surface.
x	Numeric; if pollutant is "SO2", it is sulphur in fuel in ppm, if is "Pb", Lead in fuel in ppm.
gr	Gradient or slope of road: -0.06, -0.04, -0.02, 0.00, 0.02, 0.04 or 0.06
l	Load of the vehicle: 0.0, 0.5 or 1.0
p	Character; pollutant: "CO", "FC", "NOx", "NO", "NO2", "HC", "PM", "NMHC", "CH4", "CO2", "SO2" or "Pb". Only when p is "SO2" pr "Pb" x is needed. See notes.
k	Multiplication factor

show.equation	Option to see or not the equation parameters
speed	Numeric; Speed to return Number of emission factor and not a function. It needs units in km/h
fcorr	Numeric; Correction by fuel properties by euro technology. See fuel_corr . The order from first to last is "PRE", "I", "II", "III", "IV", "V", VI, "VIc". Default is 1

Value

an emission factor function which depends of the average speed V g/km

Note

Pollutants (g/km): "CO", "NOx", "HC", "PM", "CH4", "NMHC", "CO2", "SO2", "Pb".

Black Carbon and Organic Matter (g/km): "BC", "OM"

PAH and POP (g/km): See [speciate](#) **Dioxins and furans (g equivalent toxicity / km):** See [speciate](#)

Metals (g/km): See [speciate](#)

Active Surface (cm2/km) See [speciate](#)

Total Number of particles (N/km): See [speciate](#)

The available standards for Active Surface or number of particles are: Euro II and III Euro II and III + CRDPF Euro II and III + SCR Euro IV + CRDPF Euro V + SCR

The categories Pre Euro and Euro I were assigned with the factors of Euro II and Euro III The categories euro IV and euro V were assigned with euro III + SCR

See Also

[fuel_corr](#) [emis](#) [ef_ldv_cold](#) [speciate](#)

Examples

```
## Not run:
# Quick view
pol <- c("CO", "NOx", "HC", "NMHC", "CH4", "FC", "PM", "CO2", "SO2")
f <- sapply(1:length(pol), function(i){
  print(pol[i])
  ef_hdv_speed(v = "Trucks", t = "RT", g = "<=7.5", e = "II", gr = 0,
    l = 0.5, p = pol[i], x = 10)(30)
})
f

V <- 0:130
ef1 <- ef_hdv_speed(v = "Trucks", t = "RT", g = "<=7.5", e = "II", gr = 0,
  l = 0.5, p = "HC")
plot(1:130, ef1[1:130], pch = 16, type = "b")
euro <- c(rep("V", 5), rep("IV", 5), rep("III", 5), rep("II", 5),
  rep("I", 5), rep("PRE", 15))
lef <- lapply(1:30, function(i) {
```

```

ef_hdv_speed(v = "Trucks", t = "RT", g = ">32", gr = 0,
eu = euro[i], l = 0.5, p = "NOx",
show.equation = FALSE)(25) })
efs <- EmissionFactors(unlist(lef)) #returns 'units'
plot(efs, xlab = "age")
lines(efs, type = "l")
a <- ef_hdv_speed(v = "Trucks", t = "RT", g = ">32", gr = 0,
eu = euro, l = 0.5, p = "NOx", speed = Speed(0:125))
a$speed <- NULL
filled.contour(as.matrix(a), col = cptcity::lucky(n = 24),
xlab = "Speed", ylab = "Age")
persp(x = as.matrix(a), theta = 35, xlab = "Speed", ylab = "Age",
zlab = "NOx [g/km]", col = cptcity::lucky(), phi = 25)
aa <- ef_hdv_speed(v = "Trucks", t = "RT", g = ">32", gr = 0,
eu = rbind(euro, euro), l = 0.5, p = "NOx", speed = Speed(0:125))

## End(Not run)

```

ef_im

Emission factors depending on accumulated mileage

Description

`ef_im` calculate the theoretical emission factors of vehicles. The approach is different from including deterioration factors (`emis_det`) but similar, because they represent how much emits a vehicle with a normal deterioration, but that it will pass the Inspection and Maintenance program.

Usage

```
ef_im(ef, tc, amileage, max_amileage, max_ef, verbose = TRUE)
```

Arguments

<code>ef</code>	Numeric; emission factors of vehicles with 0 mileage (new vehicles).
<code>tc</code>	Numeric; rate of growth of emissions by year of use.
<code>amileage</code>	Numeric; Accumulated mileage by age of use.
<code>max_amileage</code>	Numeric; Max accumulated mileage. This means that after this value, mileage is constant.
<code>max_ef</code>	Numeric; Max ef. This means that after this value, ef is constant.
<code>verbose</code>	Logical; if you want detailed description.

Value

An emission factor of a deteriorated vehicle under normal conditions which would be approved in a inspection and maintenance program.

Examples

```
## Not run:
# Do not run
# Passenger Cars PC
data(fkm)
# cumulative mileage from 1 to 50 years of use, 40:50
mil <- cumsum(fkm$KM_PC_E25(1:10))
ef_im(ef = seq(0.1, 2, 0.2), seq(0.1, 1, 0.1), mil)

## End(Not run)
```

ef_ive	<i>Base emissions factors from International Vehicle Emissions (IVE) model</i>
--------	--

Description

`ef_ive` returns the base emission factors from the the IVE model. This function depend on vectorized mileage, which means your can enter with the mileage by age of use and the name of the pollutant.

Usage

```
ef_ive(
  description = "Auto/Sml Truck",
  fuel = "Petrol",
  weight = "Light",
  air_fuel_control = "Carburetor",
  exhaust = "None",
  evaporative = "PCV",
  mileage,
  pol,
  details = FALSE
)
```

Arguments

description	Character; "Auto/Sml Truck" "Truck/Bus" or "Sml Engine".
fuel	Character; "Petrol", "NG Retrofit", "Natural Gas", "Prop Retro.", "Propane", "EthOH Retrofit", "OEM Ethanol", "Diesel", "Ethanol" or "CNG/LPG".
weight	Character; "Light", "Medium", "Heavy", "Lt", "Med" or "Hvy"
air_fuel_control	Character; One of the following characters: "Carburetor", "Single-Pt FI", "Multi-Pt FI", "Carb/Mixer", "FI", "Pre-Chamber Inject.", "Direct Injection", "2-Cycle", "2-Cycle, FI", "4-Cycle, Carb", "4-Cycle, FI" "4-Cycle"

exhaust	Character: "None", "2-Way", "2-Way/EGR", "3-Way", "3-Way/EGR", "None/EGR", "LEV", "ULEV", "SULEV", "EuroI", "EuroII", "EuroIII", "EuroIV", "Hybrid", "Improved", "EGR+Improv", "Particulate", "Particulate/NOx", "EuroV", "High Tech" or "Catalyst"			
evaporative	Character: "PCV", "PCV/Tank" or "None".			
mileage	Numeric; mileage of vehicle by age of use km.			
pol	Character; One of the following characters: "Carburetor", "Single-Pt FI", "Multi-Pt FI", "Carb/Mixer", "FI", "Pre-Chamber Inject.", "Direct Injection", "2-Cycle", "2-Cycle, FI", "4-Cycle, Carb", "4-Cycle, FI" "4-Cycle" #'			
"VOC_gkm"	"CO_gkm"	"NOx_gkm"	"PM_gkm"	
"Pb_gkm"	"SO2_gkm"	"NH3_gkm"	"1,3-butadiene_gkm"	
"formaldehyde_gkm"	"acetaldehyde_gkm"	"benzene_gkm"	"EVAP_gkm"	
"CO2_gkm"	"N2O_gkm"	"CH4_gkm"	"VOC_gstart"	
"CO_gstart"	"NOx_gstart"	"PM_gstart"	"Pb_gstart"	
"SO2_gstart"	"NH3_gstart"	"1,3-butadiene_gstart"	"formaldehyde_gstart"	
"acetaldehyde_gstart"	"benzene_gstart"	"EVAP_gstart"	"CO2_gstart"	
"N2O_gstart"	"CH4_gstart"			
details	Logical; option to see or not more information about vehicle.			

Value

An emission factor by annual mileage.

References

Nicole Davis, James Lents, Mauricio Osses, Nick Nikkila, Matthew Barth. 2005. Development and Application of an International Vehicle Emissions Model. Transportation Research Board, 81st Annual Meeting, January 2005, Washington, D.C.

Examples

```
## Not run:
# Do not run
# Passenger Cars PC
data(fkm)
# cumulative mileage from 1 to 50 years of use, 40:50
mil <- cumsum(fkm$KM_PC_E25(1:50))
ef_ive("Truck/Bus", mileage = mil, pol = "CO_gkm")
ef_ive(mileage = mil, pol = "CO_gkm", details = TRUE)

## End(Not run)
```

Description

`ef_ldv_cold` returns speed functions or data.frames which depends on ambient temperature average speed. The emission factors comes from the guidelines EMEP/EEA air pollutant emission inventory guidebook <http://www.eea.europa.eu/themes/air/emep-eea-air-pollutant-emission-inventory-guidebook>

Usage

```
ef_ldv_cold(
  v = "LDV",
  ta,
  cc,
  f,
  eu,
  p,
  k = 1,
  show.equation = FALSE,
  speed,
  fcorr = rep(1, 8)
)
```

Arguments

<code>v</code>	Character; Category vehicle: "LDV"
<code>ta</code>	Numeric vector or data.frame; Ambient temperature. Monthly mean can be used. When <code>ta</code> is a data.frame, one option is that the number of rows should be the number of rows of your Vehicles data.frame. This is convenient for top-down approach when each simple feature can be a polygon, with a monthly average temperature for each simple feature. In this case, the number of columns can be the 12 months.
<code>cc</code>	Character; Size of engine in cc: "<=1400", "1400_2000" or ">2000"
<code>f</code>	Character; Type of fuel: "G", "D" or "LPG"
<code>eu</code>	Character or data.frame of Characters; Euro standard: "PRE", "I", "II", "III", "IV", "V", "VI" or "VIc". When 'eu' is a data.frame and 'ta' is also a data.frame both has to have the same number of rows. For instance, When you want that each simple feature or region has a different emission standard.
<code>p</code>	Character; Pollutant: "CO", "FC", "NOx", "HC" or "PM"
<code>k</code>	Numeric; Multiplication factor
<code>show.equation</code>	Option to see or not the equation parameters
<code>speed</code>	Numeric; Speed to return Number of emission factor and not a function.

`fcorr` Numeric; Correction by fuel properties by euro technology. See [fuel_corr](#). The order from first to last is "PRE", "I", "II", "III", "IV", "V", VI, "VIc". Default is 1

Value

an emission factor function which depends of the average speed V and ambient temperature. g/km

See Also

[fuel_corr](#)

Examples

```
## Not run:
ef1 <- ef_ldv_cold(ta = 15, cc = "<=1400", f = "G", eu = "PRE", p = "CO",
show.equation = TRUE)
ef1(10)
speed <- Speed(10)
ef_ldv_cold(ta = 15, cc = "<=1400", f = "G", eu = "PRE", p = "CO", speed = speed)
# lets create a matrix of ef cold at different speeds and temperatures
te <- -50:50
lf <- sapply(1:length(te), function(i){
ef_ldv_cold(ta = te[i], cc = "<=1400", f = "G", eu = "I", p = "CO", speed = Speed(0:120))
})
filled.contour(lf, col= cptcity::lucky())
euros <- c("V", "V", "IV", "III", "II", "I", "PRE", "PRE")
ef_ldv_cold(ta = 10, cc = "<=1400", f = "G", eu = euros, p = "CO", speed = Speed(0))
lf <- ef_ldv_cold(ta = 10, cc = "<=1400", f = "G", eu = euros, p = "CO", speed = Speed(0:120))
dt <- matrix(rep(2:25,5), ncol = 12) # 12 months
ef_ldv_cold(ta = dt, cc = "<=1400", f = "G", eu = "I", p = "CO", speed = Speed(0))
ef_ldv_cold(ta = dt, cc = "<=1400", f = "G", eu = euros, p = "CO", speed = Speed(34))
euros2 <- c("V", "V", "V", "IV", "IV", "IV", "III", "III")
dfe <- rbind(euros, euros2)
ef_ldv_cold(ta = 10, cc = "<=1400", f = "G", eu = dfe, p = "CO", speed = Speed(0))

ef_ldv_cold(ta = dt[1:2,], cc = "<=1400", f = "G", eu = dfe, p = "CO", speed = Speed(0))
# Fuel corrections
fcorr <- c(0.5,1,1,1,0.9,0.9,0.9,0.9)
ef1 <- ef_ldv_cold(ta = 15, cc = "<=1400", f = "G", eu = "PRE", p = "CO",
show.equation = TRUE, fcorr = fcorr)
ef_ldv_cold(ta = 10, cc = "<=1400", f = "G", eu = dfe, p = "CO", speed = Speed(0),
fcorr = fcorr)

## End(Not run)
```


Description

This function creates a list of functions of cold start emission factors considering different euro emission standard to the elements of the list.

Usage

```
ef_ldv_cold_list(df, v = "LDV", ta, cc, f, eu, p)
```

Arguments

df	Dataframe with local emission factor
v	Category vehicle: "LDV"
ta	ambient temperature. Montly average van be used
cc	Size of engine in cc: <=1400", "1400_2000" and ">2000"
f	Type of fuel: "G" or "D"
eu	character vector of euro standards: "PRE", "I", "II", "III", "IV", "V", "VI" or "VIc".
p	Pollutant: "CO", "FC", "NOx", "HC" or "PM"

Value

A list of cold start emission factors g/km

Note

The length of the list should be equal to the name of the age categories of a specific type of vehicle

Examples

```
## Not run:  
# Do not run  
df <- data.frame(age1 = c(1,1), age2 = c(2,2))  
eu = c("I", "PRE")  
l <- ef_ldv_cold(t = 17, cc = "<=1400", f = "G",  
eu = "I", p = "CO")  
l_cold <- ef_ldv_cold_list(df, t = 17, cc = "<=1400", f = "G",  
eu = eu, p = "CO")  
length(l_cold)  
  
## End(Not run)
```

ef_ldv_scaled *Scaling constant with speed emission factors of Light Duty Vehicles*

Description

This function creates a list of scaled functions of emission factors. A scaled emission factor which at a speed of the driving cycle (SDC) gives a desired value.

Usage

```
ef_ldv_scaled(df, dfcol, SDC = 34.12, v, t = "4S", cc, f, eu, p)
```

Arguments

df	deprecated
dfcol	Column of the dataframe with the local emission factors eg df\$dfcol
SDC	Speed of the driving cycle
v	Category vehicle: "PC", "LCV", "Motorcycle" or "Moped"
t	Sub-category of of vehicle: PC: "ECE_1501", "ECE_1502", "ECE_1503", "ECE_1504", "IMPROVED_CONVENTIONAL", "OPEN_LOOP", "ALL", "2S" or "4S". LCV: "4S", Motorcycle: "2S" or "4S". Moped: "2S" or "4S"
cc	Size of engine in cc: PC: "<=1400", ">1400", "1400_2000", ">2000", "<=800", "<=2000". Motorcycle: ">=50" (for "2S"), "<=250", "250_750", ">=750". Moped: "<=50". LCV: "<3.5" for gross weight.
f	Type of fuel: "G", "D", "LPG" or "FH" (Full Hybrid: starts by electric motor)
eu	Euro standard: "PRE", "I", "II", "III", "III+DPF", "IV", "V", "VI", "VIc"
p	Pollutant: "CO", "FC", "NOx", "HC" or "PM". If your pollutant dfcol is based on fuel, use "FC", if it is based on "HC", use "HC".

Details

This function calls "ef_ldv_speed" and calculate the specific k value, dividing the local emission factor by the respective speed emissions factor at the speed representative of the local emission factor, e.g. If the local emission factors were tested with the FTP-75 test procedure, SDC = 34.12 km/h.

Value

A list of scaled emission factors g/km

Note

The length of the list should be equal to the name of the age categories of a specific type of vehicle. Thanks to Glauber Camponogara for the help.

See Also

ef_ldv_seed

Examples

```
## Not run:
data(fe2015)
co1 <- fe2015[fe2015$Pollutant=="CO", ]
lef <- ef_ldv_scaled(dfcol = co1$PC_G, v = "PC", t = "4S", cc = "<=1400", f = "G",
eu = co1$Euro_LDV, p = "CO")
length(lef)
lef[[1]](40) # First element of the list of speed functions at 40 km/h
lef[[36]](50) # 36th element of the list of speed functions at 50 km/h
plot(x = 0:150, y = lef[[36]](0:150), col = "red", type = "b", ylab = "[g/km]",
pch = 16, xlab = "[km/h]",
main = "Variation of emissions with speed of oldest vehicle")
plot(x = 0:150, y = lef[[1]](0:150), col = "blue", type = "b", ylab = "[g/km]",
pch = 16, xlab = "[km/h]",
main = "Variation of emissions with speed of newest vehicle")

## End(Not run)
```

ef_ldv_speed

Emissions factors for Light Duty Vehicles and Motorcycles

Description

[ef_ldv_speed](#) returns speed dependent emission factors, data.frames or list of emission factors. The emission factors comes from the guidelines EMEP/EEA air pollutant emission inventory guidebook <http://www.eea.europa.eu/themes/air/emep-eea-air-pollutant-emission-inventory-guidebook>

Usage

```
ef_ldv_speed(
  v,
  t = "4S",
  cc,
  f,
  eu,
  p,
  x,
  k = 1,
  speed,
  show.equation = FALSE,
  fcorr = rep(1, 8)
)
```

Arguments

v	Character; category vehicle: "PC", "LCV", "Motorcycle" or "Moped"
t	Character; sub-category of of vehicle: PC: "ECE_1501", "ECE_1502", "ECE_1503", "ECE_1504", "IMPROVED_CONVENTIONAL", "OPEN_LOOP", "ALL", "2S" or "4S". LCV: "4S", Motorcycle: "2S" or "4S". Moped: "2S" or "4S"
cc	Character; size of engine in cc: PC: "<=1400", ">1400", "1400_2000", ">2000", "<=800", "<=2000". Motorcycle: ">=50" (for "2S"), "<=250", "250_750", ">=750". Moped: "<=50". LCV : "<3.5" for gross weight.
f	Character; type of fuel: "G", "D", "LPG" or "FH" (Gasoline Full Hybrid). Full hybrid vehicles cannot be charged from the grid and recharge; only its own engine may recharge tis batteries.
eu	Character or data.frame of characters; euro standard: "PRE", "I", "II", "III", "III+DPF", "IV", "V", "VI" or "VIc". When the pollutant is active surface or number of particles, eu can also be "III+DISI"
p	Character; pollutant: "CO", "FC", "NOx", "NO", "NO2", "HC", "PM", "NMHC", "CH4", "CO2", "SO2" or "Pb". Only when p is "SO2" pr "Pb" x is needed. Also polycyclic aromatic hydrocarbons (PAHs), persistent organi pollutants (POPs), and Number of particles and Active Surface.
x	Numeric; if pollutant is "SO2", it is sulphur in fuel in ppm, if is "Pb", Lead in fuel in ppm.
k	Numeric; multiplication factor
speed	Numeric; Speed to return Number of emission factor and not a function.
show.equation	Logical; option to see or not the equation parameters.
fcorr	Numeric; Correction by fuel properties by euro technology. See fuel_corr . The order from first to last is "PRE", "I", "II", "III", "IV", "V", VI, "VIc". Default is 1

Details

The argument of this functions have several options which results in different combinations that returns emission factors. If a combination of any option is wrong it will return an empty value. Therefore, it is important ti know the combinations.

Value

An emission factor function which depends of the average speed V g/km

Note

t = "ALL" and cc == "ALL" works for several pollutants because emission fators are the same. Some exceptions are with NOx and FC because size of engine.

Hybrid cars: the only cover "PC" and according to EMEP/EEA air pollutant emission inventory guidebook 2016 (Ntziachristos and Samaras, 2016) only for euro IV. When new literature is available, I will update these factors.

Pollutants (g/km): "CO", "NOx", "HC", "PM", "CH4", "NMHC", "CO2", "SO2", "Pb", "FC".

Black Carbon and Organic Matter (g/km): "BC", "OM"

PAH and POP (g/km): [speciate](#) **Dioxins and furans(g equivalent toxicity / km):** [speciate](#)
Metals (g/km): [speciate](#)

NMHC (g/km): [speciate](#)

Active Surface (cm²/km): [speciate](#)"AS_urban", "AS_rural", "AS_highway"

Total Number of particles (N/km): [speciate](#) "N_urban", "N_rural", "N_highway", "N_50nm_urban", "N_50_100nm_rural", "N_100_1000nm_highway".

The available standards for Active Surface or number of particles are Euro I, II, III, III+DPF for diesel and III+DISI for gasoline. Pre euro vehicles has the value of Euro I and euro IV, V, VI and VIc the value of euro III.

See Also

[fuel_corr emis ef_ldv_cold](#)

Examples

```
## Not run:
# Passenger Cars PC
# Emission factor function
V <- 0:150
ef1 <- ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G", eu = "PRE",
p = "CO")
efs <- EmissionFactors(ef1(1:150))
plot(Speed(1:150), efs, xlab = "speed[km/h]", type = "b", pch = 16, col = "blue")

# Quick view
pol <- c("CO", "NOx", "HC", "NMHC", "CH4", "FC", "PM", "CO2", "SO2",
"1-butene", "propyne")
f <- sapply(1:length(pol), function(i){
ef_ldv_speed("PC", "4S", "<=1400", "G", "PRE", pol[i], x = 10)(30)
})
f

# PM Characteristics
pol <- c("AS_urban", "AS_rural", "AS_highway",
"N_urban", "N_rural", "N_highway",
"N_50nm_urban", "N_50_100nm_rural", "N_100_1000nm_highway")
f <- sapply(1:length(pol), function(i){
ef_ldv_speed("PC", "4S", "<=1400", "D", "PRE", pol[i], x = 10)(30)
})
f

# PAH POP
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G", eu = "PRE",
p = "indeno(1,2,3-cd)pyrene")(10)
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G", eu = "PRE",
p = "naphthalene")(10)

# Dioxins and Furans
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G", eu = "PRE",
p = "PCB")(10)
```

```

# NMHC
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G", eu = "PRE",
p = "hexane")(10)

# List of Copert emission factors for 40 years fleet of Passenger Cars.
# Assuming a euro distribution of euro V, IV, III, II, and I of
# 5 years each and the rest 15 as PRE euro:
euro <- c(rep("V", 5), rep("IV", 5), rep("III", 5), rep("II", 5),
rep("I", 5), rep("PRE", 15))
speed <- 25
lef <- lapply(1:40, function(i) {
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G",
eu = euro[i], p = "CO")
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G",
eu = euro[i], p = "CO", show.equation = FALSE)(25) })
# to check the emission factor with a plot
efs <- EmissionFactors(unlist(lef)) #returns 'units'
plot(efs, xlab = "age")
lines(efs, type = "l")
euros <- c("VI", "V", "IV", "III", "II")
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G",
eu = euros, p = "CO")
a <- ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G",
eu = euros, p = "CO", speed = Speed(0:120))
head(a)
filled.contour(as.matrix(a)[1:10, 1:length(euros)], col = cptcity::cpt(n = 18))
filled.contour(as.matrix(a)[110:120, 1:length(euros)], col = cptcity::cpt(n = 16))
filled.contour(as.matrix(a)[, 1:length(euros)], col = cptcity::cpt(n = 21))
filled.contour(as.matrix(a)[, 1:length(euros)],
col = cptcity::cpt("mpl_viridis", n = 21))
filled.contour(as.matrix(a)[, 1:length(euros)],
col = cptcity::cpt("mpl_magma", n = 21))
persp(as.matrix(a)[, 1:length(euros)], phi = 0, theta = 0)
persp(as.matrix(a)[, 1:length(euros)], phi = 25, theta = 45)
persp(as.matrix(a)[, 1:length(euros)], phi = 0, theta = 90)
persp(as.matrix(a)[, 1:length(euros)], phi = 25, theta = 90+45)
persp(as.matrix(a)[, 1:length(euros)], phi = 0, theta = 180)
new_euro <- c("VI", "VI", "V", "V", "V")
euro <- c("V", "V", "IV", "III", "II")
old_euro <- c("III", "II", "I", "PRE", "PRE")
meuros <- rbind(new_euro, euro, old_euro)
aa <- ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G",
eu = meuros, p = "CO", speed = Speed(10:11))

# Light Commercial Vehicles
V <- 0:150
ef1 <- ef_ldv_speed(v = "LCV", t = "4S", cc = "<3.5", f = "G", eu = "PRE",
p = "CO")
efs <- EmissionFactors(ef1(1:150))
plot(Speed(1:150), efs, xlab = "speed[km/h]")
lef <- lapply(1:5, function(i) {
ef_ldv_speed(v = "LCV", t = "4S", cc = "<3.5", f = "G",
eu = euro[i], p = "CO", show.equation = FALSE)(25) })

```

```

# to check the emission factor with a plot
efs <- EmissionFactors(unlist(lef)) #returns 'units'
plot(efs, xlab = "age")
lines(efs, type = "l")

# Motorcycles
V <- 0:150
ef1 <- ef_ldv_speed(v = "Motorcycle", t = "4S", cc = "<=250", f = "G",
eu = "PRE", p = "CO", show.equation = TRUE)
efs <- EmissionFactors(ef1(1:150))
plot(Speed(1:150), efs, xlab = "speed[km/h]")
# euro for motorcycles
eurom <- c(rep("III", 5), rep("II", 5), rep("I", 5), rep("PRE", 25))
lef <- lapply(1:30, function(i) {
ef_ldv_speed(v = "Motorcycle", t = "4S", cc = "<=250", f = "G",
eu = eurom[i], p = "CO",
show.equation = FALSE)(25) })
efs <- EmissionFactors(unlist(lef)) #returns 'units'
plot(efs, xlab = "age")
lines(efs, type = "l")
a <- ef_ldv_speed(v = "Motorcycle", t = "4S", cc = "<=250", f = "G",
eu = eurom, p = "CO", speed = Speed(0:125))
a$speed <- NULL
filled.contour(as.matrix(a), col = cptcity::lucky(),
xlab = "Speed", ylab = "Age")
persp(x = as.matrix(a), theta = 35, xlab = "Speed", ylab = "Euros",
zlab = "CO [g/km]", col = cptcity::lucky(), phi = 25)

## End(Not run)

```

ef_local

Local Emissions factors

Description

`ef_local` process an data.frame delivered by the user, but adding similar functionality and arguments as `ef_cetesb`, which are classification, filtering and projections

Usage

```

ef_local(
  p,
  veh,
  year = 2017,
  agemax = 40,
  ef,
  full = FALSE,
  project = "constant",
  verbose = TRUE
)

```

Arguments

p	Character; pollutant delivered by the user. the name of the column of the data.frame must be Pollutant .
veh	Character; Vehicle categories available in the data.frame provided by the user
year	Numeric; Filter the emission factor to start from a specific base year. If project is 'constant' values above 2017 and below 1980 will be repeated
agemax	Integer; age of oldest vehicles for that category
ef	data.frame, for local the emission factors. The names of the ef must be 'Age' 'Year' 'Pollutant' and all the vehicle categories...
full	Logical; To return a data.frame instead or a vector adding Age, Year, Brazilian emissions standards and its euro equivalent.
project	Character showing the method for projecting emission factors in future. Currently the only value is "constant"
verbose	Logical; To show more information

Details

returns a vector or data.frame of Brazilian emission factors.

Value

A vector of Emission Factor or a data.frame

Note

The names of the ef must be 'Age' 'Year' 'Pollutant' and all the vehicle categories...

See Also

[ef_cetesb](#)

Examples

```
## Not run:  
#do not run  
  
## End(Not run)
```


ef_nitro

*Emissions factors of N2O and NH3***Description**

`ef_nitro` returns emission factors as a functions of acondumulated mileage. The emission factors comes from the guidelines EMEP/EEA air pollutant emission inventory guidebook <http://www.eea.europa.eu/themes/air/emep/eea-air-pollutant-emission-inventory-guidebook>

Usage

```
ef_nitro(
  v,
  t = "Hot",
  cond = "Urban",
  cc,
  f,
  eu,
  p = "NH3",
  S = 10,
  cumileage,
  k = 1,
  show.equation = FALSE,
  fcorr = rep(1, 8)
)
```

Arguments

<code>v</code>	Category vehicle: "PC", "LCV", "Motorcycles_2S", "Motorcycles", "Trucks", "Trucks-A", "Coach" and "BUS"
<code>t</code>	Type: "Cold" or "Hot"
<code>cond</code>	"Urban", "Rural", "Highway"
<code>cc</code>	PC: "<=1400", "1400_2000", ">2000". LCV: "<3.5". Motorcycles: ">=50", "Motorcycles_2S", "<50", ">=50". Trucks: ">3.5", "7.5_12", "12_28", "28_34". Trucks_A: ">34". BUS: "<=15", ">15 & <= 18". Coach: "<=18", ">18"
<code>f</code>	Type of fuel: "G", "D" or "LPG"
<code>eu</code>	Euro standard: "PRE", "I", "II", "III", "IV", "V", "VI", "VIc"
<code>p</code>	Pollutant: "N2O", "NH3"
<code>S</code>	Sulphur (ppm). Number.
<code>cumileage</code>	Numeric; Acondumulated mileage to return number of emission factor and not a function.
<code>k</code>	Multiplication factor
<code>show.equation</code>	Option to see or not the equation parameters
<code>fcorr</code>	Numeric; Correction by by euro technology.

Value

an emission factor function which depends on the accumulated mileage, or an EmissionFactor

Note

if length of eu is bigger than 1, cumileage can have values of length 1 or length equal to length of eu

Examples

```
## Not run:
efe10 <- ef_nitro(v = "PC", t = "Hot", cond = "Urban", f = "G", cc = "<=1400",
eu = "III", p = "NH3", S = 10,
show.equation = FALSE)
efe50 <- ef_nitro(v = "PC", t = "Hot", cond = "Urban", f = "G", cc = "<=1400",
eu = "III", p = "NH3", S = 50,
show.equation = TRUE)
efe10(10)
efe50(10)
efe10 <- ef_nitro(v = "PC", t = "Hot", cond = "Urban", f = "G", cc = "<=1400",
eu = "III", p = "NH3", S = 10, cumileage = units::set_units(25000, "km"))

## End(Not run)
```

 ef_wear

Emissions factors from tyre, break and road surface wear

Description

`ef_wear` estimates wear emissions. The sources are tyres, breaks and road surface.

Usage

```
ef_wear(wear, type, pol = "TSP", speed, load = 0.5, axle = 2)
```

Arguments

wear	Character; type of wear: "tyre", "break" and "road"
type	Character; type of vehicle: "2W", "PC", "LCV", "HDV"
pol	Character; pollutant: "TSP", "PM10", "PM2.5", "PM1" and "PM0.1"
speed	Data.frame of speeds
load	Load of the HDV
axle	Number of axle of the HDV

Value

emission factors grams/km

References

Ntziachristos and Boulter 2016. Automobile tyre and break wear and road abrasion. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2016

Examples

```
## Not run:
data(net)
data(pc_profile)
pc_week <- temp_fact(net$lhv+net$hdv, pc_profile)
df <- netspeed(pc_week, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
ef <- ef_wear(wear = "tyre", type = "PC", pol = "PM10", speed = df)

## End(Not run)
```

 ef_whe

Emission factor that incorporates the effect of high emitters

Description

`ef_whe` return weighted emission factors of vehicles considering that one part of the fleet has a normal deterioration and another has a deteriorated fleet that would be rejected in a inspection and maintenance program but it is still in circulation. This emission factor might be applicable in cities without a inspection and maintenance program and with Weighted emission factors considering that part of the fleet are high emitters.

Usage

```
ef_whe(efhe, phe, ef)
```

Arguments

efhe	Numeric; Emission factors of high emitters vehicles. This vehicles would be rejected in a inspection and maintenance program.
phe	Numeric; Percentage of high emitters.
ef	Numeric; Emission factors deteriorated vehicles under normal conditions. These vehicles would be approved in a inspection and maintenance program.

Value

An emission factor by annual mileage.

Examples

```
## Not run:
# Do not run
# Let's say high emitter is 5 times the normal ef.
co_efhe <- ef_cetesb(p = "COd", "PC_G") * 5
# Let's say that the perfil of high emitters increases linearly
# till 30 years and after that percentage is constant
perc <- c(seq(0.01, 0.3, 0.01), rep(0.3, 20))
# Now, lets use our ef with normal deterioration
co_ef_normal <- ef_cetesb(p = "COd", "PC_G")
efd <- ef_whe(efhe = co_efhe, phe = perc, ef = co_ef_normal)
# now, we can plot the three ef
plot(co_efhe)
lines(co_ef_normal, pch = 16, col = "red" )
lines(efd, pch = 16, col = "blue")

## End(Not run)
```

emis

Estimation of emissions

Description

emis estimates vehicular emissions as the product of the vehicles on a road, length of the road, emission factor avaliated at the respective speed. $E = VEH * LENGTH * EF(speed)$

Usage

```
emis(
  veh,
  lkm,
  ef,
  speed,
  agemax = ifelse(is.data.frame(veh), ncol(veh), ncol(veh[[1]])),
  profile,
  simplify = FALSE,
  fortran = FALSE,
  hour = nrow(profile),
  day = ncol(profile),
  verbose = FALSE,
  nt = ifelse(check_nt() == 1, 1, check_nt()/2)
)
```

Arguments

veh "Vehicles" data-frame or list of "Vehicles" data-frame. Each data-frame as number of columns matching the age distribution of that ype of vehicle. The number of rows is equal to the number of streets link. If this is a list, the length of the list is the vehicles for each hour.

lkm	Length of each link in km
ef	List of functions of emission factors
speed	Speed data-frame with number of columns as hours. The default value is 34km/h
agemax	Age of oldest vehicles for that category
profile	Dataframe or Matrix with nrow equal to 24 and ncol 7 day of the week
simplify	Logical; to determine if EmissionsArray should les dimensions, being streets, vehicle categories and hours or default (streets, vehicle categories, hours and days). Default is FALSE to avoid break old code, but the recommendation is that new estimations use this parameter as TRUE
fortran	Logical; to try the fortran calculation when speed is not used. I will add fortran for EmissionFactorsList soon.
hour	Number of considered hours in estimation. Default value is number of rows of argument profile
day	Number of considered days in estimation
verbose	Logical; To show more information
nt	Integer; Number of threads wich must be lower than max available. See check_nt . Only when fortran = TRUE

Value

If the user applies a top-down approach, the resulting units will be according its own data. For instance, if the vehicles are veh/day, the units of the emissions implicitly will be g/day.

Note

Hour and day will be deprecated because they can be infered from the profile matrix.

Examples

```
## Not run:
# Do not run
data(net)
data(pc_profile)
data(profiles)
data(fe2015)
data(fkm)
PC_G <- c(
  33491, 22340, 24818, 31808, 46458, 28574, 24856, 28972, 37818, 49050, 87923,
  133833, 138441, 142682, 171029, 151048, 115228, 98664, 126444, 101027,
  84771, 55864, 36306, 21079, 20138, 17439, 7854, 2215, 656, 1262, 476, 512,
  1181, 4991, 3711, 5653, 7039, 5839, 4257, 3824, 3068
)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")

# Estimation for morning rush hour and local emission factors and speed
speed <- data.frame(S8 = net$ps)
lef <- EmissionFactorsList(ef_cetesb("CO", "PC_G", agemax = ncol(pc1)))
system.time(E_CO <- emis(veh = pc1, lkm = net$lkm, ef = lef, speed = speed))
```

```

system.time(E_CO_2 <- emis(veh = pc1, lkm = net$lkm, ef = lef, speed = speed, simplify = TRUE))
identical(E_CO, E_CO_2)

# Estimation for morning rush hour and local emission factors without speed
lef <- ef_cetesb("CO", "PC_G", agemax = ncol(pc1))
system.time(E_CO <- emis(veh = pc1, lkm = net$lkm, ef = lef))
system.time(E_CO_2 <- emis(veh = pc1, lkm = net$lkm, ef = lef, fortran = TRUE))
identical(E_CO, E_CO_2)

# Estimation for 168 hour and local factors and speed
pcw <- temp_fact(net$l dv + net$h dv, pc_profile)
speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
lef <- EmissionFactorsList(ef_cetesb("CO", "PC_G", agemax = ncol(pc1)))
system.time(
  E_CO <- emis(
    veh = pc1,
    lkm = net$lkm,
    ef = lef,
    speed = speed,
    profile = profiles$PC_JUNE_2014
  )
)
system.time(
  E_CO_2 <- emis(
    veh = pc1,
    lkm = net$lkm,
    ef = lef,
    speed = speed,
    profile = profiles$PC_JUNE_2014,
    simplify = TRUE
  )
)

# Estimation for 168 hour and local factors and without speed
lef <- ef_cetesb("CO", "PC_G", agemax = ncol(pc1))
system.time(
  E_CO <- emis(
    veh = pc1,
    lkm = net$lkm,
    ef = lef,
    profile = profiles$PC_JUNE_2014
  )
)
sum(E_CO)
system.time(
  E_CO_2 <- emis(
    veh = pc1,
    lkm = net$lkm,
    ef = lef,
    profile = profiles$PC_JUNE_2014,
    fortran = TRUE
  )
)

```

```

sum(E_CO)
system.time(
  E_CO_3 <- emis(
    veh = pc1,
    lkm = net$lkm,
    ef = lef,
    profile = profiles$PC_JUNE_2014,
    simplify = TRUE
  )
)
sum(E_CO)
system.time(
  E_CO_4 <- emis(
    veh = pc1,
    lkm = net$lkm,
    ef = lef,
    profile = profiles$PC_JUNE_2014,
    simplify = TRUE,
    fortran = TRUE
  )
)
sum(E_CO)
identical(round(E_CO, 2), round(E_CO_2, 2))
identical(round(E_CO_3, 2), round(E_CO_4, 2))
identical(round(E_CO_3[, , 1], 2), round(E_CO_4[, , 1], 2))
dim(E_CO_3)
dim(E_CO_4)
# but
a <- unlist(lapply(1:41, function(i) {
  unlist(lapply(1:168, function(j) {
    identical(E_CO_3[, i, j], E_CO_4[, i, j])
  })))
}))
unique(a)

# Estimation with list of vehicles
lpc <- list(pc1, pc1)
lef <- EmissionFactorsList(ef_cetesb("CO", "PC_G", agemax = ncol(pc1)))
E_COv2 <- emis(veh = lpc, lkm = net$lkm, ef = lef, speed = speed)

# top down
veh <- age_ldv(x = net$ldv[1:4], name = "PC_E25_1400", agemax = 4)
mil <- fkm$KM_PC_E25(1:4)
ef <- ef_cetesb("COd", "PC_G")[1:4]
emis(veh, units::set_units(mil, "km"), ef)

# group online
bus1 <- age_hdv(30, agemax = 4)
veh <- bus1
lkm <- units::set_units(400, "km")
speed <- 40
efco <- ef_cetesb("COd", "UB", agemax = 4)
lef <- ef_hdv_scaled(

```

```

dfcol = as.numeric(efco),
v = "Ubus",
t = "Std",
g = ">15 & <=18",
eu = rep("IV", 4),
gr = 0,
l = 0.5,
p = "CO"
)
for (i in 1:length(lef)) print(lef[[i]](10))
(a <- emis(veh = bus1, lkm = lkm, ef = efco, verbose = TRUE))
(b <- emis(veh = bus1, lkm = lkm, ef = efco, verbose = TRUE, fortran = TRUE))

## End(Not run)

```

EmissionFactors

Construction function for class "EmissionFactors"

Description

EmissionFactors returns a transformed object with class "EmissionFactors" and units g/km.

Usage

```
EmissionFactors(x, mass = "g", dist = "km", ...)
```

```
## S3 method for class 'EmissionFactors'
print(x, ...)
```

```
## S3 method for class 'EmissionFactors'
summary(object, ...)
```

```
## S3 method for class 'EmissionFactors'
plot(
  x,
  pal = "mpl_viridis",
  rev = TRUE,
  fig1 = c(0, 0.8, 0, 0.8),
  fig2 = c(0, 0.8, 0.55, 1),
  fig3 = c(0.7, 1, 0, 0.8),
  mai1 = c(0.2, 0.82, 0.82, 0.42),
  mai2 = c(1.3, 0.82, 0.82, 0.42),
  mai3 = c(0.7, 0.62, 0.82, 0.42),
  bias = 1.5,
  ...
)
```


Arguments

x	Object with class "data.frame", "matrix" or "numeric"
mass	Character to be the time units as numerator, default "g" for grams
dist	String indicating the units of the resulting distance in speed.
...	ignored
object	object with class "EmissionFactors"
pal	Palette of colors available or the number of the position
rev	Logical; to internally revert order of rgb color vectors.
fig1	par parameters for fig, par .
fig2	par parameters for fig, par .
fig3	par parameters for fig, par .
mai1	par parameters for mai, par .
mai2	par parameters for mai, par .
mai3	par parameters for mai, par .
bias	positive number. Higher values give more widely spaced colors at the high end.

Value

Objects of class "EmissionFactors" or "units"

Examples

```
## Not run:
data(fe2015)
names(fe2015)
class(fe2015)
df <- fe2015[fe2015$Pollutant=="CO", c(ncol(fe2015)-1,ncol(fe2015))]
ef1 <- EmissionFactors(df)
class(ef1)
summary(ef1)
plot(ef1)
print(ef1)

## End(Not run)
```

EmissionFactorsList *Construction function for class "EmissionFactorsList"*

Description

EmissionFactorsList returns a transformed object with class "EmissionsFactorsList".

Usage

```
EmissionFactorsList(x, ...)

## S3 method for class 'EmissionFactorsList'
print(x, ..., default = FALSE)

## S3 method for class 'EmissionFactorsList'
summary(object, ...)

## S3 method for class 'EmissionFactorsList'
plot(x, ...)
```

Arguments

x	Object with class "list"
...	ignored
default	Logical value. When TRUE prints default list, when FALSE prints messages with description of list
object	Object with class "EmissionFactorsList"

Value

Objects of class "EmissionFactorsList"

Examples

```
## Not run:
data(fe2015)
names(fe2015)
class(fe2015)
df <- fe2015[fe2015$Pollutant=="CO", c(ncol(fe2015)-1,ncol(fe2015))]
ef1 <- EmissionFactorsList(df)
class(ef1)
length(ef1)
length(ef1[[1]])
summary(ef1)
ef1

## End(Not run)
```

Emissions

Construction function for class "Emissions"

Description

Emissions returns a transformed object with class "Emissions". The type of objects supported are of classes "matrix", "data.frame" and "numeric". If the class of the object is "matrix" this function returns a dataframe.

Usage

```

Emissions(x, mass = "g", time, ...)

## S3 method for class 'Emissions'
print(x, ...)

## S3 method for class 'Emissions'
summary(object, ...)

## S3 method for class 'Emissions'
plot(
  x,
  pal = "colo_angelafaye_Coloured_sky_in",
  rev = FALSE,
  fig1 = c(0, 0.8, 0, 0.8),
  fig2 = c(0, 0.8, 0.55, 1),
  fig3 = c(0.7, 1, 0, 0.8),
  mai1 = c(0.2, 0.82, 0.82, 0.42),
  mai2 = c(1.3, 0.82, 0.82, 0.42),
  mai3 = c(0.7, 0.72, 0.82, 0.42),
  main = NULL,
  bias = 1.5,
  ...
)

```

Arguments

x	Object with class "data.frame", "matrix" or "numeric"
mass	Character to be the time units as numerator, default "g" for grams
time	Character to be the time units as denominator, eg "h"
...	ignored
object	object with class "Emissions"
pal	Palette of colors available or the number of the position
rev	Logical; to internally revert order of rgb color vectors.
fig1	par parameters for fig, par .
fig2	par parameters for fig, par .
fig3	par parameters for fig, par .
mai1	par parameters for mai, par .
mai2	par parameters for mai, par .
mai3	par parameters for mai, par .
main	title of plot
bias	positive number. Higher values give more widely spaced colors at the high end.

Value

Objects of class "Emissions" or "units"

Examples

```
## Not run:
data(net)
data(pc_profile)
data(fe2015)
data(fkm)
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
         133833,138441,142682,171029,151048,115228,98664,126444,101027,
         84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
         1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
veh <- data.frame(PC_G = PC_G)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
pcw <- temp_fact(net$ldv+net$hdv, pc_profile)
speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
pckm <- units::as_units(fkm[[1]](1:24), "km"); pckma <- cumsum(pckm)
cod1 <- emis_det(po = "CO", cc = 1000, eu = "III", km = pckma[1:11])
cod2 <- emis_det(po = "CO", cc = 1000, eu = "I", km = pckma[12:24])
#vehicles newer than pre-euro
co1 <- fe2015[fe2015$Pollutant=="CO", ] #24 obs!!!
cod <- c(co1$PC_G[1:24]*c(cod1,cod2),co1$PC_G[25:nrow(co1)])
lef <- ef_ldv_scaled(co1, cod, v = "PC", cc = "<=1400",
                    f = "G", p = "CO", eu=co1$Euro_LDV)
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed, agemax = 41,
            profile = pc_profile)
dim(E_CO) # streets x vehicle categories x hours x days
class(E_CO)
plot(E_CO)
####
Emissions(1)
Emissions(1, time = "h")

## End(Not run)
```

EmissionsArray

Construction function for class "EmissionsArray"

Description

EmissionsArray returns a transformed object with class "EmissionsArray" with 4 dimensions.

Usage

```
EmissionsArray(x, ...)
```

```
## S3 method for class 'EmissionsArray'
```

```

print(x, ...)

## S3 method for class 'EmissionsArray'
summary(object, ...)

## S3 method for class 'EmissionsArray'
plot(x, main = "average emissions", ...)

```

Arguments

x	Object with class "data.frame", "matrix" or "numeric"
...	ignored
object	object with class "EmissionsArray"
main	Title for plot

Value

Objects of class "EmissionsArray"

Note

Future version of this function will return an Array of 3 dimensions.

Examples

```

## Not run:
data(net)
data(pc_profile)
data(fe2015)
data(fkm)
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
         133833,138441,142682,171029,151048,115228,98664,126444,101027,
         84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
         1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
veh <- data.frame(PC_G = PC_G)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
pcw <- temp_fact(net$ldv+net$hdv, pc_profile)
speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
pckm <- units::set_units(fkm[[1]](1:24), "km"); pckma <- cumsum(pckm)
cod1 <- emis_det(po = "CO", cc = 1000, eu = "III", km = pckma[1:11])
cod2 <- emis_det(po = "CO", cc = 1000, eu = "I", km = pckma[12:24])
#vehicles newer than pre-euro
co1 <- fe2015[fe2015$Pollutant=="CO", ] #24 obs!!!
cod <- c(co1$PC_G[1:24]*c(cod1,cod2),co1$PC_G[25:nrow(co1)])
lef <- ef_ldv_scaled(co1, cod, v = "PC", cc = "<=1400",
                    f = "G",p = "CO", eu=co1$Euro_LDV)
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed, agemax = 41,
            profile = pc_profile, simplify = TRUE)
class(E_CO)
summary(E_CO)
E_CO

```

```

plot(E_CO)
lpc <- list(pc1, pc1)
E_COv2 <- emis(veh = lpc, lkm = net$lkm, ef = lef, speed = speed, agemax = 41,
              profile = pc_profile, hour = 2, day = 1)

## End(Not run)

```

emis_chem

*Aggregate emissions by lumped groups in chemical mechanism***Description**

`emis_chem` aggregates emissions by chemical mechanism and convert grams to mol. This function reads all hydrocarbos and respective criteria pollutants specified in `ef_ldv_speed` and `ef_hdv_speed`.

Usage

```
emis_chem(dfe, mechanism, colby, long = FALSE)
```

Arguments

<code>dfe</code>	data.frame with column 'emissions' in grams and 'pollutant' in long format. It is supposed that each line is the pollution of some region. Then the 'colby' argument is for include the name of the region.
<code>mechanism</code>	Character, "RADM2_SORG", "CBMZ_MOSAIC", "CPTEC", "GOCART_CPTEC", "MOZEM", "MOZCEM", "CAMMAM", "MOZMEM", "MOZC_T1_EM", "CB05_OPT1" or "CB05_OPT2"
<code>colby</code>	Character indicating column name for aggregating extra column. For instance, region or province.
<code>long</code>	Logical. Do you want data in long format?

Value

data.frame with lumped groups by chemical mechanism. It transform emissions in grams to mol.

Note

This feature is experimental and the mapping of pollutants and lumped species may change in future. This function is converting the initial data.frame input into data.table. To have a comprehensive speciation is necessary enter with a data.frame with column 'emission' in long format including another column named 'pollutant' with species of NMHC, CO, NO, NO2, NH3, SO2, PM2.5 and coarse PM10.

Groups derived from gases has units 'mol' and from aerosols 'g'. The aerosol units for WRF-Chem are $\mu\text{g}/\text{m}^2/\text{s}$ while for CMAQ and CAMx are g/s. So, leaving the units just in g, allow to make further change while providing flexibility for several models. TODO: Enter with wide data.frame, with each line as a each street, each column for pollutant

See Also

[ef_ldv_speed](#) [ef_hdv_speed](#) [speciate](#) [ef_evap](#)

Examples

```
## Not run:
# CO
df <- data.frame(emission = Emissions(1:10))
df$pollutant = "CO"
emis_chem(df, "CBMZ_MOSAIC")
# hexanal
df$pollutant = "hexanal"
emis_chem(df, "CBMZ_MOSAIC")
# propadiene and NO2
df2 <- df1 <- df
df1$pollutant = "propadiene"
df2$pollutant = "NO2"
(dfe <- rbind(df1, df2))
emis_chem(dfe, "CBMZ_MOSAIC")
dfe$region <- rep(letters[1:2], 10)
emis_chem(dfe, "CBMZ_MOSAIC", "region")
emis_chem(dfe, "CBMZ_MOSAIC", "region", TRUE)

## End(Not run)
```

emis_chem2

Aggregate emissions by lumped groups in chemical mechanism

Description

[emis_chem2](#) aggregates VOC emissions by chemical mechanism and convert grams to mol.

Usage

```
emis_chem2(df, mech, nx, na.rm = FALSE)
```

Arguments

df	data.frame with emissions including columns "id" and "pol".
mech	Character, "CB4", "CB05", "S99", "S7", "CS7", "S7T", "S11", "S11D", "S16C", "S18B", "RADM2", "RACM2", "MOZT1", "CBMZ", "CB05opt2"
nx	Character, colnames for emissions data, for instance "V1", "V2"...
na.rm	Logical, to remove lines with NA from group

Value

data.frame with lumped groups by chemical mechanism.

Note

- **CB05:** "ALD" "ALDX" "ETH" "HC3" "HC5" "HC8" "HCHO" "KET" "OL2" "OLI" "OLT" "TOL" "XYL"
- **CB05opt2:** "ALD2" "ALDX" "BENZENE" "ETH" "ETHA" "FORM" "IOLE" "OLE" "PAR" "TOL" "XYL"
- **RADM2:** "ALD" "ETH" "HC3" "HC5" "HC8" "HCHO" "KET" "MACR" "OL2" "OLI" "OLT" "TOL" "XYL"
- **RACM2:** "ACD" "ACE" "ACT" "ALD" "BALD" "BEN" "DIEN" "ETE" "ETH" "HC3" "HC5" "HC8" "HCHO" "MACR" "MEK" "OLI" "OLT" "TOL" "UALD" "XYM" "XYO" "XYP"
- **CB4:** "ALD2" "ETH" "FORM" "OLE" "PAR" "TOL" "XYL"
- **S99:** "ACET" "ALK1" "ALK2" "ALK3" "ALK4" "ALK5" "ARO1NBZ" "ARO2" "BALD" "BENZENE" "CCHO" "ETHENE" "HCHO" "IPROD" "MACR" "MEK" "OLE1" "OLE2" "RCHO"
- **CB4:** "ACET" "ACYE" "ALK1" "ALK2" "ALK3" "ALK4" "ALK5" "ARO1" "ARO2" "BALD" "BENZ" "CCHO" "ETHE" "HCHO" "IPRD" "MACR" "MEK" "OLE1" "OLE2" "RCHO"
- **CS7:** "ALK3" "ALK4" "ARO1" "ARO2" "CCHO" "ETHE" "HCHO" "IPRD" "NROG" "OLE1" "OLE2" "PRD2" "RCHO"
- **S7:** "ACET" "ACYE" "ALK1" "ALK2" "ALK3" "ALK4" "ALK5" "ARO1" "ARO2" "BALD" "BENZ" "CCHO" "ETHE" "HCHO" "IPRD" "MACR" "MEK" "OLE1" "OLE2" "RCHO"
- **S7T:** "13BDE" "ACET" "ACRO" "ACYE" "ALK1" "ALK2" "ALK3" "ALK4" "ALK5" "ARO1" "ARO2" "B124" "BALD" "BENZ" "CCHO" "ETHE" "HCHO" "IPRD" "MACR" "MEK" "MXYL" "OLE1" "OLE2" "OXYL" "PRPE" "PXYL" "RCHO" "TOLU"
- **S11:** "ACET" "ACYL" "ALK1" "ALK2" "ALK3" "ALK4" "ALK5" "ARO1" "ARO2" "BALD" "BENZ" "CCHO" "ETHE" "HCHO" "IPRD" "MACR" "MEK" "OLE1" "OLE2" "RCHO"
- **S11D:** "ACET" "ACRO" "ACYL" "ALLENE" "BALD" "BENZ" "BUTDE13" "BUTENE1" "C2BENZ" "C2BUTE" "C2PENT" "C4RCHO1" "CCHO" "CROTALD" "ETACTYL" "ETHANE" "ETHE" "HCHO" "HEXENE1" "ISOBUTEN" "M2C3" "M2C4" "M2C6" "M2C7" "M3C6" "M3C7" "MACR" "MEACTYL" "MEK" "MXYLENE" "NC1" "NC4" "NC5" "NC6" "NC7" "NC8" "NC9" "OLE2" "OTH2" "OTH4" "OTH5" "OXYLENE" "PENTEN1" "PROPALD" "PROPANE" "PROPENE" "PXYLENE" "RCHO" "STYRENE" "TMB123" "TMB124" "TMB135" "TOLUENE"
- **S16C:** "ACET" "ACETL" "ACRO" "ACYLS" "ALK3" "ALK4" "ALK5" "BALD" "BENZ" "BUT13" "BZ123" "BZ124" "BZ135" "C2BEN" "ETCHO" "ETHAN" "ETHEN" "HCHO" "MACR" "MECHO" "MEK" "MXYL" "NC4" "OLE1" "OLE2" "OLE3" "OLE4" "OLEA1" "OTH1" "OTH3" "OTH4" "OXYL" "PROP" "PROPE" "PXYL" "RCHO" "STYRS" "TOLU"
- **S18B:** "ACET" "ACETL" "ACRO" "ACYLS" "ALK3" "ALK4" "ALK5" "BALD" "BENZ" "BUT13" "BZ123" "BZ124" "BZ135" "C2BEN" "ETCHO" "ETHAN" "ETHEN" "HCHO" "MACR" "MECHO" "MEK" "MXYL" "NC4" "OLE1" "OLE2" "OLE3" "OLE4" "OLEA1" "OTH1" "OTH3" "OTH4" "OXYL" "PROP" "PROPE" "PXYL" "RCHO" "STYRS" "TOLU"

References

Carter, W. P. (2015). Development of a database for chemical mechanism assignments for volatile organic emissions. *Journal of the Air & Waste Management Association*, 65(10), 1171-1184.

See Also[speciate](#)**Examples**

```

{
id <- 1:2
df <- data.frame(V1 = 1:2, V2 = 1:2)
dx <- speciate(
x = df,
spec = "nmhc",
fuel = "E25",
veh = "LDV",
eu = "Exhaust"
)
dx$id <- rep(id, length(unique(dx$pol)))
names(dx)
vocE25EX <- emis_chem2(df = dx, mech = "CB05", nx = c("V1", "V2"))
}

```

emis_cold

*Estimation of cold start emissions hourly for the of the week***Description**

emis_cold emissions are estimated as the product of the vehicles on a road, length of the road, emission factor evaluated at the respective speed. The estimation considers the beta parameter, the fraction of mileage driven

Usage

```

emis_cold(
  veh,
  lkm,
  ef,
  efcold,
  beta,
  speed = 34,
  agemax = if (!inherits(x = veh, what = "list")) { ncol(veh) } else {
    ncol(veh[[1]]) },
  profile,
  simplify = FALSE,
  hour = nrow(profile),
  day = ncol(profile),
  array = TRUE,
  verbose = FALSE
)

```

Arguments

veh	"Vehicles" data-frame or list of "Vehicles" data-frame. Each data-frame as number of columns matching the age distribution of that type of vehicle. The number of rows is equal to the number of streets link
lkm	Length of each link
ef	List of functions of emission factors of vehicular categories
efcold	List of functions of cold start emission factors of vehicular categories
beta	Dataframe with the hourly cold-start distribution to each day of the period. Number of rows are hours and columns are days
speed	Speed data-frame with number of columns as hours
agemax	Age of oldest vehicles for that category
profile	Numerical or dataframe with nrow equal to 24 and ncol 7 day of the week
simplify	Logical; to determine if EmissionsArray should les dimensions, being streets, vehicle categories and hours or default (streets, vehicle categories, hours and days). Default is FALSE to avoid break old code, but the recommendation is that new estimations use this parameter as TRUE
hour	Number of considered hours in estimation
day	Number of considered days in estimation
array	Deprecated! <code>emis_cold</code> returns only arrays. When TRUE and veh is not a list, expects a profile as a dataframe producing an array with dimensions (streets x columns x hours x days)
verbose	Logical; To show more information

Value

EmissionsArray g/h

Examples

```
## Not run:
# Do not run
data(net)
data(pc_profile)
data(fe2015)
data(fkm)
data(pc_cold)
pcf <- as.data.frame(cbind(pc_cold,pc_cold,pc_cold,pc_cold,pc_cold,pc_cold,
pc_cold))
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
133833,138441,142682,171029,151048,115228,98664,126444,101027,
84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
veh <- data.frame(PC_G = PC_G)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
pcw <- temp_fact(net$ldv+net$hdv, pc_profile)
speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
```

```

pckm <- units::set_units(fkm[[1]](1:24), "km"); pckma <- cumsum(pckm)
cod1 <- emis_det(po = "CO", cc = 1000, eu = "III", km = pckma[1:11])
cod2 <- emis_det(po = "CO", cc = 1000, eu = "I", km = pckma[12:24])
#vehicles newer than pre-euro
co1 <- fe2015[fe2015$Pollutant=="CO", ] #24 obs!!!
cod <- c(co1$PC_G[1:24]*c(cod1,cod2),co1$PC_G[25:nrow(co1)])
lef <- ef_ldv_scaled(co1, cod, v = "PC", cc = "<=1400",
                    f = "G",p = "CO", eu=co1$Euro_LDV)
# Mohtly average temperature 18 Celcius degrees
lefec <- ef_ldv_cold_list(df = co1, ta = 18, cc = "<=1400", f = "G",
                        eu = co1$Euro_LDV, p = "CO" )
lefec <- c(lefec,lefec[length(lefec)], lefec[length(lefec)],
          lefec[length(lefec)], lefec[length(lefec)],
          lefec[length(lefec)])
length(lefec) == ncol(pc1)
#emis change length of 'ef' to match ncol of 'veh'
class(lefec)
PC_CO_COLD <- emis_cold(veh = pc1,
                      lkm = net$lkm,
                      ef = lef,
                      efcold = lefec,
                      beta = pcf,
                      speed = speed,
                      profile = pc_profile)

class(PC_CO_COLD)
plot(PC_CO_COLD)
lpc <- list(pc1, pc1)
PC_CO_COLDv2 <- emis_cold(veh = pc1,
                        lkm = net$lkm,
                        ef = lef,
                        efcold = lefec,
                        beta = pcf,
                        speed = speed,
                        profile = pc_profile,
                        hour = 2,
                        day = 1)

## End(Not run)

```

emis_cold_td

*Estimation of cold start emissions with top-down approach***Description**

`emis_cold_td` estimates cold start emissions with a top-down approach. This is, annual or monthly emissions or region. Specifically, the emissions are estimated for row of the simple feature (row of the spatial feature).

In general was designed so that each simple feature is a region with different average monthly temperature. This function, as other in this package, adapts to the class of the input data. providing flexibility to the user.

Usage

```
emis_cold_td(
  veh,
  lkm,
  ef,
  efcold,
  beta,
  pro_month,
  params,
  verbose = FALSE,
  fortran = FALSE,
  nt = ifelse(check_nt() == 1, 1, check_nt()/2)
)
```

Arguments

veh	"Vehicles" data-frame or spatial feature, where columns are the age distribution of that vehicle. and rows each simple feature or region. The number of rows is equal to the number of streets link
lkm	Numeric; mileage by the age of use of each vehicle.
ef	Numeric; emission factor with
efcold	Data.frame. When it is a data.frame, each column is for each type of vehicle by age of use, rows are each simple feature. When you have emission factors for each month, the order should be a data.frame in a long format, as returned by ef_ldv_cold .
beta	Data.frame with the fraction of cold starts. The rows are the fraction for each spatial feature or subregion, the columns are the age of use of vehicle.
pro_month	Numeric; monthly profile to distribute annual mileage in each month.
params	List of parameters; Add columns with information to returning data.frame
verbose	Logical; To show more information
fortran	Logical; to try the fortran calculation.
nt	Integer; Number of threads which must be lower than max available. See check_nt . Only when fortran = TRUE

Value

Emissions data.frame

See Also

[ef_ldv_cold](#)

Examples

```

## Not run:
# Do not run
veh <- age_ldv(1:10, agemax = 8)
euros <- c("V", "V", "IV", "III", "II", "I", "PRE", "PRE")
dt <- matrix(rep(2:25, 5), ncol = 12, nrow = 10) # 12 months, 10 rows
row.names(dt) <- paste0("Simple_Feature_", 1:10)
efc <- ef_ldv_cold(ta = dt, cc = "<=1400", f = "G", eu = euros, p = "CO", speed = Speed(34))
efh <- ef_ldv_speed(
  v = "PC", t = "4S", cc = "<=1400", f = "G",
  eu = euros, p = "CO", speed = Speed(runif(nrow(veh), 15, 40))
)
lkm <- units::as_units(18:11, "km") * 1000
cold_lkm <- cold_mileage(ltrip = units::as_units(20, "km"), ta = celsius(dt))
names(cold_lkm) <- paste0("Month_", 1:12)
veh_month <- c(rep(8, 1), rep(10, 5), 9, rep(10, 5))
system.time(
  a <- emis_cold_td(
    veh = veh,
    lkm = lkm,
    ef = efh[1, ],
    efcold = efc[1:10, ],
    beta = cold_lkm[, 1],
    verbose = TRUE
  )
)
system.time(
  a2 <- emis_cold_td(
    veh = veh,
    lkm = lkm,
    ef = efh[1, ],
    efcold = efc[1:10, ],
    beta = cold_lkm[, 1],
    verbose = TRUE,
    fortran = TRUE
  )
) # emistd2coldf.f95
a$emissions <- round(a$emissions, 8)
a2$emissions <- round(a2$emissions, 8)
identical(a, a2)

# Adding parameters
emis_cold_td(
  veh = veh,
  lkm = lkm,
  ef = efh[1, ],
  efcold = efc[1:10, ],
  beta = cold_lkm[, 1],
  verbose = TRUE,
  params = list(
    paste0("data_", 1:10),
    "moredata"
  )
)

```

```

)
)
system.time(
  aa <- emis_cold_td(
    veh = veh,
    lkm = lkm,
    ef = efh,
    efcold = efc,
    beta = cold_lkm,
    pro_month = veh_month,
    verbose = TRUE
  )
)
system.time(
  aa2 <- emis_cold_td(
    veh = veh,
    lkm = lkm,
    ef = efh,
    efcold = efc,
    beta = cold_lkm,
    pro_month = veh_month,
    verbose = TRUE,
    fortran = TRUE
  )
) # emistd5coldf.f95
aa$emissions <- round(aa$emissions, 8)
aa2$emissions <- round(aa2$emissions, 8)
identical(aa, aa2)

## End(Not run)

```

emis_det

Determine deterioration factors for urban conditions

Description

`emis_det` returns deterioration factors. The emission factors comes from the guidelines for developing emission factors of the EMEP/EEA air pollutant emission inventory guidebook <http://www.eea.europa.eu/themes/air/emep-eea-air-pollutant-emission-inventory-guidebook> This function subset an internal database of emission factors with each argument

Usage

```

emis_det(
  po,
  cc,
  eu,
  speed = Speed(18.9),
  km,

```

```

    verbose = FALSE,
    show.equation = FALSE
  )

```

Arguments

po	Character; Pollutant "CO", "NOx" or "HC"
cc	Character; Size of engine in cc covering "<=1400", "1400_2000" or ">2000"
eu	Character; Euro standard: "I", "II", "III", "III", "IV", "V", "VI", "VIc"
speed	Numeric; Speed to return Number of emission factor and not a function. It needs units in km/h
km	Numeric; accumulated mileage in km.
verbose	Logical; To show more information
show.equation	Option to see or not the equation parameters

Value

It returns a numeric vector representing the increase in emissions due to normal deterioring

Note

The deterioration factors functions are available for technologies euro "II", "III" and "IV". In order to cover all euro technologies, this function assumes that the deterioration function of "III" and "IV" applies for "V", "VI" and "VIc". However, as these technologies are relative new, accumulated milage is low and hence, deteeriation factors small.

Examples

```

## Not run:
data(fkm)
pckm <- fkm[[1]](1:24); pckma <- cumsum(pckm)
km <- units::set_units(pckma[1:11], km)
# length eu = length km = 1
emis_det(po = "CO", cc = "<=1400", eu = "III", km = km[5], show.equation = TRUE)
# length eu = length km = 1, length speed > 1
emis_det(po = "CO", cc = "<=1400", eu = "III", km = km[5], speed = Speed(1:10))
# length km != length eu error
# (cod1 <- emis_det(po = "CO", cc = "<=1400", eu = c("III", "IV"), speed = Speed(30),
# km = km[4]))
# length eu = 1 length km > 1
emis_det(po = "CO", cc = "<=1400", eu = "III", km = km)
# length eu = 2, length km = 2 (if different length, error!)
(cod1 <- emis_det(po = "CO", cc = "<=1400", eu = c("III", "IV"), km = km[4:5]))
# length eu = 2, length km = 2, length speed > 1
(cod1 <- emis_det(po = "CO", cc = "<=1400", eu = c("III", "IV"), speed = Speed(0:130),
km = km[4:5]))
euros <- c("V","V","V", "IV", "IV", "IV", "III", "III", "III", "III")
# length eu = 2, length km = 2, length speed > 1
(cod1 <- emis_det(po = "CO", cc = "<=1400", eu = euros, speed = Speed(1:100),

```

```

km = km[1:10]))
cod1 <- as.matrix(cod1[, 1:11])
filled.contour(cod1, col = cptcity::cpt(6277, n = 20))
filled.contour(cod1, col = cptcity::lucky(n = 19))
euro <- c(rep("V", 5), rep("IV", 5), "III")
euros <- rbind(euro, euro)
(cod1 <- emis_det(po = "CO", cc = "<=1400", eu = euros, km = km))

## End(Not run)

```

emis_dist

*Allocate emissions into spatial objects (street emis to grid)***Description**

`emis_dist` allocates emissions proportionally to each feature. "Spatial" objects are converted to "sf" objects. Currently, 'LINESTRING' or 'MULTILINESTRING' are supported. The emissions are distributed in each street.

Usage

```
emis_dist(gy, spobj, pro, osm, verbose = FALSE)
```

Arguments

gy	Numeric; a unique total (top-down)
spobj	A spatial dataframe of class "sp" or "sf". When class is "sp" it is transformed to "sf".
pro	Matrix or data-frame profiles, for instance, <code>pc_profile</code> .
osm	Numeric; vector of length 5, for instance, <code>c(5, 3, 2, 1, 1)</code> . The first element covers 'motorway' and 'motorway_link'. The second element covers 'trunk' and 'trunk_link'. The third element covers 'primary' and 'primary_link'. The fourth element covers 'secondary' and 'secondary_link'. The fifth element covers 'tertiary' and 'tertiary_link'.
verbose	Logical; to show more info.

Note

When `spobj` is a 'Spatial' object (class of `sp`), they are converted into 'sf'.

Examples

```

## Not run:
data(net)
data(pc_profile)
po <- 1000
t1 <- emis_dist(gy = po, spobj = net)

```



```

head(t1)
sum(t1$gy)
#t1 <- emis_dist(gy = po, spobj = net, osm = c(5, 3, 2, 1, 1) )
t1 <- emis_dist(gy = po, spobj = net, pro = pc_profile)

## End(Not run)

```

emis_evap

*Estimation of evaporative emissions***Description**

`emis_evap` estimates evaporative emissions from EMEP/EEA emisison guidelines

Usage

```

emis_evap(
  veh,
  x,
  ed,
  hotfi,
  hotc,
  warmc,
  carb = 0,
  p,
  params,
  pro_month,
  verbose = FALSE
)

```

Arguments

veh	Numeric or data.frame of Vehicles with untis 'veh'.
x	Numeric which can be either, daily mileage by age of use with units 'lkm', number of trips or number of proc. When it has units 'lkm', all the emission factors must be in 'g/km'. When ed is in g/day, x it is the number of days (without units). When hotfi, hotc or warmc are in g/trip, x it is the number of trips (without units). When hotfi, hotc or warmc are in g/proced, x it is the number of proced (without units).
ed	average daily evaporative emissions. If x has units 'lkm', the units of ed must be 'g/km', other case, this are simply g/day (without units).
hotfi	average hot running losses or soak evaporative factor for vehicles with fuel injection and returnless fuel systems. If x has units 'lkm', the units of ed must be 'g/km', other case, this is simply g/trip or g/proced
hotc	average running losses or soak evaporative factor for vehicles with carburetor or fuel return system for vehicles with fuel injection and returnless fuel systems. If x has units 'lkm', the units of ed must be 'g/km',

warmc	average cold and warm running losses or soak evaporative factor for vehicles with carburetor or fuel return system for vehicles with fuel injection and return-less fuel systems. If x has units 'lkm', the units of ed must be 'g/km',
carb	fraction of gasoline vehicles with carburetor or fuel return system.
p	Fraction of trips finished with hot engine
params	Character; Add columns with information to returning data.frame
pro_month	Numeric; monthly profile to distribute annual mileage in each month.
verbose	Logical; To show more information

Value

numeric vector of emission estimation in grams

Note

When veh is a "Vehicles" data.frame, emission factors are evaluated till the number of columns of veh. For instance, if the length of the emission factor is 20 but the number of columns of veh is 10, the 10 first emission factors are used.

References

Mellios G and Ntziachristos 2016. Gasoline evaporation. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2009

See Also

[ef_evap](#)

Examples

```
## Not run:
(a <- Vehicles(1:10))
(lkm <- units::as_units(1:10, "km"))
(ef <- EmissionFactors(1:10))
(ev <- emis_evap(veh = a, x = lkm, hotfi = ef))

## End(Not run)
```

emis_evap2

Estimation of evaporative emissions 2

Description

emis_evap performs the estimation of evaporative emissions from EMEP/EEA emission guidelines with Tier 2.

Usage

```
emis_evap2(
  veh,
  name,
  size,
  fuel,
  aged,
  nd4,
  nd3,
  nd2,
  nd1,
  hs_nd4,
  hs_nd3,
  hs_nd2,
  hs_nd1,
  r1_nd4,
  r1_nd3,
  r1_nd2,
  r1_nd1,
  d_nd4,
  d_nd3,
  d_nd2,
  d_nd1
)
```

Arguments

veh	Total number of vehicles by age of use. If is a list of 'Vehicles' data-frames, it will sum the columns of the eight element of the list representing the 8th hour. It was chosen this hour because it is morning rush hour but the user can adapt the data to this function
name	Character of type of vehicle
size	Character of size of vehicle
fuel	Character of fuel of vehicle
aged	Age distribution vector. E.g.: 1:40
nd4	Number of days with temperature between 20 and 35 Celsius degrees
nd3	Number of days with temperature between 10 and 25 Celsius degrees
nd2	Number of days with temperature between 0 and 15 Celsius degrees
nd1	Number of days with temperature between -5 and 10 Celsius degrees
hs_nd4	average daily hot-soak evaporative emissions for days with temperature between 20 and 35 Celsius degrees
hs_nd3	average daily hot-soak evaporative emissions for days with temperature between 10 and 25 Celsius degrees
hs_nd2	average daily hot-soak evaporative emissions for days with temperature between 0 and 15 Celsius degrees

hs_nd1	average daily hot-soak evaporative emissions for days with temperature between -5 and 10 Celsius degrees
r1_nd4	average daily running losses evaporative emissions for days with temperature between 20 and 35 Celsius degrees
r1_nd3	average daily running losses evaporative emissions for days with temperature between 10 and 25 Celsius degrees
r1_nd2	average daily running losses evaporative emissions for days with temperature between 0 and 15 Celsius degrees
r1_nd1	average daily running losses evaporative emissions for days with temperature between -5 and 10 Celsius degrees
d_nd4	average daily diurnal evaporative emissions for days with temperature between 20 and 35 Celsius degrees
d_nd3	average daily diurnal evaporative emissions for days with temperature between 10 and 25 Celsius degrees
d_nd2	average daily diurnal evaporative emissions for days with temperature between 0 and 15 Celsius degrees
d_nd1	average daily diurnal evaporative emissions for days with temperature between -5 and 10 Celsius degrees

Value

dataframe of emission estimation in grams/days

References

Mellios G and Ntziachristos 2016. Gasoline evaporation. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2009

Examples

```
## Not run:
data(net)
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
          133833,138441,142682,171029,151048,115228,98664,126444,101027,
          84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
          1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
veh <- data.frame(PC_G = PC_G)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
ef1 <- ef_evap(ef = "erhotc",v = "PC", cc = "<=1400", dt = "0_15", ca = "no")
dfe <- emis_evap2(veh = pc1,
                 name = "PC",
                 size = "<=1400",
                 fuel = "G",
                 aged = 1:ncol(pc1),
                 nd4 = 10,
                 nd3 = 4,
                 nd2 = 2,
                 nd1 = 1,
```

```

hs_nd4 = ef1*1:ncol(pc1),
hs_nd3 = ef1*1:ncol(pc1),
hs_nd2 = ef1*1:ncol(pc1),
hs_nd1 = ef1*1:ncol(pc1),
d_nd4 = ef1*1:ncol(pc1),
d_nd3 = ef1*1:ncol(pc1),
d_nd2 = ef1*1:ncol(pc1),
d_nd1 = ef1*1:ncol(pc1),
r1_nd4 = ef1*1:ncol(pc1),
r1_nd3 = ef1*1:ncol(pc1),
r1_nd2 = ef1*1:ncol(pc1),
r1_nd1 = ef1*1:ncol(pc1))
lpc <- list(pc1, pc1, pc1, pc1,
           pc1, pc1, pc1, pc1)
dfe <- emis_evap2(veh = lpc,
                 name = "PC",
                 size = "<=1400",
                 fuel = "G",
                 aged = 1:ncol(pc1),
                 nd4 = 10,
                 nd3 = 4,
                 nd2 = 2,
                 nd1 = 1,
                 hs_nd4 = ef1*1:ncol(pc1),
                 hs_nd3 = ef1*1:ncol(pc1),
                 hs_nd2 = ef1*1:ncol(pc1),
                 hs_nd1 = ef1*1:ncol(pc1),
                 d_nd4 = ef1*1:ncol(pc1),
                 d_nd3 = ef1*1:ncol(pc1),
                 d_nd2 = ef1*1:ncol(pc1),
                 d_nd1 = ef1*1:ncol(pc1),
                 r1_nd4 = ef1*1:ncol(pc1),
                 r1_nd3 = ef1*1:ncol(pc1),
                 r1_nd2 = ef1*1:ncol(pc1),
                 r1_nd1 = ef1*1:ncol(pc1))

## End(Not run)

```

emis_grid

Allocate emissions into a grid returning point emissions or flux

Description

`emis_grid` allocates emissions proportionally to each grid cell. The process is performed by the intersection between geometries and the grid. It means that requires "sr" according to your location for the projection. It is assumed that `spobj` is a `Spatial*DataFrame` or an "sf" with the pollutants in data. This function returns an object of class "sf".

It is

Usage

```
emis_grid(spobj = net, g, sr, type = "lines", FN = "sum", flux = TRUE, k = 1)
```

Arguments

spobj	A spatial dataframe of class "sp" or "sf". When class is "sp" it is transformed to "sf".
g	A grid with class "SpatialPolygonsDataFrame" or "sf".
sr	Spatial reference e.g: 31983. It is required if spobj and g are not projected. Please, see http://spatialreference.org/ .
type	type of geometry: "lines", "points" or "polygons".
FN	Character indicating the function. Default is "sum"
flux	Logical, if TRUE, it return flux (mass / area / time (implicit)) in a polygon grid, if false, mass / time (implicit) as points, in a similar fashion as EDGAR provide data.
k	Numeric to multiply emissions

Note

1) If flux = TRUE (default), emissions are flux = mass / area / time (implicit), as polygons. If flux = FALSE, emissions are mass / time (implicit), as points. Time units are not displayed because each use can have different time units for instance, year, month, hour second, etc.

2) Therefore, it is good practice to have time units in 'spobj'. This implies that spobj MUST include units!.

3) In order to check the sum of the emissions, you must calculate the grid-area in km² and multiply by each column of the resulting emissions grid, and then sum.

4) If FN = "sum", is mass conservative!.

Examples

```
## Not run:
data(net)
g <- make_grid(net, 1/102.47/2) #500m in degrees
names(net)
netsf <- sf::st_as_sf(net)
netg <- emis_grid(spobj = netsf[, c("ldv", "hdv")], g = g, sr= 31983)
plot(netg["ldv"], axes = TRUE)
plot(netg["hdv"], axes = TRUE)
netg <- emis_grid(spobj = netsf[, c("ldv", "hdv")], g = g, sr= 31983, FN = "mean")
plot(netg["ldv"], axes = TRUE)
plot(netg["hdv"], axes = TRUE)
netg <- emis_grid(spobj = netsf[, c("ldv", "hdv")], g = g, sr= 31983, flux = FALSE)
plot(netg["ldv"], axes = TRUE, pch = 16,
pal = cptcity::cpt(colorRampPalette= TRUE, rev = TRUE), cex = 3)

## End(Not run)
```

emis_hot_td

*Estimation of hot exhaust emissions with a top-down approach***Description**

`emis_hot_td` estimates cold start emissions with a top-down approach. This is, annual or monthly emissions or region. Specifically, the emissions are estimated for the row of the simple feature (row of the spatial feature).

In general was designed so that each simple feature is a region with different average monthly temperature. This function, as others in this package, adapts to the class of the input data. providing flexibility to the user.

Usage

```
emis_hot_td(
  veh,
  lkm,
  ef,
  pro_month,
  params,
  verbose = FALSE,
  fortran = FALSE,
  nt = ifelse(check_nt() == 1, 1, check_nt()/2)
)
```

Arguments

veh	"Vehicles" data-frame or spatial feature, where columns are the age distribution of that vehicle. and rows each simple feature or region.
lkm	Numeric; mileage by the age of use of each vehicle.
ef	Numeric or data.frame; emission factors. When it is a data.frame number of rows can be for each region, or also, each region repeated along 12 months. For instance, if you have 10 regions the number of rows of ef can also be 120 (10 * 120). when you have emission factors that varies with month, see ef_china .
pro_month	Numeric or data.frame; monthly profile to distribute annual mileage in each month. When it is a data.frame, each region (row) can have a different monthly profile.
params	List of parameters; Add columns with information to returning data.frame
verbose	Logical; To show more information
fortran	Logical; to try the fortran calculation.
nt	Integer; Number of threads which must be lower than max available. See check_nt . Only when fortran = TRUE

Details

List to make easier to use this function.

1. 'pro_month' is data.frame AND rows of 'ef' and 'veh' are equal.
2. 'pro_month' is numeric AND rows of 'ef' and 'veh' are equal.
3. 'pro_month' is data.frame AND rows of 'ef' is 12X rows of 'veh'.
4. 'pro_month' is numeric AND rows of 'ef' is 12X rows of 'veh'.
5. 'pro_month' is data.frame AND class of 'ef' is 'units'.
6. 'pro_month' is numeric AND class of 'ef' is 'units'.
7. NO 'pro_month' AND class of 'ef' is 'units'.
8. NO 'pro_month' AND 'ef' is data.frame.
9. 'pro_month' is numeric AND rows of 'ef' is 12 (monthly 'ef').

Value

Emissions data.frame

See Also

[ef_ldv_speed](#) [ef_china](#)

Examples

```
## Not run:
# Do not run
euros <- c("V", "V", "IV", "III", "II", "I", "PRE", "PRE")
efh <- ef_ldv_speed(
  v = "PC", t = "4S", cc = "<=1400", f = "G",
  eu = euros, p = "CO", speed = Speed(34)
)
lkm <- units::as_units(c(20:13), "km") * 1000
veh <- age_ldv(1:10, agemax = 8)
system.time(
  a <- emis_hot_td(
    veh = veh,
    lkm = lkm,
    ef = EmissionFactors(as.numeric(efh[, 1:8])),
    verbose = TRUE
  )
)
system.time(
  a2 <- emis_hot_td(
    veh = veh,
    lkm = lkm,
    ef = EmissionFactors(as.numeric(efh[, 1:8])),
    verbose = TRUE,
    fortran = TRUE
  )
) # emistd7f.f95
```



```

identical(a, a2)

# adding columns
emis_hot_td(
  veh = veh,
  lkm = lkm,
  ef = EmissionFactors(as.numeric(efh[, 1:8])),
  verbose = TRUE,
  params = list(paste0("data_", 1:10), "moredata")
)

# monthly profile (numeric) with numeric ef
veh_month <- c(rep(8, 1), rep(10, 5), 9, rep(10, 5))
system.time(
  aa <- emis_hot_td(
    veh = veh,
    lkm = lkm,
    ef = EmissionFactors(as.numeric(efh[, 1:8])),
    pro_month = veh_month,
    verbose = TRUE
  )
)
system.time(
  aa2 <- emis_hot_td(
    veh = veh,
    lkm = lkm,
    ef = EmissionFactors(as.numeric(efh[, 1:8])),
    pro_month = veh_month,
    verbose = TRUE,
    fortran = TRUE
  )
) # emistd5f.f95
aa$emissions <- round(aa$emissions, 8)
aa2$emissions <- round(aa2$emissions, 8)
identical(aa, aa2)

# monthly profile (numeric) with data.frame ef
veh_month <- c(rep(8, 1), rep(10, 5), 9, rep(10, 5))
def <- matrix(EmissionFactors(as.numeric(efh[, 1:8])),
  nrow = nrow(veh), ncol = ncol(veh), byrow = TRUE
)
def <- EmissionFactors(def)
system.time(
  aa <- emis_hot_td(
    veh = veh,
    lkm = lkm,
    ef = def,
    pro_month = veh_month,
    verbose = TRUE
  )
)
system.time(
  aa2 <- emis_hot_td(

```

```

    veh = veh,
    lkm = lkm,
    ef = def,
    pro_month = veh_month,
    verbose = TRUE,
    fortran = TRUE
  )
) # emistd1f.f95
aa$emissions <- round(aa$emissions, 8)
aa2$emissions <- round(aa2$emissions, 8)
identical(aa, aa2)

# monthly profile (data.frame)
dfm <- matrix(c(rep(8, 1), rep(10, 5), 9, rep(10, 5)),
  nrow = 10, ncol = 12,
  byrow = TRUE
)
system.time(
  aa <- emis_hot_td(
    veh = veh,
    lkm = lkm,
    ef = EmissionFactors(as.numeric(efh[, 1:8])),
    pro_month = dfm,
    verbose = TRUE
  )
)
system.time(
  aa2 <- emis_hot_td(
    veh = veh,
    lkm = lkm,
    ef = EmissionFactors(as.numeric(efh[, 1:8])),
    pro_month = dfm,
    verbose = TRUE,
    fortran = TRUE
  )
) # emistd6f.f95
aa$emissions <- round(aa$emissions, 2)
aa2$emissions <- round(aa2$emissions, 2)
identical(aa, aa2)

# Suppose that we have a EmissionsFactor data.frame with number of rows for each month
# number of rows are 10 regions
# number of columns are 12 months
tem <- runif(n = 6 * 10, min = -10, max = 35)
temp <- c(rev(tem[order(tem)]), tem[order(tem)])
plot(temp)
dftemp <- celsius(matrix(temp, ncol = 12))
dfef <- ef_evap(
  ef = c(rep("eshotfi", 8)),
  v = "PC",
  cc = "<=1400",
  dt = dftemp,
  show = F,

```

```

    ca = "small",
    ltrip = units::set_units(10, km),
    pollutant = "NMHC"
  )
dim(dfef) # 120 rows and 9 columns, 8 ef (g/km) and 1 for month
system.time(
  aa <- emis_hot_td(
    veh = veh,
    lkm = lkm,
    ef = dfef,
    pro_month = veh_month,
    verbose = TRUE
  )
)
system.time(
  aa2 <- emis_hot_td(
    veh = veh,
    lkm = lkm,
    ef = dfef,
    pro_month = veh_month,
    verbose = TRUE,
    fortran = TRUE
  )
) # emistd3f.f95
aa$emissions <- round(aa$emissions, 2)
aa2$emissions <- round(aa2$emissions, 2)
identical(aa, aa2)
plot(aggregate(aa$emissions, by = list(aa$month), sum)$x)

# Suppose that we have a EmissionsFactor data.frame with number of rows for each month
# monthly profile (data.frame)
system.time(
  aa <- emis_hot_td(
    veh = veh,
    lkm = lkm,
    ef = dfef,
    pro_month = dfm,
    verbose = TRUE
  )
)
system.time(
  aa2 <- emis_hot_td(
    veh = veh,
    lkm = lkm,
    ef = dfef,
    pro_month = dfm,
    verbose = TRUE,
    fortran = TRUE
  )
) # emistd4f.f95
aa$emissions <- round(aa$emissions, 8)
aa2$emissions <- round(aa2$emissions, 8)
identical(aa, aa2)

```

```
plot(aggregate(aa$emissions, by = list(aa$month), sum)$x)

## End(Not run)
```

emis_merge

Merge several emissions files returning data-frames or 'sf' of lines

Description

`emis_merge` reads rds files and returns a data-frame or an object of 'spatial feature' of streets, merging several files.

Usage

```
emis_merge(
  pol = "CO",
  what = "STREETS.rds",
  streets = T,
  net,
  FN = "sum",
  ignore,
  path = "emi",
  crs,
  under = "after",
  as_list = FALSE,
  k = 1,
  verbose = TRUE
)
```

Arguments

<code>pol</code>	Character. Pollutant.
<code>what</code>	Character. Word to search the emissions names, "STREETS", "DF" or whatever name. It is important to include the extension '.rds'. For instance, If you have several files "XX_CO_STREETS.rds", what should be "STREETS.rds"
<code>streets</code>	Logical. If true, <code>emis_merge</code> will read the street emissions created with <code>emis_post</code> by "streets_wide", returning an object with class 'sf'. If false, it will read the emissions data-frame and rbind them.
<code>net</code>	'Spatial feature' or 'SpatialLinesDataFrame' with the streets. It is expected # that the number of rows is equal to the number of rows of street emissions. If # not, the function will stop.
<code>FN</code>	Character indicating the function. Default is "sum"
<code>ignore</code>	Character; Which pollutants or other charavter would you like to remove?
<code>path</code>	Character. Path where emissions are located
<code>crs</code>	coordinate reference system in numeric format from http://spatialreference.org/ to transform/project spatial data using <code>sf::st_transform</code>

under	"Character"; "after" when you stored your pollutant x as 'X_' "before" when '_X' and "none" for merging directly the files.
as_list	"Logical"; for returning the results as list or not.
k	factor
verbose	Logical to display more information or not. Default is TRUE

Value

'Spatial feature' of lines or a dataframe of emissions

Examples

```
## Not run:
# Do not run

## End(Not run)
```

emis_order	<i>Re-order the emission to match specific hours and days</i>
------------	---

Description

Emissions are usually estimated for a year, 24 hours, or one week from monday to sunday (with 168 hours). This depends on the availability of traffic data. When an air quality simulation is going to be done, they cover specific periods of time. For instance, WRF Chem emissions files support periods of time, or two emissions sets for a representative day (0-12z 12-0z). Also a WRF Chem simulation scan starts a thursday at 00:00 UTC, cover 271 hours of simulations, but hour emissions are in local time and cover only 168 hours starting on monday. This function tries to transform our emissions in local time to the desired UTC time, by recycling the local emissions.

Usage

```
emis_order(
  x,
  lt_emissions,
  start_utc_time,
  desired_length,
  tz_lt = Sys.timezone(),
  seconds = 0,
  k = 1,
  net,
  verbose = TRUE
)
```

Arguments

x	one of the following: <ul style="list-style-type: none"> • Spatial object of class "Spatial". Columns are hourly emissions. • Spatial Object of class "sf". Columns are hourly emissions. • "data.frame", "matrix" or "Emissions". <p>In all cases, columns are hourly emissions.</p>
lt_emissions	Local time of the emissions at the first hour. It must be the before time of start_utc_time. For instance, if start_utc_time is 2020-02-02 00:00, and your emissions starts monday at 00:00, your lt_emissions must be 2020-01-27 00:00. The argument tz_lt will detect your current local time zone and do the rest for you.
start_utc_time	UTC time for the desired first hour. For instance, the first hour of the namelist.input for WRF.
desired_length	Integer; length to recycle or subset local emissions. For instance, the length of the WRF Chem simulations, states at namelist.input.
tz_lt	Character, Time zone of the local emissions. Default value is derived from Sys.timezone(), however, it accepts any other. If you enter a wrong tz, this function will show you a menu to choose one of the 697 time zones available.
seconds	Number of seconds to add
k	Numeric, factor.
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING".
verbose	Logical, to show more information, default is TRUE.

Value

sf or data.frame

See Also

[GriddedEmissionsArray](#)

Examples

```
## Not run:
#do not run
data(net)
data(pc_profile)
data(fe2015)
data(fkm)
PC_G <- c(33491, 22340, 24818, 31808, 46458, 28574, 24856, 28972, 37818, 49050, 87923,
         133833, 138441, 142682, 171029, 151048, 115228, 98664, 126444, 101027,
         84771, 55864, 36306, 21079, 20138, 17439, 7854, 2215, 656, 1262, 476, 512,
         1181, 4991, 3711, 5653, 7039, 5839, 4257, 3824, 3068)
veh <- data.frame(PC_G = PC_G)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
pcw <- temp_fact(net$ldv+net$hdv, pc_profile)
```

```

speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
pckm <- units::set_units(fkm[[1]](1:24), "km")
pckma <- cumsum(pckm)
cod1 <- emis_det(po = "CO", cc = 1000, eu = "III", km = pckma[1:11])
cod2 <- emis_det(po = "CO", cc = 1000, eu = "I", km = pckma[12:24])
#vehicles newer than pre-euro
co1 <- fe2015[fe2015$Pollutant=="CO", ] #24 obs!!!
cod <- c(co1$PC_G[1:24]*c(cod1,cod2),co1$PC_G[25:nrow(co1)])
lef <- ef_ldv_scaled(co1, cod, v = "PC", t = "4S", cc = "<=1400",
                    f = "G",p = "CO", eu=co1$Euro_LDV)
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed, agemax = 41,
            profile = pc_profile, simplify = TRUE)

class(E_CO)
E_CO_STREETS <- emis_post(arra = E_CO, pollutant = "CO", by = "streets", net = net)
g <- make_grid(net, 1/102.47/2, 1/102.47/2) #500m in degrees
E_CO_g <- emis_grid(spobj = E_CO_STREETS, g = g, sr= 31983)
head(E_CO_g) #class sf
gr <- GriddedEmissionsArray(E_CO_g, rows = 19, cols = 23, times = 168, T)
wCO <- emis_order(x = E_CO_g,
                  lt_emissions = "2020-02-19 00:00",
                  start_utc_time = "2020-02-20 00:00",
                  desired_length = 241)

## End(Not run)

```

emis_paved

*Estimation of resuspension emissions from paved roads***Description**

emis_paved estimates vehicular emissions from paved roads. The vehicular emissions are estimated as the product of the vehicles on a road, length of the road, emission factor from AP42 13.2.1 Paved roads. It is assumed dry hours and annual aggregation should consider moisture factor. It depends on Average Daily Traffic (ADT)

Usage

```

emis_paved(
  veh,
  adt,
  lkm,
  k = 0.62,
  sL1 = 0.6,
  sL2 = 0.2,
  sL3 = 0.06,
  sL4 = 0.03,
  W,
  net = net
)

```

Arguments

veh	Numeric vector with length of elements equals to number of streets It is an array with dimensions number of streets x hours of day x days of week
adt	Numeric vector of with Average Daily Traffic (ADT)
lkm	Length of each link
k	K_PM30 = 3.23 (g/vkm), K_PM15 = 0.77 (g/vkm), K_PM10 = 0.62 (g/vkm) and K_PM2.5 = 0.15 (g/vkm).
sL1	Silt loading (g/m2) for roads with ADT <= 500
sL2	Silt loading (g/m2) for roads with ADT > 500 and <= 5000
sL3	Silt loading (g/m2) for roads with ADT > 5000 and <= 1000
sL4	Silt loading (g/m2) for roads with ADT > 10000
W	array of dimensions of veh. It consists in the hourly averaged weight of traffic fleet in each road
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"

Value

emission estimation g/h

Note

silt values can vary a lot. For comparison:

ADT	US-EPA g/m2	CENMA (Chile) g/m2
< 500	0.6	2.4
500-5000	0.2	0.7
5000-1000	0.06	0.6
>10000	0.03	0.3

References

EPA, 2016. Emission factor documentation for AP-42. Section 13.2.1, Paved Roads. <https://www3.epa.gov/ttn/chief/ap42/ch>

CENMA Chile: Actualizacion de inventario de emisiones de contaminntes atmosfericos RM 2020 Universidad de Chile#'

Examples

```
## Not run:
# Do not run
veh <- matrix(1000, nrow = 10, ncol = 10)
W <- veh*1.5
lkm <- 1:10
ADT <- 1000:1010
emi <- emis_paved(veh = veh, adt = ADT, lkm = lkm, k = 0.65, W = W)
class(emi)
```



```
head(emi)

## End(Not run)
```

emis_post	<i>Post emissions</i>
-----------	-----------------------

Description

emis_post simplify emissions estimated as total per type category of vehicle or by street. It reads EmissionsArray and Emissions classes. It can return a dataframe with hourly emissions at each street, or a database with emissions by vehicular category, hour, including size, fuel and other characteristics.

Usage

```
emis_post(arr, veh, size, fuel, pollutant, by = "veh", net, type_emi, k = 1)
```

Arguments

arr	Array of emissions 4d: streets x category of vehicles x hours x days or 3d: streets x category of vehicles x hours
veh	Character, type of vehicle
size	Character, size or weight
fuel	Character, fuel
pollutant	Pollutant
by	Type of output, "veh" for total vehicular category , "streets_narrow" or "streets". "streets" returns a dataframe with rows as number of streets and columns the hours as days*hours considered, e.g. 168 columns as the hours of a whole week and "streets repeats the row number of streets by hour and day of the week
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING". Only when by = 'streets_wide'
type_emi	Character, type of emissions(exhaust, evaporative, etc)
k	Numeric, factor

Note

This function depends on EmissionsArray objects which currently has 4 dimensions. However, a future version of VEIN will produce EmissionsArray with 3 dimensiones and his fungeorge soros drugsectio also will change. This change will be made in order to not produce inconsistencies with previous versions, therefore, if the user count with an EmissionsArry with 4 dimension, it will be able to use this function.

Examples

```

## Not run:
# Do not run
data(net)
data(pc_profile)
data(fe2015)
data(fkm)
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
         133833,138441,142682,171029,151048,115228,98664,126444,101027,
         84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
         1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
# Estimation for morning rush hour and local emission factors
speed <- data.frame(S8 = net$ps)
p1h <- matrix(1)
lef <- EmissionFactorsList(fe2015[fe2015$Pollutant=="CO", "PC_G"])
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed,
            profile = p1h)
E_CO_STREETS <- emis_post(arr = E_CO, pollutant = "CO", by = "streets_wide")
summary(E_CO_STREETS)
E_CO_STREETSsf <- emis_post(arr = E_CO, pollutant = "CO",
                           by = "streets", net = net)
summary(E_CO_STREETSsf)
plot(E_CO_STREETSsf, main = "CO emissions (g/h)")
# arguments required: arr, veh, size, fuel, pollutant ad by
E_CO_DF <- emis_post(arr = E_CO, veh = "PC", size = "<1400", fuel = "G",
                    pollutant = "CO", by = "veh")
# Estimation 168 hours
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
pcw <- temp_fact(net$ldv+net$hdv, pc_profile)
speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
pckm <- units::set_units(fkm[[1]](1:24),"km"); pckma <- cumsum(pckm)
cod1 <- emis_det(po = "CO", cc = 1000, eu = "III", km = pckm[1:11])
cod2 <- emis_det(po = "CO", cc = 1000, eu = "I", km = pckm[12:24])
#vehicles newer than pre-euro
co1 <- fe2015[fe2015$Pollutant=="CO", ] #24 obs!!!
cod <- c(co1$PC_G[1:24]*c(cod1,cod2),co1$PC_G[25:nrow(co1)])
lef <- ef_ldv_scaled(dfcol = cod, v = "PC", cc = "<=1400",
                   f = "G",p = "CO", eu=co1$Euro_LDV)
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed, agemax = 41,
            profile = pc_profile)
# arguments required: arr, pollutant ad by
E_CO_STREETS <- emis_post(arr = E_CO, pollutant = "CO", by = "streets")
summary(E_CO_STREETS)
# arguments required: arr, veh, size, fuel, pollutant ad by
E_CO_DF <- emis_post(arr = E_CO, veh = "PC", size = "<1400", fuel = "G",
                    pollutant = "CO", by = "veh")
head(E_CO_DF)
# recreating 24 profile
lpc <-list(pc1*0.2, pc1*0.1, pc1*0.1, pc1*0.2, pc1*0.5, pc1*0.8,
          pc1, pc1*1.1, pc1,
          pc1*0.8, pc1*0.5, pc1*0.5,

```

```

      pc1*0.5, pc1*0.5, pc1*0.5, pc1*0.8,
      pc1, pc1*1.1, pc1,
      pc1*0.8, pc1*0.5, pc1*0.3, pc1*0.2, pc1*0.1)
E_COv2 <- emis(veh = lpc, lkm = net$1km, ef = lef, speed = speed[, 1:24],
             agemax = 41, hour = 24, day = 1)
plot(E_COv2)
E_CO_DFv2 <- emis_post(arr = E_COv2,
                     veh = "PC",
                     size = "<1400",
                     fuel = "G",
                     type_emi = "Exhaust",
                     pollutant = "CO", by = "veh")

head(E_CO_DFv2)

## End(Not run)

```

emis_source

A function to source vein scripts

Description

[emis_source](#) source vein scripts

Usage

```

emis_source(
  path = "est",
  pattern = ".R",
  ignore = "~",
  first,
  ask = TRUE,
  recursive = TRUE,
  full.names = TRUE,
  echo = FALSE
)

```

Arguments

path	Character; path to source scripts. Default is "est".
pattern	Character; extensions of R scripts. Default is ".R".
ignore	Character; character to be excluded. Default is "~". Sometimes, the OS creates automatic back-ups, for instance "run.R~", the idea is to avoid sourcing these files.
first	Character; first script.
ask	Logical; Check inputs or not. Default is "FALSE". It allows to stop inputs
recursive	Logical; recursive or not. Default is "TRUE"
full.names	Logical; full.names or not. Default is "TRUE".
echo	Source with echo?

Examples

```
## Not run:
# Do not run

## End(Not run)
```

emis_to_streets	<i>Emis to streets distribute top-down emissions into streets</i>
-----------------	---

Description

`emis_to_streets` allocates emissions proportionally to each feature. "Spatial" objects are converted to "sf" objects. Currently, 'LINESTRING' or 'MULTILINESTRING' supported. The emissions are distributed in each street.

Usage

```
emis_to_streets(streets, dfemis, by = "ID", stpro, verbose = TRUE)
```

Arguments

streets	sf object with geometry 'LINESTRING' or 'MULTILINESTRING'. Or SpatialLinesDataFrame
dfemis	data.frame with emissions
by	Character indicating the columns that must be present in both 'street' and 'dfemis'
stpro	data.frame with two columns, category of streets and value. The name of the first column must be "stpro" and the sf streets must also have a column with the name "stpro" indicating the category of streets. The second column must have the name "VAL" indicating the associated values to each category of street
verbose	Logical; to show more info.

Note

When `spobj` is a 'Spatial' object (class of `sp`), they are converted into 'sf'.

See Also

[add_polid](#)

Examples

```
## Not run:
data(net)
stpro = data.frame(stpro = as.character(unique(net$street)),
                  VAL = 1:9)
dnet <- net["ldv"]
dnet$stpro <- as.character(net$street)
```

```

dnet$ID <- "A"
df2 <- data.frame(BC = 10, CO = 20, ID = "A")
ste <- emis_to_streets(streets = dnet, dfemis = df2)
sum(ste$ldv)
sum(net$ldv)
sum(ste$BC)
sum(df2$BC)
ste2 <- emis_to_streets(streets = dnet, dfemis = df2, stpro = stpro)
sum(ste2$ldv)
sum(net$ldv)
sum(ste2$BC)
sum(df2$BC)

## End(Not run)

```

emis_wear

*Emission estimation from tyre, brake and road surface wear***Description**

emis_wear estimates wear emissions. The sources are tyres, breaks and road surface.

Usage

```

emis_wear(
  veh,
  lkm,
  ef,
  what = "tyre",
  speed,
  agemax = ncol(veh),
  profile,
  hour = nrow(profile),
  day = ncol(profile)
)

```

Arguments

veh	Object of class "Vehicles"
lkm	Length of the road in km.
ef	list of emission factor functions class "EmissionFactorsList", length equals to hours.
what	Character for indicating "tyre", "break" or "road"
speed	Speed data-frame with number of columns as hours
agemax	Age of oldest vehicles for that category
profile	Numerical or dataframe with nrow equal to 24 and ncol 7 day of the week
hour	Number of considered hours in estimation
day	Number of considered days in estimation

Value

emission estimation g/h

References

Ntziachristos and Boulter 2016. Automobile tyre and break wear and road abrasion. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2016

Examples

```
## Not run:
data(net)
data(pc_profile)
pc_week <- temp_fact(net$ldv[1:10] + net$hdv[1:10], pc_profile[, 1])
df <- netspeed(pc_week, net$ps[1:10], net$ffs[1:10],
              net$capacity[1:10], net$lkm[1:10], alpha = 1)
ef <- ef_wear(wear = "tyre", type = "PC", pol = "PM10", speed = df)
emi <- emis_wear(veh = age_ldv(net$ldv[1:10], name = "VEH"),
                lkm = net$lkm[1:10], ef = ef, speed = df,
                profile = pc_profile[, 1])

emi

## End(Not run)
```

 fe2015

Emission factors from Environmental Agency of Sao Paulo CETESB

Description

A dataset containing emission factors from CETESB and its equivalency with EURO

Usage

```
data(fe2015)
```

Format

A data frame with 288 rows and 12 variables:

Age Age of use

Year Year of emission factor

Pollutant Pollutants included: "CH4", "CO", "CO2", "HC", "N2O", "NMHC", "NOx", and "PM"

Proconve_LDV Proconve emission standard: "PP", "L1", "L2", "L3", "L4", "L5", "L6"

t_Euro_LDV Euro emission standard equivalence: "PRE_ECE", "I", "II", "III", "IV", "V"

Euro_LDV Euro emission standard equivalence: "PRE_ECE", "I", "II", "III", "IV", "V"

Proconve_HDV Proconve emission standard: "PP", "P1", "P2", "P3", "P4", "P5", "P7"

Euro_HDV Euro emission standard equivalence: "PRE", "I", "II", "III", "V"

PC_G CETESB emission standard for Passenger Cars with Gasoline (g/km)

LT CETESB emission standard for Light Trucks with Diesel (g/km)

Source

CETESB

fkm

List of functions of mileage in km fro Brazilian fleet

Description

Functions from CETESB: Antonio de Castro Bruni and Marcelo Pereira Bales. 2013. Curvas de intensidade de uso por tipo de veiculo automotor da frota da cidade de Sao Paulo This functions depends on the age of use of the vehicle

Usage

data(fkm)

Format

A data frame with 288 rows and 12 variables:

KM_PC_E25 Mileage in km of Passenger Cars using Gasoline with 25% Ethanol

KM_PC_E100 Mileage in km of Passenger Cars using Ethanol 100%

KM_PC_FLEX Mileage in km of Passenger Cars using Flex engines

KM_LCV_E25 Mileage in km of Light Commercial Vehicles using Gasoline with 25% Ethanol

KM_LCV_FLEX Mileage in km of Light Commercial Vehicles using Flex

KM_PC_B5 Mileage in km of Passenger Cars using Diesel with 5% biodiesel

KM_TRUCKS_B5 Mileage in km of Trucks using Diesel with 5% biodiesel

KM_BUS_B5 Mileage in km of Bus using Diesel with 5% biodiesel

KM_LCV_B5 Mileage in km of Light Commercial Vehicles using Diesel with 5% biodiesel

KM_SBUS_B5 Mileage in km of Small Bus using Diesel with 5% biodiesel

KM_ATRUCKS_B5 Mileage in km of Articulated Trucks using Diesel with 5% biodiesel

KM_MOTO_E25 Mileage in km of Motorcycles using Gasoline with 25% Ethanol

KM_LDV_GNV Mileage in km of Light Duty Vehicles using Natural Gas

Source

CETESB

fuel_corr	<i>Correction due Fuel effects</i>
-----------	------------------------------------

Description

Take into account the effect of better fuels on vehicles with older technology. If the ratio is less than 1, return 1. It means that it is not a degradation function.

Usage

```
fuel_corr(
  euro,
  g = c(e100 = 52, aro = 39, o2 = 0.4, e150 = 86, olefin = 10, s = 165),
  d = c(den = 840, pah = 9, cn = 51, t95 = 350, s = 400)
)
```

Arguments

euro	Character; Euro standards ("PRE", "I", "II", "III", "IV", "V", VI, "VIc")
g	Numeric; vector with parameters of gasoline with the names: e100(vol. sulphur, ppm)
d	Numeric; vector with parameters for diesel with the names: den (density at 15 Celsius degrees kg/m ³), pah (Back end distillation in Celsius degrees) and s (sulphur, ppm)

Value

A list with the correction of emission factors.

Note

This function cannot be used to account for deterioration, therefore, it is restricted to values between 0 and 1. Parameters for gasoline (g):

O2 = Oxygenates in

S = Sulphur content in ppm

ARO = Aromatics content in

OLEFIN = Olefins content in

E100 = Mid range volatility in

E150 = Tail-end volatility in

Parameters for diesel (d):

DEN = Density at 15 C (kg/m³)

S = Sulphur content in ppm

PAH = Aromatics content in

CN = Cetane number

T95 = Back-end distillation in o C.

Examples

```
## Not run:
f <- fuel_corr(euro = "I")
names(f)

## End(Not run)
```

get_project	<i>Download vein project</i>
-------------	------------------------------

Description

[get_project](#) downloads a project for running vein. The projects are available on [Github.com/atmoschem/vein/projects](https://github.com/atmoschem/vein/projects)

Usage

```
get_project(directory, case = "brasil", url)
```

Arguments

directory Character; Path to an existing or a new directory to be created.
case Character; One of of the following:

case	Description	EF
brazil or brazil_bu or brasil or brasil_bu	Bottom-up	CETESB
emislacovid	Bottom-up March 2020	CETESB
brazil_bu_csvgz	Bottom-up	CETESB+tunnel
brazil_csv	Bottom-up. Faster but heavier	CETESB
brazil_td_chem	Top-down with chemical mechanisms	CETESB
brazil_bu_chem	Bottom-up chemical mechanisms	CETESB+tunnel
brazil_bu_chem_streets	Bottom-up chemical mechanisms for streets and MUNICH	CETESB+tunnel
brazil_td_chem_im	Top-down with chemical mechanisms+IM	CETESB
brazil_bu_chem_im	Bottom-up chemical mechanisms+IM	CETESB+tunnel
brazil_bu_chem_streets_im	Bottom-up chemical mechanisms for streets and MUNICH+IM	CETESB+tunnel
sebr_cb05co2	Top-down SP, MG and RJ	CETESB+tunnel
amazon2014	Top-down Amazon	CETESB+tunnel
curitiba	Bottom-down +GTFS	CETESB+tunnel
masp2020	Bottom-down	CETESB+tunnel
ecuador_td	Top-down	EEA
ecuador_td_im	Top-down	EEA
ecuador_td_hot	Top-down	EEA
ecuador_td_hot_month	Top-down	EEA
moves_bu	Bottom-up	US/EPA MOVES
manizales_bu	Bottom-up chemical mechanisms	EEA
sebr_cb05co2_im	Top-down SP, MG and RJ IM	CETESB+tunnel
eu_bu_chem	Bottom-up chemical mechanisms	EEA 2019
eu_bu_chem_simple	Bottom-up chemical mechanisms 7 veh	EEA 2019

url String, with the URL to download VEIN project

Note

default case can be any of "brasil", "brazil", "brazil_bu", "brasil_bu", they are the same In any case, if you find any error, please, send a pull request in github.

In Sao Paulo the IM programs was functioning until 2011.

Examples

```
## Not run:
#do not run
get_project("awesomcity")

## End(Not run)
```

GriddedEmissionsArray *Construction function for class "GriddedEmissionsArray"*

Description

GriddedEmissionsArray returns a transformed object with class "EmissionsArray" with 4 dimensions.

Usage

```
GriddedEmissionsArray(x, ..., cols, rows, times = ncol(x), rotate = "default")

## S3 method for class 'GriddedEmissionsArray'
print(x, ...)

## S3 method for class 'GriddedEmissionsArray'
summary(object, ...)

## S3 method for class 'GriddedEmissionsArray'
plot(x, ..., times = 1)
```

Arguments

x	Object with class "SpatialPolygonDataFrame", "sf" "data.frame" or "matrix"
...	ignored
cols	Number of columns
rows	Number of rows
times	Number of times
rotate	Character, rotate array:"default", "left", "right", "cols","rows", "both", "br", "colsbr", "rowsbr", "bothbr". br means starting a matrix byrow
object	object with class "EmissionsArray"

Value

Objects of class "GriddedEmissionsArray"

Examples

```
## Not run:
data(net)
data(pc_profile)
data(fe2015)
data(fkm)
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
         133833,138441,142682,171029,151048,115228,98664,126444,101027,
         84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
         1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
veh <- data.frame(PC_G = PC_G)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
pcw <- temp_fact(net$ldv+net$hdv, pc_profile)
speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
pckm <- units::set_units(fkm[[1]](1:24), "km")
pckma <- cumsum(pckm)
cod1 <- emis_det(po = "CO", cc = 1000, eu = "III", km = pckma[1:11])
cod2 <- emis_det(po = "CO", cc = 1000, eu = "I", km = pckma[12:24])
#vehicles newer than pre-euro
co1 <- fe2015[fe2015$Pollutant=="CO", ] #24 obs!!!
cod <- c(co1$PC_G[1:24]*c(cod1,cod2),co1$PC_G[25:nrow(co1)])
lef <- ef_ldv_scaled(co1, cod, v = "PC", t = "4S", cc = "<=1400",
                   f = "G",p = "CO", eu=co1$Euro_LDV)
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed, agemax = 41,
            profile = pc_profile, simplify = TRUE)
class(E_CO)
E_CO_STREETS <- emis_post(arr = E_CO, pollutant = "CO", by = "streets",
                        net = net, k = units::set_units(1, "1/h"))
g <- make_grid(net, 1/102.47/2, 1/102.47/2) #500m in degrees
E_CO_g <- emis_grid(spobj = E_CO_STREETS, g = g, sr= 31983)
plot(E_CO_g["V9"])
# check all
rots <- c("default", "left", "right",
         "cols","rows", "both",
         "br", "colsbr", "rowsbr", "bothbr")
oldpar <- par()
par(mfrow = c(2,5))
lg <- lapply(seq_along(rots), function(i){
  x <- GriddedEmissionsArray(E_CO_g,
                            rows = 19,
                            cols = 23,
                            times = 168,
                            rotate = rots[i])
  plot(x, main = rots[i])
})
par(mfrow = c(1,1))
```

```
## End(Not run)
```

```
grid_emis          Allocate emissions gridded emissions into streets (grid to emis street)
```

Description

`grid_emis` it is sort of the opposite of `emis_grid`. It allocates gridded emissions into streets. This function applies `emis_dist` into each grid cell using `lapply`. This function is in development and pull request are welcome.

Usage

```
grid_emis(spobj, g, top_down = FALSE, sr, pro, char, verbose = FALSE)
```

Arguments

<code>spobj</code>	A spatial dataframe of class "sp" or "sf". When class is "sp" it is transformed to "sf".
<code>g</code>	A grid with class "SpatialPolygonsDataFrame" or "sf". This grid includes the total emissions with the column "emission". If the profile is going to be used, the column 'emission' must include the sum of the emissions for each profile. For instance, if profile covers the hourly emissions, the column 'emission' must be the sum of the hourly emissions.
<code>top_down</code>	Logical; requires emissions named 'emissions' and allows to apply profile factors. If your data is hourly emissions or a spatial grid with several emissions at different hours, being each hour a column, it is better to use <code>top_down = FALSE</code> . In this way all the hourly emissions are considered, however, each hourly emissions has to have the name "V" and the number of the hour like "V1"
<code>sr</code>	Spatial reference e.g: 31983. It is required if <code>spobj</code> and <code>g</code> are not projected. Please, see http://spatialreference.org/ .
<code>pro</code>	Numeric, Matrix or data-frame profiles, for instance, <code>pc_profile</code> .
<code>char</code>	Character, name of the first letter of hourly emissions. New variables in R start with the letter "V", for your hourly emissions might start with the letter "h". This option applies when <code>top_down</code> is <code>FALSE</code> . For instance, if your hourly emissions are: "h1", "h2", "h3"... 'char' can be "h"
<code>verbose</code>	Logical; to show more info.

Note

Your gridded emissions might have flux units (mass / area / time(implicit)) You must multiply your emissions with the area to return to the original units.

Examples

```

## Not run:
data(net)
data(pc_profile)
data(fkm)
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
133833,138441,142682,171029,151048,115228,98664,126444,101027,
      84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
# Estimation for morning rush hour and local emission factors
lef <- EmissionFactorsList(ef_cetesb("CO", "PC_G"))
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef,
            profile = 1, speed = Speed(1))
E_CO_STREETS <- emis_post(arrs = E_CO, by = "streets", net = net)

g <- make_grid(net, 1/102.47/2) #500m in degrees

gCO <- emis_grid(spobj = E_CO_STREETS, g = g)
gCO$emission <- gCO$V1
area <- sf::st_area(gCO)
area <- units::set_units(area, "km^2") #Check units!
gCO$emission <- gCO$emission*area
#
\dontrun{
#do not run
library(osmdata)
library(sf)
osm <- osmdata_sf(
  add_osm_feature(
    opq(bbox = st_bbox(gCO)),
    key = 'highway')$osm_lines[, c("highway")]
st <- c("motorway", "motorway_link", "trunk", "trunk_link",
"primary", "primary_link", "secondary", "secondary_link",
"tertiary", "tertiary_link")
osm <- osm[osm$highway %in% st, ]
plot(osm, axes = T)
# top_down requires name `emissions` into gCO`
xnet <- grid_emis(osm, gCO, top_down = TRUE)
plot(xnet, axes = T)
# bottom_up requires that emissions are named `V` plus the hour like `V1`
xnet <- grid_emis(osm, gCO,top_down= FALSE)
plot(xnet["V1"], axes = T)
}

## End(Not run)

```

Description

invcop help to copy and zip projects

Usage

```
invcop(  
  in_name = getwd(),  
  out_name,  
  all = FALSE,  
  main = TRUE,  
  ef = TRUE,  
  est = TRUE,  
  network = TRUE,  
  veh_rds = FALSE,  
  veh_csv = TRUE,  
  zip = TRUE  
)
```

Arguments

in_name	Character; Name of current project.
out_name	Character; Name of output project.
all	Logical; copy ALL (and for once) or not.
main	Logical; copy or not.
ef	Logical; copy or not.
est	Logical; copy or not.
network	Logical; copy or not.
veh_rds	Logical; copy or not.
veh_csv	Logical; copy or not.
zip	Logical; zip or not.

Value

emission estimation g/h

Note

This function was created to copy and zip project without the emis.

Examples

```
## Not run:  
# Do not run  
  
## End(Not run)
```

inventory	<i>Inventory function.</i>
-----------	----------------------------

Description

inventory produces an structure of directories and scripts in order to run vein. It is required to know the vehicular composition of the fleet.

Usage

```
inventory(
  name,
  vehcomp = c(PC = 1, LCV = 1, HGV = 1, BUS = 1, MC = 1),
  show.main = FALSE,
  scripts = TRUE,
  show.dir = FALSE,
  show.scripts = FALSE,
  clear = TRUE,
  rush.hour = FALSE,
  showWarnings = FALSE
)
```

Arguments

name	Character, path to new main directory for running vein. NO BLANK SPACES
vehcomp	Vehicular composition of the fleet. It is required a named numerical vector with the names "PC", "LCV", "HGV", "BUS" and "MC". In the case that there are no vehicles for one category of the composition, the name should be included with the number zero, for example, PC = 0. The maximum number allowed is 99 per category.
show.main	Logical; Do you want to see the new main.R file?
scripts	Logical Do you want to generate or no R scripts?
show.dir	Logical value for printing the created directories.
show.scripts	Logical value for printing the created scripts.
clear	Logical value for removing recursively the directory and create another one.
rush.hour	Logical, to create a template for morning rush hour.
showWarnings	Logical, showWarnings?

Value

Structure of directories and scripts for automating the compilation of vehicular emissions inventory. The structure can be used with another type of sources of emissions. The structure of the directories is: daily, ef, emi, est, images, network and veh. This structure is a suggestion and the user can use another. ' ef: it is for storing the emission factors data-frame, similar to data(fe2015) but including one column for each of the categories of the vehicular composition. For instance, if PC = 5, there

should be 5 columns with emission factors in this file. If LCV = 5, another 5 columns should be present, and so on.

emi: Directory for saving the estimates. It is suggested to use .rds extension instead of .rda.

est: Directory with subdirectories matching the vehicular composition for storing the scripts named input.R.

images: Directory for saving images.

network: Directory for saving the road network with the required attributes. This file will include the vehicular flow per street to be used by age* functions.

veh: Directory for storing the distribution by age of use of each category of the vehicular composition. Those are data-frames with number of columns with the age distribution and number of rows as the number of streets. The class of these objects is "Vehicles". Future versions of vein will generate Vehicles objects with the explicit spatial component.

The name of the scripts and directories are based on the vehicular composition, however, there is included a file named main.R which is just an R script to estimate all the emissions. It is important to note that the user must add the emission factors for other pollutants. Also, this function creates the scripts input.R where the user must specify the inputs for the estimation of emissions of each category. Also, there is a file called traffic.R to generate objects of class "Vehicles". The user can rename these scripts.

Examples

```
## Not run:
name = file.path(tempdir(), "YourCity")
inventory(name = name)

## End(Not run)
```

long_to_wide

Transform data.frame from long to wide format

Description

`long_to_wide` transform data.frame from long to wide format

Usage

```
long_to_wide(
  df,
  column_with_new_names = names(df)[1],
  column_with_data = "emission",
  column_fixed,
  net
)
```


Arguments

df data.frame with three column.
 column_with_new_names Character, column that has new column names
 column_with_data Character column with data
 column_fixed Character, column that will remain fixed
 net To return a sf

Value

wide data.frame.

See Also

[emis_hot_td](#) [emis_cold_td](#) [wide_to_long](#)

Examples

```
## Not run:
df <- data.frame(pollutant = rep(c("CO", "propadiene", "NO2"), 10),
  emission = vein::Emissions(1:30),
  region = rep(letters[1:2], 15))
df
long_to_wide(df)
long_to_wide(df, column_fixed = "region")

## End(Not run)
```

<code>make_grid</code>	<i>Creates rectangular grid for emission allocation</i>
------------------------	---

Description

`make_grid` creates a sf grid of polygons. The spatial reference is taken from the spatial object.

Usage

```
make_grid(spobj, width, height = width, polygon, crs = 4326, ...)
```

Arguments

spobj A spatial object of class sp or sf.
 width Width of grid cell. It is recommended to use projected values.
 height Height of grid cell.
 polygon Deprecated! [make_grid](#) returns only sf grid of polygons.

crs	coordinate reference system in numeric format from http://spatialreference.org/ to transform/project spatial data using <code>sf::st_transform</code> . The default value is 4326
...	ignored

Value

A grid of polygons class 'sf'

Examples

```
## Not run:
data(net)
grid <- make_grid(net, width = 0.5/102.47) #500 mts
plot(grid, axes = TRUE) #class sf
# make grid now returns warnings for crs with form +init...
#grid <- make_grid(net, width = 0.5/102.47) #500 mts

## End(Not run)
```

moves_ef

MOVES emission factors

Description

`moves_ef` reads and filter MOVES data.frame of emission factors.

Usage

```
moves_ef(
  ef,
  vehicles,
  source_type_id = 21,
  process_id = 1,
  fuel_type_id = 1,
  pollutant_id = 2,
  road_type_id = 5,
  speed_bin
)
```

Arguments

ef	emission factors from <code>EmissionRates_running</code> exported from MOVES
vehicles	Name of category, with length equal to <code>fuel_type_id</code> and other with id
source_type_id	Number to identify type of vehicle as defined by MOVES.
process_id	Number to identify emission process defined by MOVES.

fuel_type_id	Number to identify type of fuel as defined by MOVES.
pollutant_id	Number to identify type of pollutant as defined by MOVES.
road_type_id	Number to identify type of road as defined by MOVES.
speed_bin	Data.frame or vector of avgSpeedBinID as defined by MOVES.

Value

EmissionFactors data.frame

Note

'decoder' shows a decoder for MOVES to identify

Examples

```
{
  data(decoder)
  decoder
}
```

moves_rpd

MOVES estimation of using rates per distance

Description

[moves_rpd](#) estimates running exhaust emissions using MOVES emission factors.

Usage

```
moves_rpd(
  veh,
  lkm,
  ef,
  fuel_type,
  speed_bin,
  profile,
  source_type_id = 21,
  fuel_type_id = 1,
  pollutant_id = 91,
  road_type_id = 5,
  process_id = 1,
  vehicle = NULL,
  vehicle_type = NULL,
  fuel_subtype = NULL,
  net,
  path_all,
  verbose = FALSE
)
```

Arguments

veh	"Vehicles" data-frame or list of "Vehicles" data-frame. Each data-frame as number of columns matching the age distribution of that type of vehicle. The number of rows is equal to the number of streets link.
lkm	Length of each link in miles
ef	emission factors from EmissionRates_running exported from MOVES
fuel_type	Data.frame of fuelSubtypeID exported by MOVES.
speed_bin	Data.frame or vector of avgSpeedBinID as defined by MOVES.
profile	Data.frame or Matrix with nrows equal to 24 and ncol 7 day of the week
source_type_id	Number to identify type of vehicle as defined by MOVES.
fuel_type_id	Number to identify type of fuel as defined by MOVES.
pollutant_id	Number to identify type of pollutant as defined by MOVES.
road_type_id	Number to identify type of road as defined by MOVES.
process_id	Number to identify type of pollutant as defined by MOVES.
vehicle	Character, type of vehicle
vehicle_type	Character, subtype of vehicle
fuel_subtype	Character, subtype of vehicle
net	Road network class sf
path_all	Character to export whole estimation. It is not recommended since it is usually too heavy.
verbose	Logical; To show more information. Not implemented yet

Value

a list with emissions at each street and data.base aggregated by categories. See `link{emis_post}`

Note

'decoder' shows a decoder for MOVES

Examples

```
{
  data(decoder)
  decoder
}
```

 moves_rpdy

MOVES estimation of using rates per distance by model year

Description

`moves_rpdy` estimates running exhaust emissions using MOVES emission factors.

Usage

```
moves_rpdy(
  veh,
  lkm,
  ef,
  source_type_id = 21,
  fuel_type_id = 1,
  pollutant_id = 91,
  road_type_id = 5,
  fuel_type,
  speed_bin,
  profile,
  vehicle,
  vehicle_type,
  fuel_subtype,
  process_id,
  net,
  path_all,
  verbose = FALSE
)
```

Arguments

veh	"Vehicles" data-frame or list of "Vehicles" data-frame. Each data-frame as number of columns matching the age distribution of that type of vehicle. The number of rows is equal to the number of streets link.
lkm	Length of each link in miles
ef	emission factors from EmissionRates_running exported from MOVES
source_type_id	Number to identify type of vehicle as defined by MOVES.
fuel_type_id	Number to identify type of fuel as defined by MOVES.
pollutant_id	Number to identify type of pollutant as defined by MOVES.
road_type_id	Number to identify type of road as defined by MOVES.
fuel_type	Data.frame of fuelSubtypeID exported by MOVES.
speed_bin	Data.frame or vector of avgSpeedBinID as defined by MOVES.
profile	Data.frame or Matrix with nrow equal to 24 and ncol 7 day of the week
vehicle	Character, type of vehicle

vehicle_type	Character, subtype of vehicle
fuel_subtype	Character, subtype of vehicle
process_id	Character, processID
net	Road network class sf
path_all	Character to export whole estimation. It is not recommended since it is usually too heavy.
verbose	Logical; To show more information. Not implemented yet

Value

a list with emissions at each street and data.base aggregated by categories. See [link{emis_post}](#)

Note

'decoder' shows a decoder for MOVES

Examples

```
{
  data(decoder)
  decoder
}
```

moves_rpdy_meta

MOVES estimation of using rates per distance by model year

Description

[moves_rpdy_meta](#) estimates running exhaust emissions using MOVES emission factors.

Usage

```
moves_rpdy_meta(
  metadata,
  lkm,
  ef,
  fuel_type,
  speed_bin,
  profile,
  agemax = 31,
  net,
  simplify = TRUE,
  verbose = FALSE
)
```

Arguments

metadata	data.frame with the metadata for a vein project for MOVES.
lkm	Length of each link in miles
ef	emission factors from EmissionRates_running exported from MOVES
fuel_type	Data.frame of fuelSubtypeID exported by MOVES.
speed_bin	Data.frame or vector of avgSpeedBinID as defined by MOVES.
profile	Data.frame or Matrix with nrow equal to 24 and ncol 7 day of the week
agemax	Integer; max age for the fleet, assuming the same for all vehicles.
net	Road network class sf
simplify	Logical, to return the whole object or processed by streets and veh
verbose	Logical; To show more information. Not implemented yet

Value

a list with emissions at each street and data.base aggregated by categories.

Note

The idea is the user enter with emissions factors by pollutant

Examples

```
{
  data(decoder)
  decoder
}
```

moves_rpdy_sf

MOVES estimation of using rates per distance by model year

Description

`moves_rpdy_sf` estimates running exhaust emissions using MOVES emission factors.

Usage

```
moves_rpdy_sf(
  veh,
  lkm,
  ef,
  speed_bin,
  profile,
  source_type_id = 21,
  vehicle = NULL,
  vehicle_type = NULL,
```

```

    fuel_subtype = NULL,
    path_all,
    verbose = FALSE
  )

```

Arguments

veh	"Vehicles" data-frame or list of "Vehicles" data-frame. Each data-frame as number of columns matching the age distribution of that type of vehicle. The number of rows is equal to the number of streets link.
lkm	Length of each link in miles
ef	emission factors from EmissionRates_running exported from MOVES filtered by sourceTypeID and fuelTypeID.
speed_bin	Data.frame or vector of avgSpeedBinID as defined by MOVES.
profile	numeric vector of normalized traffic for the morning rush hour
source_type_id	Number to identify type of vehicle as defined by MOVES.
vehicle	Character, type of vehicle
vehicle_type	Character, subtype of vehicle
fuel_subtype	Character, subtype of vehicle
path_all	Character to export whole estimation. It is not recommended since it is usually too heavy.
verbose	Logical; To show more information. Not implemented yet

Value

a list with emissions at each street and data.base aggregated by categories. See `link{emis_post}`

Note

‘decoder’ shows a decoder for MOVES

Examples

```

{
  data(decoder)
  decoder
}

```

moves_rpsy_meta *MOVES estimation of using rates per start by model year*

Description

`moves_rpsy_meta` estimates running exhaust emissions using MOVES emission factors.

Usage

```
moves_rpsy_meta(
  metadata,
  lkm,
  ef,
  fuel_type,
  profile,
  agemax = 31,
  net,
  simplify = TRUE,
  verbose = FALSE,
  colk,
  colkt = F
)
```

Arguments

metadata	data.frame with the metadata for a vein project for MOVES.
lkm	Length of each link in miles
ef	emission factors from EmissionRates_running exported from MOVES
fuel_type	Data.frame of fuelSubtypeID exported by MOVES.
profile	Data.frame or Matrix with nrow equal to 24 and ncol 7 day of the week
agemax	Integer; max age for the fleet, assuming the same for all vehicles.
net	Road network class sf
simplify	Logical, to return the whole object or processed by streets and veh
verbose	Logical; To show more information. Not implemented yet
colk	Character identifying a column in 'metadata' to multiply the emission factor
colkt	Logical, TRUE if 'colk' is used

Value

a list with emissions at each street and data.base aggregated by categories.

Note

The idea is the user enter with emissions factors by pollutant

Examples

```
{
  data(decoder)
  decoder
}
```

 moves_rpsy_sf

MOVES estimation of using rates per start by model year

Description

[moves_rpsy_sf](#) estimates running exhaust emissions using MOVES emission factors.

Usage

```
moves_rpsy_sf(
  veh,
  lkm,
  ef,
  profile,
  source_type_id = 21,
  vehicle = NULL,
  vehicle_type = NULL,
  fuel_subtype = NULL,
  net,
  path_all,
  verbose = FALSE
)
```

Arguments

veh	"Vehicles" data-frame or list of "Vehicles" data-frame. Each data-frame as number of columns matching the age distribution of that type of vehicle. The number of rows is equal to the number of streets link.
lkm	Length of each link in miles
ef	emission factors from EmissionRates_running exported from MOVES filtered by sourceTypeID and fuelTypeID.
profile	numeric vector of normalized traffic for the morning rush hour
source_type_id	Number to identify type of vehicle as defined by MOVES.
vehicle	Character, type of vehicle
vehicle_type	Character, subtype of vehicle
fuel_subtype	Character, subtype of vehicle
net	Road network class sf
path_all	Character to export whole estimation. It is not recommended since it is usually too heavy.
verbose	Logical; To show more information. Not implemented yet

Value

a list with emissions at each street and data.base aggregated by categories. See [link{emis_post}](#)

Note

'decoder' shows a decoder for MOVES

Examples

```
{
  data(decoder)
  decoder
}
```

moves_speed

Return speed bins according to US/EPA MOVES model

Description

speed_moves return an object of average speed bins as defined by US EPA MOVES. The input must be speed as miles/h (mph)

Usage

```
moves_speed(x, net)
```

Arguments

x Object with class, "sf", "data.frame", "matrix" or "numeric" with speeds in miles/h (mph)

net optional spatial dataframe of class "sf". it is transformed to "sf".

Examples

```
{
  data(net)
  net$mph <- units::set_units(net$ps, "miles/h")
  net$speed_bins <- moves_speed(net$mph)
  head(net)
  moves_speed(net["ps"])
}
```

my_age	<i>Returns amount of vehicles at each age</i>
--------	---

Description

my_age returns amount of vehicles at each age using a numeric vector.

Usage

```
my_age(
  x,
  y,
  agemax,
  name = "vehicle",
  k = 1,
  pro_street,
  net,
  verbose = FALSE,
  namerows
)
```

Arguments

x	Numeric; vehicles by street (or spatial feature).
y	Numeric or data.frame; when pro_street is not available, y must be 'numeric', else, a 'data.frame'. The names of the columns of this data.frame must be the same as the elements of pro_street and each column must have a profile of age of use of vehicle. When 'y' is 'numeric' the vehicles has the same age distribution to all streets. When 'y' is a data.frame, the distribution by age of use varies the streets.
agemax	Integer; age of oldest vehicles for that category
name	Character; of vehicle assigned to columns of dataframe.
k	Integer; multiplication factor. If its length is > 1, it must match the length of x
pro_street	Character; each category of profile for each street. The length of this character vector must be equal to the length of 'x'. The names of the data.frame 'y' must have the same content of 'pro_street'
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"
verbose	Logical; message with average age and total number of vehicles.
namerows	Any vector to be change row.names. For instance, the name of regions or streets.

Value

dataframe of age distribution of vehicles.

Note

The functions `age*` produce distribution of the circulating fleet by age of use. The order of using these functions is:

1. If you know the distribution of the vehicles by age of use, use: `my_age`
2. If you know the sales of vehicles, or (the `regis`)*better) the registry of new vehicles, use `age` to apply a survival function.
3. If you know the theoretical shape of the circulating fleet and you can use `age_ldv`, `age_hdv` or `age_moto`. For instance, you don't know the sales or registry of vehicles, but somehow you know the shape of this curve.
4. You can use/merge/transform/adapt any of these functions.

Examples

```
## Not run:
data(net)
dpc <- c(seq(1,20,3), 20:10)
PC_E25_1400 <- my_age(x = net$ldv, y = dpc, name = "PC_E25_1400")
class(PC_E25_1400)
plot(PC_E25_1400)
PC_E25_1400sf <- my_age(x = net$ldv, y = dpc, name = "PC_E25_1400", net = net)
class(PC_E25_1400sf)
plot(PC_E25_1400sf)
PC_E25_1400nsf <- sf::st_set_geometry(PC_E25_1400sf, NULL)
class(PC_E25_1400nsf)
yy <- data.frame(a = 1:5, b = 5:1) # perfiles por categoria de calle
pro_street <- c("a", "b", "a") # categorias de cada calle
x <- c(100,5000, 3) # vehiculos
my_age(x = x, y = yy, pro_street = pro_street)

## End(Not run)
```

net

Road network of the west part of Sao Paulo city

Description

This dataset is an `sf` class object with roads from a traffic simulation made by CET Sao Paulo, Brazil

Usage

```
data(net)
```

Format

A Spatial data.frame (`sf`) with 1796 rows and 1 variables:

ldv Light Duty Vehicles (veh/h)

hdv Heavy Duty Vehicles (veh/h)

lkm Length of the link (km)

ps Peak Speed (km/h)
ffs Free Flow Speed (km/h)
tstreet Type of street
lanes Number of lanes per link
capacity Capacity of vehicles in each link (1/h)
tmin Time for travelling each link (min)
geometry geometry

netspeed

Calculate speeds of traffic network

Description

netspeed Creates a dataframe of speeds for different hours and each link based on morning rush traffic data

Usage

```

netspeed(
  q = 1,
  ps,
  ffs,
  cap,
  lkm,
  alpha = 0.15,
  beta = 4,
  net,
  scheme = FALSE,
  dist = "km"
)
  
```

Arguments

q	Data-frame of traffic flow to each hour (veh/h)
ps	Peak speed (km/h)
ffs	Free flow speed (km/h)
cap	Capacity of link (veh/h)
lkm	Distance of link (km)
alpha	Parameter of BPR curves
beta	Parameter of BPR curves
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"
scheme	Logical to create a Speed data-frame with 24 hours and a default profile. It needs ffs and ps:
dist	String indicating the units of the resulting distance in speed. Default is units from peak speed 'ps'

00:00-06:00	ffs
06:00-07:00	average between ffs and ps
07:00-10:00	ps
10:00-17:00	average between ffs and ps
17:00-20:00	ps
20:00-22:00	average between ffs and ps
22:00-00:00	ffs

Value

dataframe speeds with units or sf.

Examples

```
{
data(net)
data(pc_profile)
pc_week <- temp_fact(net$ldv+net$hdv, pc_profile)
df <- netspeed(pc_week, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
class(df)
plot(df) #plot of the average speed at each hour, +- sd
# net$ps <- units::set_units(net$ps, "miles/h")
# net$ffs <- units::set_units(net$ffs, "miles/h")
# df <- netspeed(pc_week, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
# class(df)
# plot(df) #plot of the average speed at each hour, +- sd
# df <- netspeed(ps = net$ps, ffs = net$ffs, scheme = TRUE)
# class(df)
# plot(df) #plot of the average speed at each hour, +- sd
# dfsf <- netspeed(ps = net$ps, ffs = net$ffs, scheme = TRUE, net = net)
# class(dfsf)
# head(dfsf)
# plot(dfsf, pal = cptcity::lucky(colorRampPalette = TRUE, rev = TRUE),
# key.pos = 1, max.plot = 9)
}
```

pc_cold

Profile of Vehicle start patterns

Description

This dataset is a dataframe with percentage of hourly starts with a lapse of 6 hours with engine turned off. Data source is: Lents J., Davis N., Nikkila N., Osses M. 2004. Sao Paulo vehicle activity study. ISSRC. www.issrc.org

Usage

```
data(pc_cold)
```

Format

A data frame with 24 rows and 1 variables:

V1 24 hours profile vehicle starts for Monday

pc_profile

Profile of traffic data 24 hours 7 n days of the week

Description

This dataset is a dataframe with traffic activity normalized monday 08:00-09:00. This data is normalized at 08:00-09:00. It comes from data of toll stations near Sao Paulo City. The source is ARTESP (www.artesp.com.br)

Usage

```
data(pc_profile)
```

Format

A data frame with 24 rows and 7 variables:

V1 24 hours profile for Monday

V2 24 hours profile for Tuesday

V3 24 hours profile for Wednesday

V4 24 hours profile for Thursday

V5 24 hours profile for Friday

V6 24 hours profile for Saturday

V7 24 hours profile for Sunday

pollutants

Data.frame with pollutants names and molar mass used in VEIN

Description

This dataset also includes MIR, MOIR and EBIR is Carter SAPRC07.xls <https://www.engr.ucr.edu/~carter/SAPRC/>

Usage

```
data(pollutants)
```


Format

A data frame with 148 rows and 10 variables:

n Number for each pollutant, from 1 to 132

group1 classification for pollutants including "NMHC", "PAH", "METALS", "PM", "criteria" and "PCDD"

group2 A sub classification for pollutants including "alkenes", "alkynes", "aromatics", "alkanes", "PAH", "aldehydes", "ketones", "METALS", "PM_char", "criteria", "cycloalkanes", "NMHC", "PCDD", "PM10", "PM2.5"

pollutant 1 of the 132 pollutants covered

CAS CAS Registry Number

g_mol molar mass

MIR Maximum incremental Reactivity (gm O3 / gm VOC)

MOIR Reactivity (gm O3 / gm VOC)

EBIR Reactivity (gm O3 / gm VOC)

notes Inform some assumption for molar mass

profiles

Profile of traffic data 24 hours 7 n days of the week

Description

This dataset is a list of data-frames with traffic activity normalized monday 08:00-09:00. It comes from data of toll stations near Sao Paulo City. The source is ARTESP (www.artesp.com.br) for months January and June and years 2012, 2013 and 2014. The type of vehicles covered are PC, LCV, MC and HGV.

Usage

`data(pc_profile)`

Format

A list of data-frames with 24 rows and 7 variables:

PC_JUNE_2012 168 hours

PC_JUNE_2013 168 hours

PC_JUNE_2014 168 hours

LCV_JUNE_2012 168 hours

LCV_JUNE_2013 168 hours

LCV_JUNE_2014 168 hours

MC_JUNE_2012 168 hours

MC_JUNE_2013 168 hours
MC_JUNE_2014 168 hours
HGV_JUNE_2012 168 hours
HGV_JUNE_2013 168 hours
HGV_JUNE_2014 168 hours
PC_JANUARY_2012 168 hours
PC_JANUARY_2013 168 hours
PC_JANUARY_2014 168 hours
LCV_JANUARY_2012 168 hours
LCV_JANUARY_2013 168 hours
LCV_JANUARY_2014 168 hours
MC_JANUARY_2012 168 hours
MC_JANUARY_2014 168 hours
HGV_JANUARY_2012 168 hours
HGV_JANUARY_2013 168 hours
HGV_JANUARY_2014 168 hours

remove_units	<i>Remove units</i>
--------------	---------------------

Description

`remove_units` Remove units from sf, data.frames, matrix or units.

Usage

```
remove_units(x)
```

Arguments

x Object with class "sf", "data.frame", "matrix" or "units"

Value

"sf", "data.frame", "matrix" or numeric

Examples

```
## Not run:  
ef1 <- ef_cetesb(p = "C0", c("PC_G", "PC_FE"))  
class(ef1)  
sapply(ef1, class)  
a <- remove_units(ef1)  
  
## End(Not run)
```

speciate	<i>Speciation of emissions</i>
----------	--------------------------------

Description

speciate separates emissions in different compounds. It covers black carbon and organic matter from particulate matter. Soon it will be added more speciations

Usage

```
speciate(
  x = 1,
  spec = "bcom",
  veh,
  fuel,
  eu,
  list = FALSE,
  pmpar,
  verbose = FALSE
)
```

Arguments

x	Emissions estimation
spec	<p>The speciations are:</p> <ul style="list-style-type: none"> • "bcom": Splits PM2.5 in black carbon and organic matter. • "tyre" or "tire": Splits PM in PM10, PM2.5, PM1 and PM0.1. • "brake": Splits PM in PM10, PM2.5, PM1 and PM0.1. • "road": Splits PM in PM10 and PM2.5. • "nox": Splits NOx in NO and NO2. • "nmhc": Splits NMHC in compounds, see ef_1dv_speed. • "pmiag", "pmneu", "pmneu2": Splits PM in groups, see note below. <p>The following still available but they will be removed soon:</p> <ul style="list-style-type: none"> • "iag_racm": ethanol emissions added in hc3. • "iag" or "iag_cb05": Splits NMHC by CB05 (WRF exb05_opt1) group . • "petroiag_cb05": Splits NMHC by CB05 (WRF exb05_opt1) group . • "iag_cb05v2": Splits NMHC by CB05 (WRF exb05_opt2) group . • "neu_cb05": Splits NMHC by CB05 (WRF exb05_opt2) group alternative. • "petroiag_cb05v2": Splits NMHC by CB05 (WRF exb05_opt2) group alternative.
veh	<p>Type of vehicle:</p> <ul style="list-style-type: none"> • "bcom": veh can be "PC", "LCV", HDV" or "Motorcycle". • "tyre" or "tire": not necessary.

- "brake": not necessary.
- "road": not necessary.
- "nox": veh can be "PC", "LCV", HDV" or "Motorcycle".
- "nmhc": veh can be "LDV", "HDV" or "LPG".
- ""pmiag", "pmneu", "pmneu2": not necessary.

#' The following still available but they will be removed soon:

- "iag_racm": veh accepts "veh".
- "iag" or "iag_cb05": veh accepts "veh" .
- "iag_cb05v2": veh accepts "veh" .
- "neu_cb05": veh accepts "veh" .
- "petroiag_cb05": veh accepts "veh" .
- "petroiag_cb05v2": veh accepts "veh" .

fuel

Fuel.

- "bcom": "G" or "D".
- "tyre" or "tire": not necessary.
- "brake": not necessary.
- "road": not necessary.
- "nox": "G", "D", "LPG", "E85" or "CNG".
- "nmhc": "G", "D" or "LPG".
- "pmiag", "pmneu", "pmneu2": not necessary.

#' The following still available but they will be removed soon:

- "iag_racm": "G", "E" or "D".
- "iag" or "iag_cb05": "G", "E" or "D".
- "iag_cb05v2": "G", "E" or "D".
- "neu_cb05": "G", "E" or "D".
- "petroiag_cb05": "G", "E" or "D".
- "petroiag_cb05v2": "G", "E" or "D".

eu

Emission standard

- "bcom": "G" or "D".
- "tyre" or "tire": not necessary.
- "brake": not necessary.
- "road": not necessary.
- "nox": "G", "D", "LPG", "E85" or "CNG".
- "nmhc": "PRE", "ECE_1501", "ECE_1502", "ECE_1503", "I", "II", "III", "IV", "V", "III-CDFP", "IV-CDFP", "V-CDFP", "III-ADFP", "IV-ADFP", "V-ADFP" or "OPEN_LOOP". eu can be "ALL" if spec is "nmhc" and fuel is "LPG"
- "pmiag", "pmneu", "pmneu2": not necessary.

#' The following still available but they will be removed soon:

- "iag_racm": "Exhaust", "Evaporative" or "Liquid".
- "iag" or "iag_cb05": "Exhaust", "Evaporative" or "Liquid".

	<ul style="list-style-type: none"> • "iag_cb05v2": "Exhaust", "Evaporative" or "Liquid". • "neu_cb05": "Exhaust", "Evaporative" or "Liquid". • "petroiag_cb05": "Exhaust", "Evaporative" or "Liquid". • "petroiag_cb05v2": "Exhaust", "Evaporative" or "Liquid".
list	when TRUE returns a list with number of elements of the list as the number species of pollutants
pmpar	Numeric vector for PM speciation eg: c(e_so4i = 0.0077, e_so4j = 0.0623, e_no3i = 0.00247, e_no3j = 0.01053, e_pm25i = 0.1, e_pm25j = 0.3, e_orgi = 0.0304, e_orgj = 0.1296, e_eci = 0.056, e_ecj = 0.024, h2o = 0.277) These are default values. however, when this argument is present, new values are used.
verbose	Logical to show more information

Value

dataframe of speciation in grams or mols

Note

spec **"pmiag"** speciate pm2.5 into e_so4i, e_so4j, e_no3i, e_no3j, e_mp2.5i, e_mp2.5j, e_orgi, e_orgj, e_eci, e_ecj and h2o. Reference: Rafee, S.: Estudo numerico do impacto das emissoes veiculares e fixas da cidade de Manaus nas concentracoes de poluentes atmosfericos da regio amazonica, Master thesis, Londrina: Universidade Tecnologica Federal do Parana, 2015.

specs: "neu_cb05", "pmneu" and "pmneu2" provided by Daniel Schuch, from Northeastern University

Speciation with fuels **"E25"**, **"E100"** and **"B5"** made by Prof. Leila Martins (UTFPR), represents BRAZILIAN fuel

pmiag2 pass the mass only on j fraction

References

"bcom": Ntziachristos and Zamaras. 2016. Passenger cars, light commercial trucks, heavy-duty vehicles including buses and motorcycles. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2016

"tyre", "brake" and "road": Ntziachristos and Boulter 2016. Automobile tyre and brake wear and road abrasion. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2016

"iag": Ibarra-Espinosa S. Air pollution modeling in Sao Paulo using bottom-up vehicular emissions inventories. 2017. PhD thesis. Instituto de Astronomia, Geofisica e Ciencias Atmosfericas, Universidade de Sao Paulo, Sao Paulo, page 88. Speciate EPA: <https://cfpub.epa.gov/speciate/>. : K. Sexton, H. Westberg, "Ambient hydrocarbon and ozone measurements downwind of a large automotive painting plant" Environ. Sci. Technol. 14:329 (1980).P.A. Scheff, R.A. Schauer, James J., Kleeman, Mike J., Cass, Glen R., Characterization and Control of Organic Compounds Emitted from Air Pollution Sources, Final Report, Contract 93-329, prepared for California Air Resources Board Research Division, Sacramento, CA, April 1998. 2004 NPRI National Databases as of April 25, 2006, http://www.ec.gc.ca/pdb/npri/npri_dat_rep_e.cfm. Memorandum Proposed procedures for preparing composite speciation profiles using Environment Canada s National Pollutant Release

Inventory (NPRI) for stationary sources, prepared by Ying Hsu and Randy Strait of E.H. Pechan Associates, Inc. for David Niemi, Marc Deslauriers, and Lisa Graham of Environment Canada, September 26, 2006.

Examples

```
## Not run:
# Do not run
pm <- rnorm(n = 100, mean = 400, sd = 2)
(df <- speciate(pm, veh = "PC", fuel = "G", eu = "I"))
(df <- speciate(pm, spec = "brake", veh = "PC", fuel = "G", eu = "I"))
(dfa <- speciate(pm, spec = "iag", veh = "veh", fuel = "G", eu = "Exhaust"))
(dfb <- speciate(pm, spec = "iag_cb05v2", veh = "veh", fuel = "G", eu = "Exhaust"))
(dfb <- speciate(pm, spec = "neu_cb05", veh = "veh", fuel = "G", eu = "Exhaust"))
pm <- units::set_units(pm, "g/km^2/h")
#(dfb <- speciate(as.data.frame(pm), spec = "pmiag", veh = "veh", fuel = "G", eu = "Exhaust"))
#(dfb <- speciate(as.data.frame(pm), spec = "pmneu", veh = "veh", fuel = "G", eu = "Exhaust"))
#(dfb <- speciate(as.data.frame(pm), spec = "pmneu2", veh = "veh", fuel = "G", eu = "Exhaust"))
# new
(pah <- speciate(spec = "pah", veh = "LDV", fuel = "G", eu = "I"))
(xs <- speciate(spec = "pcdd", veh = "LDV", fuel = "G", eu = "I"))
(xs <- speciate(spec = "pmchar", veh = "LDV", fuel = "G", eu = "I"))
(xs <- speciate(spec = "metals", veh = "LDV", fuel = "G", eu = "all"))

## End(Not run)
```

Speed

Construction function for class "Speed"

Description

Speed returns a transformed object with class "Speed" and units km/h. This function includes two arguments, distance and time. Therefore, it is possible to change the units of the speed to "m" to "s" for example. This function returns a data.frame with units for speed. When this function is applied to numeric vectors it adds class "units".

Usage

```
Speed(x, ..., dist = "km", time = "h")
```

```
## S3 method for class 'Speed'
print(x, ...)
```

```
## S3 method for class 'Speed'
summary(object, ...)
```

```
## S3 method for class 'Speed'
plot(
  x,
```

```

pal = "mpl_inferno",
rev = FALSE,
fig1 = c(0, 0.8, 0, 0.8),
fig2 = c(0, 0.8, 0.55, 1),
fig3 = c(0.7, 1, 0, 0.8),
mai1 = c(0.2, 0.82, 0.82, 0.42),
mai2 = c(1.3, 0.82, 0.82, 0.42),
mai3 = c(0.7, 0.62, 0.82, 0.42),
bias = 1.5,
...
)

```

Arguments

x	Object with class "data.frame", "matrix" or "numeric"
...	ignored Default is units is "km"
dist	String indicating the units of the resulting distance in speed.
time	Character to be the time units as denominator, default is "h"
object	Object with class "Speed"
pal	Palette of colors available or the number of the position
rev	Logical; to internally revert order of rgb color vectors.
fig1	par parameters for fig, par .
fig2	par parameters for fig, par .
fig3	par parameters for fig, par .
mai1	par parameters for mai, par .
mai2	par parameters for mai, par .
mai3	par parameters for mai, par .
bias	positive number. Higher values give more widely spaced colors at the high end.

Value

Constructor for class "Speed" or "units"

Note

default time unit for speed is hour

See Also

[units](#)

Examples

```

{
  data(net)
  data(pc_profile)
  speed <- Speed(net$ps)
  class(speed)
  plot(speed, type = "l")
  pc_week <- temp_fact(net$ldv+net$hdv, pc_profile)
  df <- netspeed(pc_week, net$ps, net$ffs, net$capacity, net$lkm)
  summary(df)
  plot(df)
  # changing to miles
  net$ps <- units::set_units(net$ps, "miles/h")
  net$ffs <- units::set_units(net$ffs, "miles/h")
  net$lkm <- units::set_units(net$lkm, "miles")
  df <- netspeed(pc_week, net$ps, net$ffs, net$capacity, net$lkm, dist = "miles")
  plot(df)
}

```

split_emis

*Split street emissions based on a grid***Description**

`split_emis` split street emissions into a grid.

Usage

```
split_emis(net, distance, add_column, verbose = TRUE)
```

Arguments

net	A spatial dataframe of class "sp" or "sf". When class is "sp" it is transformed to "sf" with emissions.
distance	Numeric distance or a grid with class "sf".
add_column	Character indicating name of column of distance. For instance, if distance is an sf object, and you want to add one extra column to the resulting object.
verbose	Logical, to show more information.

Examples

```

## Not run:
data(net)
g <- make_grid(net, 1/102.47/2) #500m in degrees
names(net)
dim(net)
netsf <- sf::st_as_sf(net)[, "ldv"]
x <- split_emis(net = netsf, distance = g)

```



```

dim(x)
g$A <- rep(letters, length = 20)[1:nrow(g)]
g$B <- rev(g$A)
netsf <- sf::st_as_sf(net)[, c("ldv", "hdv")]
xx <- split_emis(netsf, g, add_column = c("A", "B"))

## End(Not run)

```

temp_fact

Expansion of hourly traffic data

Description

temp_fact is a matrix multiplication between traffic and hourly expansion data-frames to obtain a data-frame of traffic at each link to every hour

Usage

```
temp_fact(q, pro, net, time)
```

Arguments

q	Numeric; traffic data per each link
pro	Numeric; expansion factors data-frames
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"
time	Character to be the time units as denominator, eg "1/h"

Value

data-frames of expanded traffic or sf.

Examples

```

## Not run:
# Do not run
data(net)
data(pc_profile)
pc_week <- temp_fact(net$ldv+net$hdv, pc_profile)
plot(pc_week)
pc_weeksf <- temp_fact(net$ldv+net$hdv, pc_profile, net = net)
plot(pc_weeksf)

## End(Not run)

```

to_latex	<i>creates a .tex a table from a data.frame</i>
----------	---

Description

`to_latex` reads a data.frame and generates a .tex table, aiming to replicate the method of tablegenerator.com

Usage

```
to_latex(df, file, caption = "My table", label = "tab:df")
```

Arguments

df	data.frame with three column.
file	Character, name of new .tex file
caption	Character caption of table
label	Character, label of table

Value

a text file with extension .tex.

See Also

[vein_notes](#) [long_to_wide](#)

Other helpers: [colplot\(\)](#), [dmonth\(\)](#), [wide_to_long\(\)](#)

Examples

```
## Not run:
df <- data.frame(pollutant = rep(c("CO", "propadiene", "NO2"), 10),
                 emission = vein::Emissions(1:30),
                 region = rep(letters[1:2], 15))

df
long_to_wide(df)
(df2 <- long_to_wide(df, column_fixed = "region"))
to_latex(df2)
to_latex(long_to_wide(df, column_fixed = "region"),
file = paste0(tempfile(), ".tex"))

## End(Not run)
```

Vehicles

*Construction function for class "Vehicles"***Description**

Vehicles returns a transformed object with class "Vehicles" and units 'veh'. The type of objects supported are of classes "matrix", "data.frame", "numeric" and "array". If the object is a matrix it is converted to data.frame. If the object is "numeric" it is converted to class "units".

Usage

```
Vehicles(x, ..., time = NULL)

## S3 method for class 'Vehicles'
print(x, ...)

## S3 method for class 'Vehicles'
summary(object, ...)

## S3 method for class 'Vehicles'
plot(
  x,
  pal = "colo_lightningmccarl_into_the_night",
  rev = TRUE,
  bk = NULL,
  fig1 = c(0, 0.8, 0, 0.8),
  fig2 = c(0, 0.8, 0.55, 1),
  fig3 = c(0.7, 1, 0, 0.8),
  mai1 = c(0.2, 0.82, 0.82, 0.42),
  mai2 = c(1.3, 0.82, 0.82, 0.42),
  mai3 = c(0.7, 0.62, 0.82, 0.42),
  bias = 1.5,
  ...
)
```

Arguments

x	Object with class "Vehicles"
...	ignored
time	Character to be the time units as denominator, eg "1/h"
object	Object with class "Vehicles"
pal	Palette of colors available or the number of the position
rev	Logical; to internally revert order of rgb color vectors.
bk	Break points in sorted order to indicate the intervals for assigning the colors.
fig1	par parameters for fig, par .

fig2 par parameters for fig, [par](#).
 fig3 par parameters for fig, [par](#).
 mai1 par parameters for mai, [par](#).
 mai2 par parameters for mai, [par](#).
 mai3 par parameters for mai, [par](#).
 bias positive number. Higher values give more widely spaced colors at the high end.

Value

Objects of class "Vehicles" or "units"

Examples

```

## Not run:
lt <- rnorm(100, 300, 10)
class(lt)
vlt <- Vehicles(lt)
class(vlt)
plot(vlt)
LT_B5 <- age_hdv(x = lt, name = "LT_B5")
summary(LT_B5)
plot(LT_B5)

## End(Not run)

```

 vein_notes

Notes with sysinfo

Description

[vein_notes](#) creates a text file '.txt' for writing technical notes about this emissions inventory

Usage

```

vein_notes(
  notes,
  file = "README",
  yourname = Sys.info()["login"],
  title = "Notes for this VEIN run",
  approach = "Top Down",
  traffic = "Your traffic information",
  composition = "Your traffic information",
  ef = "Your information about emission factors",
  cold_start = "Your information about cold starts",
  evaporative = "Your information about evaporative emission factors",
  standards = "Your information about standards",
  mileage = "Your information about mileage"
)

```

Arguments

notes	Character; vector of notes.
file	Character; Name of the file. The function will generate a file with an extension '.txt'.
yourname	Character; Name of the inventor compiler.
title	Character; Title of this file. For instance: "Vehicular Emissions Inventory of Region XX, Base year XX"
approach	Character; vector of notes.
traffic	Character; vector of notes.
composition	Character; vector of notes.
ef	Character; vector of notes.
cold_start	Character; vector of notes.
evaporative	Character; vector of notes.
standards	Character; vector of notes.
mileage	Character; vector of notes.

Value

Writes a text file.

Examples

```
## Not run:  
#do not run  
a <- "delete"  
f <- vein_notes("notes", file = a)  
file.remove(f)  
  
## End(Not run)
```

vkm

Estimation of VKM

Description

vkm consists in the product of the number of vehicles and the distance driven by these vehicles in km. This function reads hourly vehicles and then extrapolates the vehicles

Usage

```
vkm(
  veh,
  lkm,
  profile,
  hour = nrow(profile),
  day = ncol(profile),
  array = TRUE,
  as_df = TRUE
)
```

Arguments

veh	Numeric vector with number of vehicles per street
lkm	Length of each link (km)
profile	Numerical or dataframe with nrows equal to 24 and ncol 7 day of the week
hour	Number of considered hours in estimation
day	Number of considered days in estimation
array	When FALSE produces a dataframe of the estimation. When TRUE expects a profile as a dataframe producing an array with dimensions (streets x hours x days)
as_df	Logical; when TRUE transform returning array in data.frame (streets x hour*days)

Value

emission estimation of vkm

Examples

```
## Not run:
# Do not run
pc <- lkm <- abs(rnorm(10,1,1))*100
pro <- matrix(abs(rnorm(24*7,0.5,1)), ncol=7, nrow=24)
vkms <- vkm(veh = pc, lkm = lkm, profile = pro)
class(vkms)
dim(vkms)
vkms2 <- vkm(veh = pc, lkm = lkm, profile = pro, as_df = FALSE)
class(vkms2)
dim(vkms2)

## End(Not run)
```

wide_to_long	<i>Transform data.frame from wide to long format</i>
--------------	--

Description

[wide_to_long](#) transform data.frame from wide to long format

Usage

```
wide_to_long(df, column_with_data = names(df), column_fixed, geometry)
```

Arguments

df	data.frame with three column.
column_with_data	Character column with data
column_fixed	Character, column that will remain fixed
geometry	To return a sf

Value

long data.frame.

See Also

[emis_hot_td](#) [emis_cold_td](#) [long_to_wide](#)

Other helpers: [colplot\(\)](#), [dmonth\(\)](#), [to_latex\(\)](#)

Examples

```
## Not run:  
data(net)  
net <- sf::st_set_geometry(net, NULL)  
df <- wide_to_long(df = net)  
head(df)  
  
## End(Not run)
```

Index

- * **Add distance units**
 - add_lkm, 4
 - add_miles, 4
- * **China**
 - ef_china, 24
- * **age**
 - age, 7
 - age_hdv, 9
 - age_ldv, 11
 - age_moto, 12
- * **cold**
 - cold_mileage, 17
 - ef_ldv_cold, 39
 - ef_ldv_cold_list, 40
- * **cumileage**
 - ef_nitro, 49
- * **datasets**
 - decoder, 19
 - fe2015, 94
 - fkm, 95
 - net, 117
 - pc_cold, 119
 - pc_profile, 120
 - pollutants, 120
 - profiles, 121
- * **deterioration**
 - emis_det, 70
- * **ef_china**
 - ef_china, 24
- * **emission**
 - ef_cetesb, 21
 - ef_china, 24
 - ef_eea, 28
 - ef_hdv_scaled, 32
 - ef_hdv_speed, 34
 - ef_im, 36
 - ef_ive, 37
 - ef_ldv_cold, 39
 - ef_ldv_cold_list, 40
 - ef_ldv_scaled, 42
 - ef_ldv_speed, 43
 - ef_local, 47
 - ef_nitro, 49
 - ef_whe, 51
 - emis_det, 70
- * **emitters**
 - ef_whe, 51
- * **factors**
 - ef_cetesb, 21
 - ef_china, 24
 - ef_eea, 28
 - ef_hdv_scaled, 32
 - ef_hdv_speed, 34
 - ef_im, 36
 - ef_ive, 37
 - ef_ldv_cold, 39
 - ef_ldv_cold_list, 40
 - ef_ldv_scaled, 42
 - ef_ldv_speed, 43
 - ef_local, 47
 - ef_nitro, 49
 - ef_whe, 51
 - emis_det, 70
- * **helpers**
 - colplot, 17
 - dmonth, 20
 - to_latex, 130
 - wide_to_long, 135
- * **high**
 - ef_whe, 51
- * **ive**
 - ef_ive, 37
- * **mileage**
 - cold_mileage, 17
 - ef_im, 36
- * **speed**
 - ef_hdv_scaled, 32
 - ef_hdv_speed, 34

- ef_ive, 37
- ef_ldv_scaled, 42
- ef_ldv_speed, 43
- * **start**
 - ef_ldv_cold_list, 40
- * **units**
 - remove_units, 122
- add_lkm, 4, 5
- add_miles, 4, 4
- add_polid, 5, 5, 92
- adt, 6, 6
- age, 7, 7, 8, 10, 12–14, 117
- age_hdv, 8, 9, 9, 10, 12–14, 117
- age_ldv, 8, 10, 11, 11, 12–14, 117
- age_moto, 8, 10, 12, 12, 13, 117
- aw, 14, 14
- celsius, 15
- check_nt, 16, 53, 68, 79
- cold_mileage, 17
- colplot, 17, 17, 20, 130, 135
- decoder, 19
- dmonth, 19, 20, 130, 135
- ef_cetesb, 21, 21, 28, 47, 48
- ef_china, 24, 24, 79, 80
- ef_eea, 28
- ef_evap, 29, 29, 63, 74
- ef_fun, 31, 31
- ef_hdv_scaled, 32, 32
- ef_hdv_speed, 34, 62, 63
- ef_im, 36, 36
- ef_ive, 37, 37
- ef_ldv_cold, 35, 39, 39, 45, 68
- ef_ldv_cold_list, 40
- ef_ldv_scaled, 42
- ef_ldv_speed, 20, 26, 43, 43, 62, 63, 80, 123
- ef_local, 47, 47
- ef_nitro, 49, 49
- ef_wear, 50, 50
- ef_whe, 51, 51
- emis, 35, 45, 52, 52
- emis_chem, 62, 62
- emis_chem2, 63, 63
- emis_cold, 65, 66
- emis_cold_td, 67, 67, 105, 135
- emis_det, 36, 70, 70
- emis_dist, 72, 72, 100
- emis_evap, 73, 73
- emis_evap2, 74
- emis_grid, 77, 77, 100
- emis_hot_td, 26, 79, 79, 105, 135
- emis_merge, 84, 84
- emis_order, 85
- emis_paved, 87
- emis_post, 84, 89
- emis_source, 91, 91
- emis_to_streets, 5, 92, 92
- emis_wear, 93
- EmissionFactors, 56
- EmissionFactorsList, 57
- Emissions, 58
- EmissionsArray, 60
- fe2015, 94
- fkm, 95
- fuel_corr, 29, 35, 40, 44, 45, 96
- get_project, 97, 97
- grid_emis, 100, 100
- GriddedEmissionsArray, 86, 98
- invcop, 101
- inventory, 103
- long_to_wide, 104, 104, 130, 135
- make_grid, 105, 105
- moves_ef, 106, 106
- moves_rpd, 107, 107
- moves_rpdy, 109, 109
- moves_rpdy_meta, 110, 110
- moves_rpdy_sf, 111, 111
- moves_rpsy_meta, 113, 113
- moves_rpsy_sf, 114, 114
- moves_speed, 115
- my_age, 8, 10, 12, 13, 116, 117
- net, 117
- netspeed, 118
- par, 18, 19, 57, 59, 127, 131, 132
- pc_cold, 119
- pc_profile, 120
- plot.EmissionFactors (EmissionFactors), 56

plot.EmissionFactorsList
 (EmissionFactorsList), 57
plot.Emissions (Emissions), 58
plot.EmissionsArray (EmissionsArray), 60
plot.GriddedEmissionsArray
 (GriddedEmissionsArray), 98
plot.Speed (Speed), 126
plot.Vehicles (Vehicles), 131
pollutants, 120
print.EmissionFactors
 (EmissionFactors), 56
print.EmissionFactorsList
 (EmissionFactorsList), 57
print.Emissions (Emissions), 58
print.EmissionsArray (EmissionsArray),
 60
print.GriddedEmissionsArray
 (GriddedEmissionsArray), 98
print.Speed (Speed), 126
print.Vehicles (Vehicles), 131
profiles, 121

remove_units, 122, 122

speciate, 35, 45, 63, 65, 123
Speed, 126
split_emis, 128, 128
summary.EmissionFactors
 (EmissionFactors), 56
summary.EmissionFactorsList
 (EmissionFactorsList), 57
summary.Emissions (Emissions), 58
summary.EmissionsArray
 (EmissionsArray), 60
summary.GriddedEmissionsArray
 (GriddedEmissionsArray), 98
summary.Speed (Speed), 126
summary.Vehicles (Vehicles), 131

temp_fact, 129
title, 18
to_latex, 19, 20, 130, 130, 135

units, 127

Vehicles, 131
vein_notes, 130, 132, 132
vkm, 133

weekly (emis_order), 85
wide_to_long, 19, 20, 105, 130, 135, 135