

Package ‘zipangu’

March 11, 2022

Title Japanese Utility Functions and Data

Version 0.3.0

Description Some data treated by the Japanese R user require unique operations and processing. These are caused by address, Kanji, and traditional year representations. 'zipangu' transforms specific to Japan into something more general one.

License MIT + file LICENSE

URL <https://uribo.github.io/zipangu/>,
<https://github.com/uribo/zipangu>

BugReports <https://github.com/uribo/zipangu/issues>

Depends R (>= 3.2)

Imports dplyr (>= 0.8.3),
lifecycle (>= 0.1.0),
lubridate (>= 1.7.4),
magrittr (>= 1.5),
memoise,
purrr (>= 0.3.3),
rlang (>= 0.4.0),
stringi (>= 1.4.3),
stringr (>= 1.4.0),
tibble (>= 2.1.3),
arabic2kansuji (>= 0.1.0),
stats

Suggests covr (>= 3.4.0),
testthat (>= 2.1.0),
scales (>= 1.1.0)

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.2

R topics documented:

convert_jdate	2
convert_jyear	3

dl_zipcode_file	4
find_date_by_wday	4
harmonize_prefecture_name	5
is_jholiday	5
is_prefecture	6
is_zipcode	7
jholiday_spec	7
jnprefs	9
kana	10
kansuji2arabic	11
label_kansuji	12
read_zipcode	13
separate_address	14
str_jconv	14
str_jnormalize	16
zipcode Spacer	17
Index	18

convert_jdate	<i>Convert Japanese date format to date object</i>
---------------	----------------------------------------------------

Description

[Maturing]

Usage

```
convert_jdate(date)
```

Arguments

date a character object.

Examples

```
convert_jdate("R3/2/27")

## [1] "2021-02-27"

convert_jdate("\u4ee4\u548c2\u5e747\u67086\u65e5")

## [1] "2020-07-06"
```

convert_jyear	<i>Convert Japanese imperial year to Anno Domini</i>
---------------	------------------------------------------------------

Description**[Maturing]****Usage**

convert_jyear(jyear)

Arguments

jyear Japanese imperial year (jyear). Kanji or Roman character

Examples

convert_jyear("R1")

[1] 2019

convert_jyear("Heisei2")

[1] 1990

convert_jyear("\u5e73\u6210\u5143\u5e74")

[1] 1989

convert_jyear(c("\u662d\u548c10\u5e74", "\u5e73\u621014\u5e74"))

[1] 1935 2002

convert_jyear(kansuji2arabic_all("\u5e73\u6210\u4e09\u5e74"))

[1] 1991

dl_zipcode_file *Download a zip-code file*

Description

[**Maturing**]

Usage

```
dl_zipcode_file(path, exdir = NULL)
```

Arguments

path	local file path or zip file URL
exdir	The directory to extract zip file. If NULL, use temporary folder.

Examples

```
## Not run:
dl_zipcode_file(path = "https://www.post.japanpost.jp/zipcode/dl/oogaki/zip/02aomori.zip")
dl_zipcode_file("https://www.post.japanpost.jp/zipcode/dl/oogaki/zip/02aomori.zip",
                exdir = getwd())

## End(Not run)
```

find_date_by_wday *Find out the date of the specific month and weekday*

Description

[**Experimental**] Get the date of the Xth the specific weekday

Usage

```
find_date_by_wday(year, month, wday, ordinal)
```

Arguments

year	numeric year
month	numeric month
wday	numeric weekday
ordinal	number of week

Value

a vector of class POSIXct

Examples

```
find_date_by_wday(2021, 1, 2, 2)
```

`harmonize_prefecture_name`*Harmonize the notation of Japanese prefecture names.*

Description**[Experimental]****Usage**`harmonize_prefecture_name(x, to)`**Arguments**

<code>x</code>	Input vector.
<code>to</code>	Option. Whether to use longer ("long") or shorter ("short") prefectures.

Details

Convert with and without terminal notation, respectively.

- long option, long formal name
- Use the short option to omit the trailing characters

Examples

```
x <- c("\u6771\u4eac\u90fd", "\u5317\u6d77\u9053", "\u6c96\u7e04\u770c")
harmonize_prefecture_name(x, to = "short")
x <- c("\u6771\u4eac", "\u5317\u6d77\u9053", "\u6c96\u7e04")
harmonize_prefecture_name(x, to = "long")
```

`is_jholiday`*Is x a public holidays in Japan?*

Description**[Experimental]** Whether it is a holiday defined by Japanese law (enacted in 1948)**Usage**`is_jholiday(date)`**Arguments**

<code>date</code>	a vector of POSIXt , numeric or character objects
-------------------	-------------------------------------------------------------------

Details

Holiday information refers to data published as of December 21, 2020. Future holidays are subject to change.

Value

TRUE if x is a public holidays in Japan, FALSE otherwise.

Examples

```
is_jholiday("2021-01-01")
```

```
## [1] TRUE
```

```
is_jholiday("2018-12-23")
```

```
## [1] TRUE
```

```
is_jholiday("2019-12-23")
```

```
## [1] FALSE
```

is_prefecture

Check correctly prefecture names

Description

[Stable]

Usage

```
is_prefecture(x)
```

Arguments

x Input vector.

Details

Check if the string is a prefectural string. If it contains the name of the prefecture and other strings (e.g. city name), it returns FALSE.

Value

logical

Examples

```
is_prefecture("\u6771\u4eac\u90fd")
```

```
is_prefecture(c("\u6771\u4eac", "\u4eac\u90fd", "\u3064\u304f\u3070"))
```

`is_zipcode`*Test zip-code*

Description**[Experimental]****Usage**`is_zipcode(x)`**Arguments**

<code>x</code>	Zip-code. Number or character. Hyphens may be included, but the input must contain a 7-character number.
----------------	----------------------------------------------------------------------------------------------------------

Value

A logical vector.

Examples

```
is_zipcode(7000027)
is_zipcode("700-0027")
```

`jholiday_spec`*Public holidays in Japan*

Description**[Experimental]****Usage**`jholiday_spec(year, name, lang = "en")``jholiday(year, lang = "en")`**Arguments**

<code>year</code>	numeric years after 1949. If NA supplied, <code>jholiday_spec</code> returns NA respectively. On the other hand, <code>jholiday</code> always omits any NA values.
<code>name</code>	holiday names. If this argument is not the same length of year, the first element will be recycled.
<code>lang</code>	switch for turning values to "en" or "jp".

Details

Holiday information refers to data published as of December 21, 2020. Future holidays are subject to change.

Examples

```
jholiday_spec(2019, "Sports Day")
```

```
## [1] "2019-10-14"
```

```
jholiday_spec(2021, "Sports Day")
```

```
## [1] "2021-07-23"
```

List of a specific year holidays

```
jholiday(2021, "en")
```

```
## $`New Year's Day`
```

```
## [1] "2021-01-01"
```

```
##
```

```
## $`Coming of Age Day`
```

```
## [1] "2021-01-11"
```

```
##
```

```
## $`Foundation Day`
```

```
## [1] "2021-02-11"
```

```
##
```

```
## $`The Emperor's Birthday`
```

```
## [1] "2021-02-23"
```

```
##
```

```
## $`Vernal Equinox Day`
```

```
## [1] "2021-03-20"
```

```
##
```

```
## $`Showa Day`
```

```
## [1] "2021-04-29"
```

```
##
```

```
## $`Constitution Memorial Day`
```

```
## [1] "2021-05-03"
```

```
##
```

```
## $`Greenery Day`
```

```
## [1] "2021-05-04"
```

```
##
```

```
## $`Children's Day`
```

```
## [1] "2021-05-05"
```

```
##
```

```
## $`Marine Day`
```

```
## [1] "2021-07-22"
```

```
##
```

```
## $`Sports Day`
```

```
## [1] "2021-07-23"
```

```
##
```

```
## $`Mountain Day`
```

```
## [1] "2021-08-08"
```

```
##
```

```
## $`Respect for the Aged Day`
```

```
## [1] "2021-09-20"
```

```
##
```



```
## `$`Autumnal Equinox Day`  
## [1] "2021-09-23"  
##  
## `$`Culture Day`  
## [1] "2021-11-03"  
##  
## `$`Labour Thanksgiving Day`  
## [1] "2021-11-23"
```

References

Public Holiday Law <https://www8.cao.go.jp/chosei/shukujitsu/gaiyou.html>, <https://elaws.e-gov.go.jp/document?lawid=323AC1000000178>

jpnprefs

Prefectural informations in Japan

Description

Prefectures dataset.

Usage

```
jpnprefs
```

Format

A tibble with 47 rows 5 variables:

- jis_code: jis code
- prefecture_kanji: prefecture names
- prefecture: prefecture names
- region: region
- major_island:

Examples

```
jpnprefs
```

`kana`*Create kana vector*

Description

[Experimental] Generates a vector consisting of the elements of kana. Options exist for the inclusion of several elements.

Usage

```
kana(type, ...)
```

```
hiragana(  
  core = TRUE,  
  dakuon = FALSE,  
  handakuon = FALSE,  
  kogaki = FALSE,  
  historical = FALSE  
)
```

```
katakana(  
  core = TRUE,  
  dakuon = FALSE,  
  handakuon = FALSE,  
  kogaki = FALSE,  
  historical = FALSE  
)
```

Arguments

`type` "hiragana" ("hira") or "katakana" ("kata")

`...` Arguments passed on to [hiragana](#)

`core` is include core kana characters.

`dakuon` e.g. ga, gi, gu, ge, go

`handakuon` e.g. pa, pi, pu, pe, po

`kogaki` small character

`historical` old style

Examples

```
kana(type = "hira", core = TRUE)  
kana(type = "hira", core = TRUE, handakuon = TRUE)
```

kansuji2arabic	<i>Convert kansuji character to arabic</i>
----------------	--------------------------------------------

Description

[Experimental] Converts a given Kansuji element such as Ichi (1) and Nana (7) to an Arabic. `kansuji2arabic_all()` converts only Kansuji in the string. `kansuji2arabic_num()` convert kansuji that contain the positions (e.g. Hyaku, Sen, etc) with the numbers represented by kansuji. `kansuji2arabic_str()` converts kansuji in a string to numbers represented by kansuji while retaining the non-kansuji characters.

Usage

```
kansuji2arabic(str, convert = TRUE, .under = Inf)

kansuji2arabic_all(str, ...)

kansuji2arabic_num(str, consecutive = c("convert", "non"), ...)

kansuji2arabic_str(
  str,
  consecutive = c("convert", "non"),
  widths = c("all", "halfwidth"),
  ...
)
```

Arguments

<code>str</code>	Input vector.
<code>convert</code>	If FALSE, will return as numeric. The default value is TRUE, and numeric values are treated as strings.
<code>.under</code>	Number scale to be converted. The default value is infinity.
<code>...</code>	Other arguments to carry over to <code>kansuji2arabic()</code>
<code>consecutive</code>	If you select "convert", any sequence of 1 to 9 kansuji will be replaced with Arabic numerals. If you select "non", any sequence of 1-9 kansuji will not be replaced by Arabic numerals.
<code>widths</code>	If you select "all", both full-width and half-width Arabic numerals are taken into account when calculating kansuji, but if you select "halfwidth", only half-width Arabic numerals are taken into account when calculating kansuji.

Value

a character or numeric.

Examples

```
kansuji2arabic("\u4e00")
kansuji2arabic(c("\u4e00", "\u767e"))
kansuji2arabic(c("\u4e00", "\u767e"), convert = FALSE)
# Keep Kansuji over 1000.
```

```

kansuji2arabic(c("\u4e00", "\u767e", "\u5343"), .under = 1000)
# Convert all character
kansuji2arabic_all("\u3007\u4e00\u4e8c\u4e09\u56db\u4e94\u516d\u4e03\u516b\u4e5d\u5341")
kansuji2arabic_all("\u516b\u4e01\u76ee")
# Convert kansuji that contain the positions with the numbers represented by kansuji.
kansuji2arabic_num("\u4e00\u5104\u4e8c\u5343\u4e09\u767e\u56db\u5341\u4e94\u4e07")
kansuji2arabic_num("\u4e00\u5104\u4e8c\u4e09\u56db\u4e94\u4e07\u516d\u4e03\u516b\u4e5d")
# Converts kansuji in a string to numbers represented by kansuji.
kansuji2arabic_str("\u91d1\u4e00\u5104\u4e8c\u5343\u4e09\u767e\u56db\u5341\u4e94\u4e07\u5186")
kansuji2arabic_str("\u91d1\u4e00\u5104\u4e8c\u4e09\u56db\u4e94\u4e07\u516d\u4e03\u516b\u4e5d\u5186")
kansuji2arabic_str("\u91d11\u51042345\u4e076789\u5186")

```

label_kansuji

Label numbers in Kansuji format

Description

Automatically scales and labels with the Kansuji Myriad Scale (e.g. "Man", "Oku", etc). Use [label_kansuji\(\)](#) converts the label value to either Kansuji value or a mixture of Arabic numerals and the Kansuji Scales for ten thousands, billions, and ten quadrillions. Use [label_kansuji_suffix\(\)](#) converts the label value to an Arabic numeral followed by the Kansuji Scale with the suffix.

Usage

```

label_kansuji(
  unit = NULL,
  sep = "",
  prefix = "",
  big.mark = "",
  number = c("arabic", "kansuji"),
  ...
)

```

```

label_kansuji_suffix(
  accuracy = 1,
  unit = NULL,
  sep = NULL,
  prefix = "",
  big.mark = "",
  significant.digits = FALSE,
  ...
)

```

Arguments

unit	Optional units specifier.
sep	Separator between number and Kansuji unit.
prefix	Symbols to display before value.
big.mark	Character used between every 3 digits to separate thousands.
number	If Number is arabic, it will return a mixture of Arabic and the Kansuji Myriad Scale; if Kansuji, it will return only Kansuji numerals.

... Other arguments passed on to `base::prettyNum()` or `scales::label_number()`.

accuracy A number to round to. Use (e.g.) 0.01 to show 2 decimal places of precision.

significant.digits Determines whether or not the value of accuracy is valid as a significant figure with a decimal point. The default is FALSE, in which case if accuracy is 2 and the value is 1.10, 1.1 will be displayed, but if TRUE and installed 'scales' package, 1.10 will be displayed.

Value

All `label_()` functions return a "labelling" function, i.e. a function that takes a vector `x` and returns a character vector of length(`x`) giving a label for each input value.

Examples

```
library("scales")
demo_continuous(c(1, 1e9), label = label_kansuji())
demo_continuous(c(1, 1e9), label = label_kansuji_suffix())
```

read_zipcode	<i>Read Japan post's zip-code file</i>
--------------	----------------------------------------

Description

[Experimental]

Usage

```
read_zipcode(path, type = c("oogaki", "kogaki", "roman", "jigyosyo"))
```

Arguments

path local file path or zip file URL

type Input file type, one of "oogaki", "kogaki", "roman", "jigyosyo"

Details

Reads zip-code data in csv format provided by japan post group and parse it as a data.frame. Corresponds to the available "oogaki", "kogaki", "roman" and "jigyosyo" types. These file types must be specified by the argument.

Value

`tibble`

See Also

<https://www.post.japanpost.jp/zipcode/dl/readme.html>, <https://www.post.japanpost.jp/zipcode/dl/jigyosyo/readme.html>

Examples

```
# Input sources
read_zipcode(path = system.file("zipcode_dummy/13TOKYO_oogaki.CSV", package = "zipangu"),
             type = "oogaki")
read_zipcode(system.file("zipcode_dummy/13TOKYO_kogaki.CSV", package = "zipangu"),
             "oogaki")
read_zipcode(system.file("zipcode_dummy/KEN_ALL_ROME.CSV", package = "zipangu"),
             "roman")
read_zipcode(system.file("zipcode_dummy/JIGYOSYO.CSV", package = "zipangu"),
             "jigyosyo")
## Not run:
# Or directly from a URL
read_zipcode("https://www.post.japanpost.jp/zipcode/dl/jigyosyo/zip/jigyosyo.zip")

## End(Not run)
```

separate_address	<i>Separate address elements</i>
------------------	----------------------------------

Description

[Experimental] Parses and decomposes address string into elements of prefecture, city, and lower address.

Usage

```
separate_address(str)
```

Arguments

str Input vector. address strings.

Value

A list of elements that make up an address.

Examples

```
separate_address("\u5317\u6d77\u9053\u672d\u5e4c\u5e02\u4e2d\u592e\u533a")
```

str_jconv	<i>Converts the kind of string used as Japanese</i>
-----------	-----------------------------------------------------

Description

[Stable]

Usage

```

str_jconv(str, fun, to)

str_conv_hirakana(str, to = c("hiragana", "katakana"))

str_conv_zenhan(str, to = c("zenkaku", "hankaku"))

str_conv_romanhira(str, to = c("roman", "hiragana"))

str_conv_normalize(str, to = c("nfkc"))

```

Arguments

str	Input vector.
fun	convert function
to	Select the type of character to convert.

Details

Converts the types of string treat by Japanese people to each other. The following types are supported.

- Hiraganra to Katakana
- Zenkaku to Hankaku
- Latin (Roman) to Hiragana

See Also

These functions are powered by the stringi package's [stri_trans_general\(\)](#).

Examples

```

str_jconv("\u30a2\u30a4\u30a6\u30a8\u30aa", str_conv_hirakana, to = "hiragana")
str_jconv("\u3042\u3044\u3046\u3048\u304a", str_conv_hirakana, to = "katakana")
str_jconv("\uff41\uff10", str_conv_zenhan, "hankaku")
str_jconv("\uff76\uff9e\uff6f", str_conv_zenhan, "zenkaku")
str_jconv("\u30a2\u30a4\u30a6\u30a8\u30aa", str_conv_romanhira, "roman")
str_jconv("\u2460", str_conv_normalize, "nfkc")
str_conv_hirakana("\u30a2\u30a4\u30a6\u30a8\u30aa", to = "hiragana")
str_conv_hirakana("\u3042\u3044\u3046\u3048\u304a", to = "katakana")
str_conv_zenhan("\uff41\uff10", "hankaku")
str_conv_zenhan("\uff76\uff9e\uff6f", "zenkaku")
str_conv_romanhira("aiueo", "hiragana")
str_conv_romanhira("\u3042\u3044\u3046\u3048\u304a", "roman")
str_conv_normalize("\u2460", "nfkc")

```

zipcode_spacer	<i>Insert and remove zip-code connect character</i>
----------------	-----------------------------------------------------

Description

[Maturing] Inserts a hyphen as a delimiter in the given zip-code string. Or exclude the hyphen.

Usage

```
zipcode_spacer(x, remove = FALSE)
```

Arguments

x	Zip-code. Number or character. Hyphens may be included, but the input must contain a 7-character number.
remove	Default is FALSE. If TRUE, remove the hyphen.

Examples

```
zipcode_spacer(7000027)
zipcode_spacer("305-0053")
zipcode_spacer("305-0053", remove = TRUE)
```

Index

* **datasets**
 jpnprefs, 9

base::prettyNum(), 13

convert_jdate, 2
convert_jyear, 3

dl_zipcode_file, 4

find_date_by_wday, 4

harmonize_prefecture_name, 5
hiragana, 10
hiragana(kana), 10

is_jholiday, 5
is_prefecture, 6
is_zipcode, 7

jholiday(jholiday_spec), 7
jholiday_spec, 7
jpnprefs, 9

kana, 10
kansuji2arabic, 11
kansuji2arabic(), 11
kansuji2arabic_all(kansuji2arabic), 11
kansuji2arabic_all(), 11
kansuji2arabic_num(kansuji2arabic), 11
kansuji2arabic_num(), 11
kansuji2arabic_str(kansuji2arabic), 11
kansuji2arabic_str(), 11
katakana(kana), 10

label_kansuji, 12
label_kansuji(), 12
label_kansuji_suffix(label_kansuji), 12
label_kansuji_suffix(), 12

POSIXt, 5

read_zipcode, 13

scales::label_number(), 13
separate_address, 14
str_conv_hirakana(str_jconv), 14
str_conv_normalize(str_jconv), 14
str_conv_romanhira(str_jconv), 14
str_conv_zenhan(str_jconv), 14
str_jconv, 14
str_jnormalize, 16
stri_trans_general(), 15

tibble, 13

zipcode_spacer, 17